

Technical data sheet



Product: 5700, 5702

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: KLEBEBAND

Article group: EINSEITIG

Download: 07.08.2025

SAFETY STRIPES TAPES 5700, 5702

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708

3M

Safety Stripe Tapes

5700 • 5702

Technical Data

Product Description 3M™ Safety Stripe Tapes are durable vinyl tapes used to identify and mark traffic areas and physical hazards.

Product Construction	Backing	Adhesive	Color	Standard Roll Length
	Vinyl (transparent with stripes printed on underside)	Rubber	3M™ Safety Strip Tape 5700 - black/white 3M™ Safety Strip Tape 5702 - black/yellow	36 yds. (33 m)
Standard Widths Available: Contact your authorized 3M distributor or 3M sales representative.				

Typical Physical Properties	Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.		
			ASTM Test Method
Adhesion to Steel:	19 oz./in. width (21 N/100 mm)		D-3330
Tensile Strength at Break:	15 lbs./in. width (260 N/100 mm)		D-3759
Elongation at Break:	170%		D-3759
Backing Thickness:	4.2 mils (0.11 mm)		D-3652
Total Tape Thickness:	5.4 mils (0.14 mm)		D-3652
Temperature Use Range:	40° to 170°F (4° to 77°C)		

Features	<ul style="list-style-type: none">• Resists most common solvents, but care must be taken to avoid ketones, esters and chlorinated hydrocarbons which may cause backing to swell or degrade in the intended product application.• Avoid using on highly plasticized materials which may result in adhesive softening and subsequent adhesion failure of tape.• Best results are attained when applied to a clean, dry surface at temperatures between 60° to 80°F (16° to 27°C).
-----------------	---

Application Ideas	<ul style="list-style-type: none">• Excellent for many lane and safety marking applications.• Helps identify hazard areas.
--------------------------	---

3M™ Safety Strip Tapes

5700 • 5702

Storage	Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.
Shelf Life	To obtain best performance, use this product within 18 months from date of manufacture.
Product Use	All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.
Warranty and Limited Remedy	Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.
Limitation of Liability	Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



Industrial Business Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 70-0709-4893-3 (2001/6/05)