Security data sheet



Product:	PLUS SCHNELLFEST
Manufacturer:	UHU GMBH & CO KG
Product group:	KLEBSTOFF
Article group:	2-K KLEBSTOFF
Download:	01.05.2024

UHU PLUS SCHNELLFEST KART. 50ML

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH Industriestraße 15 D-75382 Althengstett Telephone: E-Mail: +49(0)7051/9297-0 Website: +49(0)7051/9297-99 www.tewipack.de

Fax

info@tewipack.de

Managing director: Alexander Uhl, Michael Uhl HRB 330424 Amtsgericht Stuttgart 85

Bank details: Sparkasse Pforzheim Calw BLZ 666 500 Konto 17 787

Commerzbank Sindelfingen BLZ 603 400 71 Konto 8 001 166

Vereinigte Volksbank AG Böblingen BLZ 603 900 00 Konto 80 089 003

Postbank Stuttgart BLZ 600 100 70 Konto 146 294 708



62983 - UHU plus schnellf. Kart. 50ml D/F

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2021

Version number 10

Revision: 10.02.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

- · Trade name: UHU plus schnellf. Kart. 50ml D/F
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7
 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 emaill: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

- Further information obtainable from: UHU QESH • 1.4 Emergency telephone number:
- Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Warning

(Contd. on page 2) GB-EN



Printing date 18.02.2021

Version number 10

Revision: 10.02.2021

Trade name: UHU plus schnellf. Kart. 50ml D/F

	(Contd. of page 1)
Hazard-determ	nining components of labelling:
	ct: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <
700)	
Hazard statem	nents
H315 Causes s	skin irritation.
H319 Causes s	serious eye irritation.
H317 May caus	se an allergic skin reaction.
H411 Toxic to a	aquatic life with long lasting effects.
Precautionary	statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P261	Avoid breathing vapours.
P280	Wear protective gloves.
	IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P3	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container in accordance with national regulations.
Additional info	ormation:
Contains epoxy	/ constituents. May produce an allergic reaction.
2.3 Other haza	irds
Results of PB	T and vPvB assessment
PBT: Not applie	cable.
vPvB: Not appl	licable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

• Dangerous components:

Dangereae componenter		
CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy	50-100%
NLP: 500-033-5	resin (number average molecular weight \leq 700)	
Index number: 603-074-00-8	Aquatic Chronic 2, H411; 🕔 Skin Irrit. 2, H315; Eye	
Reg.nr.: 01-2119456619-26-	Irrit. 2, H319; Skin Sens. 1, H317	
XXXX		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page 3) GB-EN



Printing date 18.02.2021

Version number 10

Revision: 10.02.2021

(Contd. of page 2)

Trade name: UHU plus schnellf. Kart. 50ml D/F

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.
- **SECTION 5: Firefighting measures**
- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
- Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 10
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)



Printing date 18.02.2021

Version number 10

Revision: 10.02.2021

Trade name: UHU plus schnellf. Kart. 50ml D/F

(Contd. of page 3) 8.1 Control parameters · Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace. • Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Personal protective equipment: General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Not required. Recommended filter device for short term use: Combination filter A-P1 Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Hand protection Material : butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm) Break through time : >8h : Ethyl Vinyl Alcohol Laminate (EVAL) Material Break through time : >8h glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles

> (Contd. on page 5) GB-EN



Printing date 18.02.2021

Version number 10

Revision: 10.02.2021

(Contd. of page 4)

Trade name: UHU plus schnellf. Kart. 50ml D/F

Goggles recommended during refilling

9.1 Information on basic physical and		
 9.1 Information on basic physical and chemical properties General Information Appearance: 		
Form:	Fluid	
Colour:	Colourless	
Odour:	Amine-like	
· Odour threshold:	Not determined.	
· pH-value at 20 °C:	6	
 Change in condition Melting point/freezing point: Initial boiling point and boiling rang 	Undetermined. Je: Undetermined.	
· Flash point:	>150 °C	
· Flammability (solid, gas):	Not applicable.	
· Decomposition temperature:	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product does not present an explosion hazard.	
 Explosion limits: Lower: Upper: 	Not determined. Not determined.	
· Vapour pressure:	Not determined.	
 Density at 20 °C: Relative density Vapour density Evaporation rate 	1.16 g/cm ³ Not determined. Not determined. Not determined.	
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
 Viscosity: Dynamic at 20 °C: Kinematic: 	40000 mPas Not determined.	
· Solvent content:		
Solids content: • 9.2 Other information	100.0 % All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.	

(Contd. on page 6)

GB-EN



Printing date 18.02.2021

Version number 10

Revision: 10.02.2021

Trade name: UHU plus schnellf. Kart. 50ml D/F

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Not applicable.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

(Contd. on page 7)



Printing date 18.02.2021

Version number 10

Revision: 10.02.2021

(Contd. of page 6)

Trade name: UHU plus schnellf. Kart. 50ml D/F

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information · 14.1 UN-Number · ADR/ADN, IMDG, IATA UN3082 · 14.2 UN proper shipping name · ADR/ADN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)) · IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)), MARINE POLLUTANT ·IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)) · 14.3 Transport hazard class(es) · ADR/ADN Class 9 (M6) Miscellaneous dangerous substances and articles. (Contd. on page 8) GB-EN



Printing date 18.02.2021

Version number 10

Revision: 10.02.2021

Trade name: UHU plus schnellf. Kart. 50ml D/F

· Label	9
· IMDG, IATA	
· Class	9 Miscellaneous dangerous substances an articles.
Label	9
· 14.4 Packing group · ADR/ADN, IMDG, IATA	III
• 14.5 Environmental hazards: • Marine pollutant: • Special marking (ADR/ADN): • Special marking (IATA):	Product contains environmentally hazardou substances: reaction product: bisphenol-A (epichlorhydrin); epoxy resin (number averag molecular weight ≤ 700) Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user Hazard identification number (Kemler code EMS Number: Stowage Category	Warning: Miscellaneous dangerous substance and articles.): 90 F-A,S-F A
 14.7 Transport in bulk according to Annex I of Marpol and the IBC Code 	Not applicable.
· Transport/Additional information:	
 ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
 Transport category Tunnel restriction code 	3
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml



Printing date 18.02.2021

· UN "Model Regulation":

Version number 10

Revision: 10.02.2021

Trade name: UHU plus schnellf. Kart. 50ml D/F

(Contd. of page 8)

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION P R O D U C T : B I S P H E N O L - A -(EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT \leq 700)), 9, III

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Skin corrosion/irritationThe classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.Skin sensitisation Hazardous to the aquatic environment - long- term (chronic) aquatic hazardThe classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	 Classification according to Regulation (EC) No 1272/2008 		
	Serious eye damage/eye irritation Skin sensitisation Hazardous to the aquatic environment - long-	based on the calculation method using substance data according to Regulation (EC) No	

· Department issuing SDS: UHU QESH

Contact: UHU QESH

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 10)

GB-EN



Printing date 18.02.2021

Version number 10

Revision: 10.02.2021

(Contd. of page 9)

Trade name: UHU plus schnellf. Kart. 50ml D/F

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 • * Data compared to the previous version altered.

GB-EN



62983 - UHU plus schnellf. Kart. 50ml D/F

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.02.2021

Version number 9

Revision: 10.02.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- · Trade name: UHU plus schnellf. Kart. 50ml D/F
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- **1.3 Details of the supplier of the safety data sheet** • **Manufacturer/Supplier:** UHU GmbH & Co.KG Herrmannstraße 7 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 emaill: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

- Further information obtainable from: UHU QESH • 1.4 Emergency telephone number:
- Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:
- polymercaptane
- · Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)



Printing date 18.02.2021

Version number 9

Revision: 10.02.2021

Trade name: UHU plus schnellf. Kart. 50ml D/F

(Contd. of page 1)

P102 Keep out of reach of children.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P501 Dispose of contents/container in accordance with national regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Adhesive

Dangerous components:		
CAS: 72244-98-5 EC number: 615-735-8 Reg.nr.: 01-2120118957-46- XXXX	polymercaptane Skin Sens. 1, H317; Aquatic Chronic 3, H412	50-100%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-10%
CAS: 280-57-9 EINECS: 205-999-9	triethylenediamine ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315	1-2.5%
• Additional information: For the	he wording of the listed hazard phrases refer to section 16	Ъ.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: No special measures required.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 3) GB-EN



Printing date 18.02.2021

Version number 9

Revision: 10.02.2021

(Contd. of page 2)

Trade name: UHU plus schnellf. Kart. 50ml D/F

• 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Not required.

• 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water. • 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** No special precautions are necessary if used correctly. • **Information about fire - and explosion protection:** No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- Storage class: 10
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals. Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not required.
- Recommended filter device for short term use: Combination filter A-P1

(Contd. on page 4)



Printing date 18.02.2021

Version number 9

Revision: 10.02.2021

(Contd. of page 3)

Trade name: UHU plus schnellf. Kart. 50ml D/F

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
- glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber · **Penetration time of glove material**
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Goggles recommended during refilling

SECTION 9: Physical and chemical properties		
9.1 Information on basic physical and chemical properties		
General Information		
Appearance:		
Form:	Fluid	
Colour:	Colourless	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value at 20 °C:	11	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling rang	ge: 156 °C	
Flash point:	>100 °C	
Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not determined.	
Density at 20 °C:	1.138 g/cm ³	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
	(Contd. on page	

GB-EN



Printing date 18.02.2021

Version number 9

Revision: 10.02.2021

Trade name: UHU plus schnellf. Kart. 50ml D/F

	(Contd. of page 4)
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
 Viscosity: Dynamic at 20 °C: Kinematic: 	17500 mPas Not determined.
Solvent content:	
Solids content: 9.2 Other information	1.8 % All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

280-57-9 triethylenediamine

Oral LD50 1700 mg/kg (rat)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Not applicable.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 18.02.2021

Version number 9

Revision: 10.02.2021

(Contd. of page 5)

Trade name: UHU plus schnellf. Kart. 50ml D/F

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Harmful to aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
ADR/ADN, IMDG, IATA	not regulated	
	-	
14.2 UN proper shipping name		
ADR/ADN, IMDG, IATA	not regulated	
· 14.3 Transport hazard class(es)		
ADR/ADN, ADN, IMDG, IATA		
Class	not regulated	
· 14.4 Packing group		
ADR/ADN, IMĎG, IATA	not regulated	



Printing date 18.02.2021

Version number 9

Revision: 10.02.2021

Trade name: UHU plus schnellf. Kart. 50ml D/F

	(Contd. of page 6
 14.5 Environmental hazards: 	Not applicable.
 14.6 Special precautions for user 	Not applicable.
 14.7 Transport in bulk according to Ann of Marpol and the IBC Code 	ex II Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· UN "Model Regulation":	not regulated

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

This information is based on our present know	ledge. However, this shall not constitute a guarante
	establish a legally valid contractual relationship.
Relevant phrases H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting e	ffects.
Classification according to Regulation (EC)	No 1272/2008
Skin sensitisation	The classification of the mixture is generally
Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
 Department issuing SDS: UHU QESH Contact: UHU QESH Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandise International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and L EINECS: European Inventory of Existing Commercial Cher ELINCS: European List of Notified Chemical Substances 	
ELINCS. European List of Notified Chemical Substances	(Contd. on page
	Gi



Printing date 18.02.2021

Version number 9

Revision: 10.02.2021

(Contd. of page 7)

GB-EN

Trade name: UHU plus schnellf. Kart. 50ml D/F

CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 * * Data compared to the previous version altered.