Security data sheet



Product:	PLUS ENDFEST 300
Manufacturer:	UHU GMBH & CO KG
Product group:	KLEBSTOFF
Article group:	2-K KLEBSTOFF
Download:	28.04.2024

UHU PLUS ENDFEST 300 HARS 915G

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH Industriestraße 15 D-75382 Althengstett Telephone: E-Mail: +49(0)7051/9297-0 Website: +49(0)7051/9297-99 www.tewipack.de

Fax

info@tewipack.de

Managing director: Alexander Uhl, Michael Uhl HRB 330424 Amtsgericht Stuttgart

Bank details: Sparkasse Pforzheim Calw BLZ 666 500 85 Konto 17 787 Commerzbank Sindelfingen BLZ 603 400 71 Konto 8 001 166

Vereinigte Volksbank AG Böblingen BLZ 603 900 00 Konto 80 089 003

Postbank Stuttgart BLZ 600 100 70 Konto 146 294 708



45663 - UHU PLUS ENDFEST 300 HARS 915G*3 L204

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.12.2021

Version number 14

Revision: 04.12.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- · Trade name: UHU PLUS ENDFEST 300 HARS 915G*3 L204
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7
 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 emaill: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

• Further information obtainable from: UHU QESH • 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Warning

(Contd. on page 2)

GB-EN



Printing date 04.12.2021

Version number 14

Revision: 04.12.2021

Trade name: UHU PLUS ENDFEST 300 HARS 915G*3 L204

	(Contd. of page 1)			
	mining components of labelling:			
reaction prod 700)	uct: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq			
reaction prod 700)	uct: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight \leq			
· Hazard stater	ments			
H315 Causes	skin irritation.			
H319 Causes	serious eye irritation.			
	use an allergic skin reaction.			
	aquatic life with long lasting effects.			
· Precautionar	y statements			
P101	If medical advice is needed, have product container or label at hand.			
P102	Keep out of reach of children.			
P261	Avoid breathing vapours.			
P280	Wear protective gloves.			
P302+P352	IF ON SKIN: Wash with plenty of soap and water.			
P305+P351+F	P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact			
	lenses, if present and easy to do. Continue rinsing.			
P501	Dispose of contents/container in accordance with national regulations.			
	· Additional information:			
	EUH205 Contains epoxy constituents. May produce an allergic reaction.			
	· 2.3 Other hazards			
	Results of PBT and vPvB assessment			
	• PBT: Not applicable.			
· vPvB: Not ap	plicable.			

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Adhesive

· Dangerous components:

	Dangerous components.		
	CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy	50-100%
	NLP: 500-033-5	resin (number average molecular weight \leq 700)	
	Index number: 603-074-00-8	🚯 Aquatic Chronic 2, H411; 🕔 Skin Irrit. 2, H315;	
	Reg.nr.: 01-2119456619-26-	Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	
XXXX Specific concentration limits:			
		Eye Irrit. 2; H319: C ≥ 5 %	
		Skin Irrit. 2; H315: C ≥ 5 %	
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40- xxxxreaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; Skin Sens. 1, H317		reaction product: bisphenol-F-(epichlorhydrin) epoxy	≥2.5-<10%
		resin (number average molecular weight \leq 700)	
		Škin Šens. 1, H317	
_	• Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: No special measures required.

(Contd. on page 3)

www.uhu.com



Printing date 04.12.2021

Version number 14

Revision: 04.12.2021

(Contd. of page 2)

Trade name: UHU PLUS ENDFEST 300 HARS 915G*3 L204

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- \cdot 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

- Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

- **6.4 Reference to other sections** See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Information about fire - and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions: Keep container tightly sealed.
- Storage class: 10

(Contd. on page 4) GB-EN



Printing date 04.12.2021

Version number 14

Revision: 04.12.2021

(Contd. of page 3)

Trade name: UHU PLUS ENDFEST 300 HARS 915G*3 L204

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls

• Appropriate engineering controls No further data; see item 7.

- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection: Not required.
- · Recommended filter device for short term use: Combination filter A-P1
- · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Hand protection Material	: butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm)
Break through time	: > 8 h

Material	: Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time	: > 8 h
alove material for short-term up	se / splash· (10 min <rtt <480="" min)·="" neopr<="" nitrile="" rubber,="" td=""></rtt>

glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



Printing date 04.12.2021

Version number 14

Revision: 04.12.2021

(Contd. of page 4)

Trade name: UHU PLUS ENDFEST 300 HARS 915G*3 L204

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

	properties	
· 9.1 Information on basic physical and chemical properties		
General Information		
Physical state	Fluid	
· Colour:	Colourless	
· Odour:	Weak, characteristic	
Odour threshold:	Not determined.	
• Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point and		
boiling range	Undetermined.	
Flammability	Not applicable.	
Lower and upper explosion limit		
Lower:	Not determined.	
Upper:	Not determined.	
Flash point:	>150 °C	
Auto-ignition temperature:	Product is not selfigniting.	
Decomposition temperature:	Not determined.	
pH at 20 °C	6	
Viscosity:		
Kinematic viscosity	Not determined.	
Dynamic at 20 °C:	40000 mPas	
Solubility		
water:	Not miscible or difficult to mix.	
Partition coefficient n-octanol/water (log		
value)	Not determined.	
Vapour pressure:	Not determined.	
Density and/or relative density		
Density at 20 °C:	1.15 g/cm³	
Relative density	Not determined.	
Vapour density	Not determined.	
9.2 Other information	All relevant physical data were determined for the	
	mixture. All non-determined data are no	
	measurable or not relevant for the	
A	characterization of the mixture.	
Appearance:		
Form:	Fluid	
Important information on protection of healt	(N	
and environment, and on safety.		
Explosive properties:	Product does not present an explosion hazard.	
	(Contd. on page 6	

www.uhu.com



Printing date 04.12.2021

Version number 14

Revision: 04.12.2021

Trade name: UHU PLUS ENDFEST 300 HARS 915G*3 L204

	(Contd. of page	ge :
· Solvent content:		
· Solids content:	91.0 %	
· Change in condition		
· Evaporation rate	Not determined.	
· Information with regard to physical haz	ard	
classes		
· Explosives	Void	
Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

 \cdot Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB-EN



Printing date 04.12.2021

Version number 14

Revision: 04.12.2021

Trade name: UHU PLUS ENDFEST 300 HARS 915G*3 L204

(Contd. of page 6)

• **Reproductive toxicity** Based on available data, the classification criteria are not met.

- \cdot STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- \cdot Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 8)

GB-EN



Printing date 04.12.2021

Version number 14

Revision: 04.12.2021

Trade name: UHU PLUS ENDFEST 300 HARS 915G*3 L204

(Contd. of page 7)

· 14.1 UN number or ID number · ADR/ADN, IMDG, IATA	UN3082 -
14.2 UN proper shipping name ADR/ADN	3082 ENVIRONMENTALLY HAZARDO SUBSTANCE, LIQUID, N.O.S. (reaction produ bisphenol-A-(epichlorhydrin); epoxy resin (num average molecular weight ≤ 700), reacti product: bisphenol-F-(epichlorhydrin) epoxy re
IMDG	<pre>(number average molecular weight ≤ 700)) ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (reaction produ bisphenol-A-(epichlorhydrin); epoxy resin (numl average molecular weight ≤ 700), reacti product: bisphenol-F-(epichlorhydrin) epoxy re (number average molecular weight ≤ 700 MARINE POLLUTANT</pre>
ΙΑΤΑ	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (reaction produ bisphenol-A-(epichlorhydrin); epoxy resin (numl average molecular weight ≤ 700), reacti product: bisphenol-F-(epichlorhydrin) epoxy re (number average molecular weight ≤ 700))
14.3 Transport hazard class(es)	
ADR/ADN	
Class	9 (M6) Miscellaneous dangerous substances a articles.
Label	9
	9 Miscellaneous dangerous substances a
Class	articles.
Class Label	9

GB-EN



Printing date 04.12.2021

Version number 14

Revision: 04.12.2021

Trade name: UHU PLUS ENDFEST 300 HARS 915G*3 L204

	(Contd. of page 8)
· Special marking (IATA):	Symbol (fish and tree)
 · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
· Transport/Additional information:	
 ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3
 Transport category Tunnel restriction code 	-
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION P R O D U C T : B I S P H E N O L - A - (EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700), REACTION PRODUCT: BISPHENOL-F- (EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $500\ t$
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 10)

GB-EN



Printing date 04.12.2021

Version number 14

Revision: 04.12.2021

Trade name: UHU PLUS ENDFEST 300 HARS 915G*3 L204

· REGULATION (EU) 2019/1148

(Contd. of page 9)

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.
- EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008

	· · · · · · · · · · · · · · · · · · ·	
Skin corrosion/irritation	The classification of the mixture is generally	
Serious eye damage/eye irritation	based on the calculation method using	
Skin sensitisation	substance data according to Regulation (EC) No	
Hazardous to the aquatic environment - long-	1272/2008.	
term (chronic) aquatic hazard	121212000.	
lenn (chronic) aqualic hazaru		
Department issuing SDS: UHU QESH		
• •		
Contact: UHU QESH		
 Date of previous version: 16.09.2021 		
• Version number of previous version: 13		
Abbreviations and acronyms:		
	dises dangereuses par route (European Agreement Concerning	
the International Carriage of Dangerous Goods by Road)		
IMDG: International Maritime Code for Dangerous Goods		
IATA: International Air Transport Association		
GHS: Globally Harmonised System of Classification and La		
EINECS: European Inventory of Existing Commercial Chemical Substances		
ELINCS: European List of Notified Chemical Substances		
CAS: Chemical Abstracts Service (division of the American	Chemical Society)	
PBT: Persistent, Bioaccumulative and Toxic		
vPvB: very Persistent and very Bioaccumulative		
Skin Irrit. 2: Skin corrosion/irritation – Category 2		
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2		
Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment -	long term equatio hezerd Category 2	
•	a , b ,	
** Data compared to the previous version alter		
	GB-EN	