Security data sheet



Product:	PLUS ENDFEST 300
Manufacturer:	UHU GMBH & CO KG
Product group:	KLEBSTOFF
Article group:	2-K KLEBSTOFF
Download:	27.04.2024

UHU PLUS ENDFEST 300 HARDENER 740G

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH Industriestraße 15 D-75382 Althengstett Telephone: E-Mail: +49(0)7051/9297-0 Website: +49(0)7051/9297-99 www.tewipack.de

Fax

info@tewipack.de

Managing director: Alexander Uhl, Michael Uhl HRB 330424 Calw Amtsgericht Stuttgart 85

Bank details: Sparkasse Pforzheim BLZ 666 500 Konto 17 787

Commerzbank Sindelfingen BLZ 603 400 71 Konto 8 001 166

Vereinigte Volksbank AG Böblingen BLZ 603 900 00 Konto 80 089 003

Postbank Stuttgart BLZ 600 100 70 Konto 146 294 708



45683 - UHU PLUS ENDFEST 300 HRDENER 740G*3 L221

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.02.2021

Version number 6

Revision: 10.02.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

- · Trade name: UHU PLUS ENDFEST 300 HRDENER 740G*3 L221
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7
 D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 emaill: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

• Further information obtainable from: UHU QESH

• **1.4 Emergency telephone number:** Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Danger

• Hazard-determining components of labelling: N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamin

(Contd. on page 2)



Printing date 10.02.2021

Version number 6

Revision: 10.02.2021

Trade name: UHU PLUS ENDFEST 300 HRDENER 740G*3 L221

(Contd. of page 1) amine, polyethylenepoly-,triethylenetetramine fraction · Hazard statements H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P260 Do not breathe vapours. Wear protective gloves / eye protection. P280 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P302+P352 IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/container in accordance with national regulations. 2.3 Other hazards Results of PBT and vPvB assessment · PBT: Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description: Adhesive

· Dangerous components:		
CAS: 10563-29-8 EINECS: 234-148-4	N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamin Skin Corr. 1B, H314; () Acute Tox. 4, H302; Skin Sens. 1B, H317	2.5-10%
CAS: 90640-67-8 EINECS: 292-588-2 Reg.nr.: 01-2119487919-13	amine, polyethylenepoly-,triethylenetetramine fraction Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	2.5-10%
Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

GB-EN



Printing date 10.02.2021

Version number 6

Revision: 10.02.2021

(Contd. of page 2)

Trade name: UHU PLUS ENDFEST 300 HRDENER 740G*3 L221

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions. • 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
- Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 8 A
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)



Printing date 10.02.2021

Version number 6

Revision: 10.02.2021

Trade name: UHU PLUS ENDFEST 300 HRDENER 740G*3 L221

(Contd. of page 3)

8.1 Control parameters
 Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

- Avoid contact with the eyes and skin.
- Respiratory protection: Not required.
- Recommended filter device for short term use: Combination filter A-P1
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Hand protection Material	: butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm)
Break through time	: > 8 h

Material: Ethyl Vinyl Alcohol Laminate (EVAL)Break through time: > 8 h

Break through time : > 8 h glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any

indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

(Contd. on page 5)



Printing date 10.02.2021

Version number 6

Revision: 10.02.2021

(Contd. of page 4)

Trade name: UHU PLUS ENDFEST 300 HRDENER 740G*3 L221

Goggles recommended during refilling

SECTION 9: Physical and chemi	SECTION 9: Physical and chemical properties	
 9.1 Information on basic physical and chemical properties General Information Appearance: 		
Form: Colour: Odour: Odour:	Fluid Yellow Amine-like Not determined.	
· pH-value:	Not determined.	
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined.	
· Flash point:	>100 °C	
· Flammability (solid, gas):	Not applicable.	
 Decomposition temperature: 	Not determined.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Explosive properties:	Product does not present an explosion hazard.	
 Explosion limits: Lower: Upper: 	Not determined. Not determined.	
· Vapour pressure:	Not determined.	
 Density at 20 °C: Relative density Vapour density Evaporation rate 	0.95 g/cm ³ Not determined. Not determined. Not determined.	
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
 Viscosity: Dynamic at 20 °C: Kinematic: 	32500 mPas Not determined.	
· Solvent content:		
Solids content: • 9.2 Other information	84.2 % All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.	

(Contd. on page 6)

GB-EN



Printing date 10.02.2021

Version number 6

Revision: 10.02.2021

Trade name: UHU PLUS ENDFEST 300 HRDENER 740G*3 L221

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes severe skin burns and eye damage.
- · Serious eye damage/irritation
- Causes serious eye damage.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Not applicable.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Must not reach sewage water or drainage ditch undiluted or unneutralised.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)



Printing date 10.02.2021

Version number 6

Revision: 10.02.2021

Trade name: UHU PLUS ENDFEST 300 HRDENER 740G*3 L221

· 12.6 Other adverse effects No further relevant information available.

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information	SECTION 14: Transport information	
· 14.1 UN-Number · ADR/ADN, IMDG, IATA	UN2735	
 14.2 UN proper shipping name ADR/ADN 	2735 POLYAMINES, LIQUID, CORROSIVE N.O.S. (N'-(3-aminopropyl)-N,N-dimethylpropane- 1,3-diamin)	
· IMDG, IATA	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (N' (3-aminopropyl)-N,N-dimethylpropane-1,3-diamin)	
· 14.3 Transport hazard class(es)		
· ADR/ADN		
· Class · Label	8 (C7) Corrosive substances. 8	
· IMDG, IATA		
· Class · Label	8 Corrosive substances. 8	
 14.4 Packing group ADR/ADN, IMDG, IATA 	111	
· 14.5 Environmental hazards:	Not applicable.	
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: 	Warning: Corrosive substances. 80 F-A,S-B	
	(Contd. on page 8	



Printing date 10.02.2021

Version number 6

Revision: 10.02.2021

Trade name: UHU PLUS ENDFEST 300 HRDENER 740G*3 L221

	(Contd. of page 7)
 Segregation groups Stowage Category Stowage Code 	Alkalis B SW2 Clear of living quarters.
 14.7 Transport in bulk according to Annex I of Marpol and the IBC Code 	I Not applicable.
 Transport/Additional information: Quantity limitations 	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
 ADR/ADN Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (N'-(3-AMINOPROPYL)-N, N- DIMETHYLPROPANE-1,3-DIAMIN), 8, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II
- None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

(Contd. on page 9)

GB-EN



Printing date 10.02.2021

Version number 6

Revision: 10.02.2021

(Contd. of page 8)

Trade name: UHU PLUS ENDFEST 300 HRDENER 740G*3 L221

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

<u> </u>	
Skin corrosion/irritation	The classification of the mixture is generally based on the
Serious eye damage/eye irritation	calculation method using substance data according to
Skin sensitisation	Regulation (EC) No 1272/2008.

· Department issuing SDS: UHU QESH

· Contact: UHU QESH

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

** Data compared to the previous version altered.

GB-EN