

Technical data sheet



Product: 8561

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: KLEBEBAND

Article group: OBERFLÄCHENSCHUTZFOLIE

Download: 01.07.2025

POLYURETHANE PROTECTIVE TAPE 8561

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708



Polyurethane Protective Tape

8561

Technical Datasheet

April 2010

Product Description

3M™ Polyurethane Protective Tape 8561 is made from an abrasion-resistant polyurethane elastomer that resists puncture, tearing, abrasion and erosion. 3M 8561 Tape provides a simple, easy, and fast method of protecting a surface from corrosion, abrasion, erosion and minor impact damage. 3M 8561 Tape is constructed with a long-aging, solvent-resistant, pressure-sensitive, acrylic adhesive protected with an easy-release paper liner.

3M™ Polyurethane Protective Tape 8561 is a transparent tape available with a paper liner only.

Typical Physical Properties and Performance Characteristics

Notes: 1) The following technical information and data should be considered representative or typical only and should not be used for specification purposes.
2) ASTM = American Society for Testing and Materials.
3) Metric values are listed in parenthesis.

A. Dimensions

Approximate Applied Thickness:*	0.012 inch (0.30 mm) Film 0.002 inch (0.06 mm) Adhesive 0.014 inch (0.36 mm) = Total thickness
Standard Roll Length:	36 yd (32.9 m)
Available Widths:	Minimum 1/4 inch Maximum 48 inches (0.625 cm to 122 cm)
Approximate Weight:*	0.79 lb/yd ² (428 g/m ²)

*Excludes the paper liner that is removed from the tape prior to application.

B. Typical Physical Properties and Performance Characteristics

Property	Test Method	Units	Typical Value
Tensile Strength @ Break	ASTM D882	lb/in (N/100 mm)	75 (1313)
Elongation % @ Break	ASTM D882	%	400
Peel Adhesion @ 70°F (21°C) to:			
Plate Glass	ASTM D3330 Method A 24 hour dwell	oz/in (N/100 mm)	36 (39)
Anodized Aluminum	ASTM D3330 Method A 24 hour dwell	oz/in (N/100 mm)	62 (67)
Acrylic Enamel Paint	ASTM D3330 Method A 24 hour dwell	oz/in (N/100 mm)	26 (28)
Mil-P-23377 Epoxy Primer	ASTM D3330 Method A 24 hour dwell	oz/in (N/100 mm)	42 (45)

General Information

- 3M 8561 Tape has good environmental resistance properties and has been used to isolate and protect substrates from environmental damage and corrosive elements.
- 3M 8561 Tape may be painted per 3M Technical Bulletin "3M™ Polyurethane Protective Tape, Paint Instructions" (70-0702-6358-0).

3M™ Polyurethane Protective Tape 8561

Technical Datasheet

Safety and Regulatory

- 3M™ Polyurethane Protective Tape is **100%** solids and contains no hazardous air pollutants (HAPs), volatile organic components (VOCs). Respiratory protection is not required under normal use conditions.
- Polyurethane Protective Tape meets US Federal and California regulations for landfillable materials. The product is potentially recyclable.
- Packaging materials meet US Federal and California regulations for landfillable materials and are recyclable or reusable.
- This product is considered to be an article that does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.

Shipping and Storage

No special/hazardous labeling or packaging required and no regulations for air, ground or water shipment for this product.

Keep film in a clean area, away from excessive moisture and out of direct sunlight. Store rolls in the shipping carton. Return partially used rolls to the shipping carton.

Shelf Life: Two (2) years from the date of manufacture or as expressly certified by 3M.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for health and safety information before using this product. For additional health and safety information, please visit www.3M.com/msds or call 1-800-364-3577 or (651) 737-6501.

For Additional Information

In the U.S., call toll free 1-800-235-2376, or fax 1-800-435-3082 or 651-737-2171. For U.S. Military, call 1-866-556-5714. If you are outside of the U.S., please contact your nearest 3M office or one of the following branches:

Australia 61-2-498-9711 tel 61-2-498-9710 fax	Austria 01-86686-298 tel 01-86686-229 fax	Brazil 55 19 3838-7876 tel 55 19 3838-6892 fax	Canada 800-410-6880 ext. 6018 tel 800-263-3489 fax
China 86-21-62753535 tel 86-21-62190698 fax	Denmark 45-43-480100 tel 45-43-968596 fax	France 0810-331-300 tel 30-31-6195 fax	Germany 02131-14-2344 tel 02131-14-3647 fax
Italy 02-7035-2177 tel 02-7035-2125 fax	Japan 03-3709-8245 tel 03-3709-8743 fax	Korea 02-3771-4114 tel 02-786-7429 fax	Netherlands 31-71-5-450-272 tel 31-71-5-450-280 fax
South Africa 11-922-9111 tel 11-922-2116 fax	Spain 34-91-321-6000 tel 34-91-321-6002 fax	Switzerland 01-724-9114 tel 01-724-9068 fax	United Kingdom (0) 161-237-6174 tel (0) 161-237-3371 fax

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



This product was manufactured under a 3M quality standard registered under AS9100 standards.

Aerospace and Aircraft Maintenance Department

3M Center, Building 223-1N-14
St. Paul, MN 55144-1000
1-800-235-2376
www.3M.com/aerospace

3M is a trademark of 3M Company.

Please recycle. Printed in U.S.A.
©3M 2010 (4/10) All rights reserved.
60-9700-0108-1