

Technical data sheet



Product: 8956

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: KLEBEBAND

Article group: EINSEITIG

Download: 31.08.2025

SCOTCH FILAMENT TAPE 8956

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708



Scotch™ Filament Tape 8956

Product Data Sheet

October 2009

Supersedes: December 2003

Product Description A utility packaging tape reinforced with continuous glass filaments which gives tensile strength to the tape.

Key Features The ScotchPro™ bi-axially oriented polypropylene backing provides abrasion, moisture and scuff resistance. The adhesive is formulated to adhere adequately to fiberboard surfaces.

Construction

Adhesive Type	Synthetic Rubber Resin (Hot Melt)
Backing	BOPP
Reinforcement	Glass Yarns
Total Thickness AFERA 5006	120 µm
Core size (ID)	76 mm (3")
Colour	Transparent

Performance Characteristics

Adhesion to Stainless Steel AFERA 5001	8,0 N/cm
Tensile Strength AFERA 5004	260 N/cm
Elongation at Break AFERA 5004	6 %
Static Shear AFERA 5012	2000+ minutes

Storage	Store in clean dry place. Temperature of 21 °C and 50 % relative humidity are recommended.
Shelf Life	Scotch 8956 has a shelf life of 12 months from date of dispatch by 3M.
Precautionary Information	Refer to product label and Material Safety Data Sheet for health and safety information before using the product. For information please contact your local 3M Office. www.3M.com
For Additional Information	To request additional product information see address below
Important Notice	All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications.
This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M Adrique Francophone
Société à responsabilité limitée
Au capital de 19.756.400 Dirhams
Siège Social: ZF Ksar Almajaz Bureau
6 Plateforme
Lot n°2 Immeuble 4 zénith Tanger
R.C : 74327, I.F. : 18745050

3M Gulf Limited
Ein El Mreisseh
Saint Charles City Center, 4th Floor
P.O.Box: 11-5025
Riad el Solh
Beirut 1107 2180
Lebanon

3M Minnesota Mining & Manufacturing Nigeria Limited
No 2 Sheraton Opebi Link Road
Ikeja
Lagos
Nigeria

3M Arabia, LLC
Building 24-25 3M Saudi Arabia
Zone C, Business Gate
Airport Road Riyadh
Saudi Arabia

3M Gulf (Representation Office)
Suhaim Bin Hamad St., Al Mana Towers
Tower B, 2nd Floor, Office No.4
Doha Qatar
P.O.Box 14684

3M Pakistan
Islamic Chamber of Commerce Building
ST-2/A, Block 9, KDA Scheme 5
Clifton, Karachi
Pakistan

3M Egypt
Finance Center, New Cairo
Plot 140, Banking Sector
5th settlement, Cairo
Egypt

3M Kenya Ltd.
Victoria Towers, 3rd Floor
Kilimanjaro Av, Upperhill
Kenya

3M South Africa & Sub-Saharan Africa
146A Kelvin Drive
Woodmead, Sandton
South Africa

3M Gulf Limited
Dubai Internet City
Building No. 11, 3rd Floor
U.A.E

3M Maroc
Société à responsabilité limitée
Au capital de 18.000.000 de Dirhams
Siège Social: 33
lot la colline II Sidi Maarouf – Casablanca
R.C:78517, I.F.: 1084514
Morocco