Security data sheet



Product:	PLUS ENDFEST 300
Manufacturer:	UHU GMBH & CO KG
Product group:	KLEBSTOFF
Article group:	2-K KLEBSTOFF
Download:	21.12.2024

# UHU PLUS ENDFEST 300 163G 45630

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH Industriestraße 15 D-75382 Althengstett Telephone: E-Mail: +49(0)7051/9297-0 Website: +49(0)7051/9297-99 www.tewipack.de

Fax

info@tewipack.de

Managing director: Alexander Uhl, Michael Uhl HRB 330424 Amtsgericht Stuttgart 85

Bank details: Sparkasse Pforzheim Calw BLZ 666 500 Konto 17 787

Commerzbank Sindelfingen BLZ 603 400 71 Konto 8 001 166

Vereinigte Volksbank AG Böblingen BLZ 603 900 00 Konto 80 089 003

Postbank Stuttgart BLZ 600 100 70 Konto 146 294 708



### 45639 - UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2023

Version number 28 (replaces version 27)

Revision: 31.03.2023

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

· Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
   Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7
   D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 emaill: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

#### • Further information obtainable from: UHU QESH • 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

# **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

# GHS07

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.

#### · 2.2 Label elements

### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



· Signal word Warning

(Contd. on page 2)

GB-EN



Printing date 02.04.2023

Version number 28 (replaces version 27)

Revision: 31.03.2023

### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

	(Contd. of page 1)
· Hazard-deterr	nining components of labelling:
	uct: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$
700)	······································
	uct: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$
700)	
Hazard staten	nents
H315 Causes	skin irritation.
H319 Causes	serious eye irritation.
	se an allergic skin reaction.
H411 Toxic to	aquatic life with long lasting effects.
Precautionary	/ statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P261	Avoid breathing vapours.
P280	Wear protective gloves.
	IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P	2338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container in accordance with national regulations.
Additional inf	
	ains epoxy constituents. May produce an allergic reaction.
2.3 Other haza	
	T and vPvB assessment
• PBT: Not appl	
vPvB: Not app	olicable.

# **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

# · **Description:** Adhesive

#### · Dangerous components:

	Dangerous components.		
Γ	CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy	50-100%
	NLP: 500-033-5	resin (number average molecular weight $\leq$ 700)	
	Index number: 603-074-00-8	Aquatic Chronic 2, H411; 🚸 Skin Irrit. 2, H315;	
	Reg.nr.: 01-2119456619-26-	Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	
	XXXX	Specific concentration limits:	
		Eye Irrit. 2; H319: C ≥ 5%	
		Skin Irrit. 2; H315: C ≥ 5 %	
F	CAS: 9003-36-5	reaction product: bisphenol-F-(epichlorhydrin) epoxy	≥2.5-<10%
	NLP: 500-006-8	resin (number average molecular weight $\leq$ 700)	
	Reg.nr.: 01-2119454392-40-	Aquatic Chronic 2, H411; 🚯 Skin Irrit. 2, H315;	
	XXXX	Škin Šens. 1, H317	
Additional information: For the wording of the listed hazard phrases refer to section 16.			6.

## **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

· General information: No special measures required.

(Contd. on page 3)



Printing date 02.04.2023

Version number 28 (replaces version 27)

Revision: 31.03.2023

(Contd. of page 2)

#### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

#### · After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- $\cdot$  5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

# **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

- Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

- **6.4 Reference to other sections** See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Information about fire - and explosion protection: No special measures required.

#### · 7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- $\cdot$  Further information about storage conditions: Keep container tightly sealed.
- Storage class: 10

(Contd. on page 4) GB-EN



Printing date 02.04.2023

Version number 28 (replaces version 27)

Revision: 31.03.2023

Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

• 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

# **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls

• Appropriate engineering controls No further data; see item 7.

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection: Not required.
- · Recommended filter device for short term use: Combination filter A-P1
- · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

	: butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm) : > 8 h
--	--

Material	:	Ethyl Vinyl Alcohol Laminate (EVAL)	
Break through time	:	> 8 h	
alove material for short-term us	e	/ splash: (10 min <btt <480="" min):="" nitrile="" rubber<="" td=""><td>neonr</td></btt>	neonr

glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber Nitrile rubber, NBR

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

#### Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

(Contd. on page 5)



Printing date 02.04.2023

Version number 28 (replaces version 27)

Revision: 31.03.2023

(Contd. of page 4)

### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

# · Eye/face protection



L

Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical p	properties
· 9.1 Information on basic physical and chem	ical properties
General Information	
Physical state	Fluid
· Colour:	Colourless
· Odour:	Weak, characteristic
· Odour threshold:	Not determined.
<ul> <li>Melting point/freezing point:</li> </ul>	Undetermined.
Boiling point or initial boiling point and	
boiling range	Undetermined.
· Flammability	Not applicable.
<ul> <li>Lower and upper explosion limit</li> </ul>	
· Lower:	Not determined.
· Upper:	Not determined.
Flash point:	>150 °C
Decomposition temperature:	Not determined.
pH at 20 °C	6
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	40000 mPas
· Solubility	
· water:	Not miscible or difficult to mix.
<ul> <li>Partition coefficient n-octanol/water (log</li> </ul>	
value)	Not determined.
· Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	1.15 g/cm <sup>3</sup>
Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
· Appearance:	
· Form:	Fluid
· Important information on protection of heal	th
and environment, and on safety.	
<ul> <li>Auto-ignition temperature:</li> </ul>	Product is not selfigniting.
<ul> <li>Explosive properties:</li> </ul>	Product does not present an explosion hazard.
	(Contd. on page 6)



Printing date 02.04.2023

Version number 28 (replaces version 27)

Revision: 31.03.2023

#### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

	(Contd. of page
Solvent content:	
Solids content:	91.0 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haz	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

# **SECTION 10: Stability and reactivity**

• 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity

Not applicable.

(Contd. on page 7) GB-EN

GB-EN -



45639 - UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2023

Version number 28 (replaces version 27)

Revision: 31.03.2023

#### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

(Contd. of page 6)

Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:

· Acute effects (acute toxicity, irritation and corrosivity) Not applicable.

- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards

#### · Endocrine disrupting properties

None of the ingredients is listed.

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Remark: Toxic for fish

### · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

(Contd. on page 8)



Printing date 02.04.2023

Version number 28 (replaces version 27)

Revision: 31.03.2023

(Contd. of page 7)

### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR/ADN, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR/ADN	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-A-(epichlorhydrin); epoxy resin (numbe average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
IMDG	ÈNVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)) MARINE POLLUTANT
ΙΑΤΑ	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reactio product: bisphenol-F-(epichlorhydrin) epoxy resi (number average molecular weight ≤ 700))
14.3 Transport hazard class(es)	
ADR/ADN	
Class Label	9 (M6) Miscellaneous dangerous substances an articles. 9
· IMDG, IATA	
Class	9 Miscellaneous dangerous substances an articles.
Label	9



Printing date 02.04.2023

Version number 28 (replaces version 27)

Revision: 31.03.2023

#### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

	(Contd. of page 8
· 14.4 Packing group · ADR/ADN, IMDG, IATA	111
14.5 Environmental hazards: Marine pollutant: Special marking (ADR/ADN): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
<ul> <li>14.6 Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
<ul> <li>14.7 Maritime transport in bulk according to IMO instruments</li> </ul>	Not applicable.
Transport/Additional information:	
ADR/ADN Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3
Transport category Tunnel restriction code	3 (-)
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION P R O D U C T : B I S P H E N O L - A (EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700) REACTION PRODUCT: BISPHENOL-F (EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III

# **SECTION 15: Regulatory information**

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

(Contd. on page 10)

GB-EN



Printing date 02.04.2023

Version number 28 (replaces version 27)

Revision: 31.03.2023

#### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

(Contd. of page 9)

• Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t • REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Relevant phrases

H315 Causes skin irritation.

- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

#### Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
<ul> <li>Department issuing SDS: UHU QESH</li> <li>Contact: UHU QESH</li> <li>Date of previous version: 25.10.2022</li> <li>Version number of previous version: 27</li> <li>Abbreviations and acronyms: <ul> <li>ADR: Accord relatif au transport international des marchand the International Carriage of Dangerous Goods by Road)</li> <li>IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association</li> <li>GHS: Globally Harmonised System of Classification and Lab EINECS: European Inventory of Existing Commercial Chemia ELINCS: European List of Notified Chemical Substances</li> <li>CAS: Chemical Abstracts Service (division of the American OPBT: Persistent, Bioaccumulative and Toxic</li> </ul> </li> </ul>	ical Substances
	(Conta: on page 11)

Contd. on page 11) ——— GB-EN



Printing date 02.04.2023

Version number 28 (replaces version 27)

Revision: 31.03.2023

Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

(Contd. of page 10)

vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\* Data compared to the previous version altered.



# 45639 - UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2023

Version number 15 (replaces version 14)

Revision: 18.03.2023

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

· Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Adhesive
- 1.3 Details of the supplier of the safety data sheet
   Manufacturer/Supplier: UHU GmbH & Co.KG Herrmannstraße 7
   D-77815 Bühl (Baden) Tel.:0049-(0)7223-284-0 emaill: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

- Further information obtainable from: UHU QESH
   1.4 Emergency telephone number:
- Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111 Schottland (NHS 24) 111

# **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



· Signal word Danger

• **Hazard-determining components of labelling:** N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

(Contd. on page 2)

GB-EN



Printing date 02.04.2023

Version number 15 (replaces version 14)

Revision: 18.03.2023

#### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

(Contd. of page 1) amine, polyethylenepoly-,triethylenetetramine fraction · Hazard statements H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P260 Do not breathe vapours. Wear protective gloves / eye protection. P280 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P302+P352 IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/container in accordance with national regulations. 2.3 Other hazards Results of PBT and vPvB assessment · PBT: Not applicable.

• **vPvB:** Not applicable.

### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· Description: Adhesive

· Dangerous components:			
CAS: 10563-29-8 EINECS: 234-148-4	N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine Skin Corr. 1B, H314;  Acute Tox. 4, H302; Skin Sens. 1B, H317	≥5-≤10%	
CAS: 90640-67-8 EINECS: 292-588-2 Reg.nr.: 01-2119487919-13	amine, polyethylenepoly-,triethylenetetramine fraction Skin Corr. 1B, H314; Eye Dam. 1, H318; O Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥3-<5%	
• Additional information: For the wording of the listed hazard phrases refer to section 16.			

SECTION 4: First aid measures

### · 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)



Printing date 02.04.2023

Version number 15 (replaces version 14)

Revision: 18.03.2023

(Contd. of page 2)

#### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions. • 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

# **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
- Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

- Prevent formation of aerosols.
- · Information about fire and explosion protection: Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 8 A
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

GB-FN



Printing date 02.04.2023

Version number 15 (replaces version 14)

Revision: 18.03.2023

#### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

(Contd. of page 3)

# **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- Respiratory protection: Not required.
- Recommended filter device for short term use: Combination filter A-P1
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

ne material: > 0,12 mm
: butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm)
: >8h

Material: Ethyl Vinyl Alcohol Laminate (EVAL)Break through time: > 8 hglove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber</td>Nitrile rubber, NBR

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

#### Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

(Contd. on page 5)



Printing date 02.04.2023

Version number 15 (replaces version 14)

Revision: 18.03.2023

(Contd. of page 4)

### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

# · Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

9.1 Information on basic physical and chem	ical properties
General Information	
Physical state	Fluid
Colour:	Yellow
Odour:	Amine-like
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	
boiling range	~278 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	>100 °C
Decomposition temperature:	Not determined.
рН	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic at 20 °C:	32500 mPas
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.95 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for the
	mixture. All non-determined data are no
	measurable or not relevant for the
	characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of heal	th
and environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.

www.uhu.com



Printing date 02.04.2023

Version number 15 (replaces version 14)

Revision: 18.03.2023

#### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

	(Contd. of	page
Solvent content:		
Solids content:	84.2 %	
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
• Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

# **SECTION 10: Stability and reactivity**

• 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation
- Causes severe skin burns and eye damage.
- · Serious eye damage/irritation
- Causes serious eye damage.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity

Not applicable.

(Contd. on page 7)

GB-EN



45639 - UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.04.2023

Version number 15 (replaces version 14)

Revision: 18.03.2023

#### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

(Contd. of page 6)

Based on available data, the classification criteria are not met.

• Carcinogenicity Based on available data, the classification criteria are not met.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards

#### · Endocrine disrupting properties

None of the ingredients is listed.

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

# **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 8)



Printing date 02.04.2023

Version number 15 (replaces version 14)

Revision: 18.03.2023

#### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

(Contd. of page 7)

14.1 UN number or ID number ADR/ADN, IMDG, IATA	UN2735
14.2 UN proper shipping name ADR/ADN IMDG, IATA	2735 POLYAMINES, LIQUID, CORROSIVE N.O.S. (N'-(3-aminopropyl)-N,N-dimethylpropan 1,3-diamine) POLYAMINES, LIQUID, CORROSIVE, N.O.S. (N (3-aminopropyl)-N,N-dimethylpropane-1,3 diamine)
14.3 Transport hazard class(es) ADR/ADN	
Class Label	8 (C7) Corrosive substances. 8
IMDG, IATA	
Class Label	8 Corrosive substances. 8
14.4 Packing group ADR/ADN, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Segregation groups Stowage Category Stowage Code	Warning: Corrosive substances. 80 F-A,S-B (SGG18) Alkalis B SW2 Clear of living quarters.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information: Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
ADR/ADN Limited quantities (LQ)	5L



Printing date 02.04.2023

Version number 15 (replaces version 14)

Revision: 18.03.2023

### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

	(Contd. of page 8)
<ul> <li>Excepted quantities (EQ)</li> <li>Transport category</li> <li>Tunnel restriction code</li> </ul>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 E
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (N'-(3-AMINOPROPYL)-N,N- DIMETHYLPROPANE-1,3-DIAMINE), 8, III

### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
- None of the ingredients is listed.
- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
- None of the ingredients is listed.
- Annex II REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors
- None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. (Contd. on page 10)



Printing date 02.04.2023

Version number 15 (replaces version 14)

Revision: 18.03.2023

#### Trade name: UHU PLUS ENDFEST 300 YE FB 163G\*20 L011

Relevant phrases	
H302 Harmful if swallowed.	
H312 Harmful in contact with	skin.
H314 Causes severe skin bu	rns and eye damage.
H317 May cause an allergic	
H318 Causes serious eye da	
H412 Harmful to aquatic life	
-	Regulation (EC) No 1272/2008
Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
Department issuing SDS: U Contact: UHU QESH Date of previous version: 2 Version number of previous Abbreviations and acronyn	5.10.2022 s version: 14