Technical data sheet



Product: AIRFLOW 1

Manufacturer: **MEDMIX**

Product group: **KLEBSTOFF**

Article group: **KLEBEPISTOLE**

Download: 13.06.2025

COX™ AIRFLOW 1™ SACHET 600ML

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results



TECHNICAL DATASHEET

Airflov1 SACHET 600ml



A single component pneumatic bead applicator for sachets



PRODUCT FEATURES:

- High volume trigger valve for immediate sealant flow
- Quick exhaust valve to minimise "flow-on"
- Manufactured in UK to high quality standards for reliability and safety
- Wide range of accessories and spare available to make the most of the applicator and give it a long service life
- 6.8bar (100psi) regulator as standard (others available)

Standard: 6.8 bar (100 psi)

Options available: 3.4 bar (50 psi) **5.2 bar** (75 psi) **5.2 bar** (75 psi)

8.5 bar (125 psi)

The Cox Airflow 1 is part of a range of pneumatic applicators. Ideally suited to larger scale production line and commercial operations where easy access to compressed air is available, giving substantial productivity gains over manual applicators. The Airflow range provides fast, effortless application and smooth consistent sealant flow for high quality workmanship.

For more information call +44(0)1635 264500 Or visit www.pccox.co.uk













TECHNICAL DATASHEET

Airflov1[™] SACHET 600ml



A single component pneumatic bead applicator for sachets

APPLICATIONS:

- · For low to medium viscosity
- · Sachet volumes: 310ml, 400ml, 600ml

SPECIFICATIONS:

- Max Pneumatic Pressure: 6.8bar (100psi) (others available)
- Maximum Thrust: 1.64kN
 Barrel Length: 457mm
- Tool Weight: 1.12kg
- Tool Material: Black cast aluminium with epoxy coating handle, silver anodised aluminium barrel
- Certificates: ISO, REACH, CE, ENPackaging Options: 1 or 10 per box

WEB LINKS:

- Academy video www.pccox.co.uk/en/cox-academy
- Spare parts diagram www.pccox.co.uk/en/exploded-


OTHER MODELS AVAILABLE:

- Airflow 1 Cartridge
- · Airflow 1 Combi
- Airflow 1 Combi HP
- Airflow 1 1000 S
- Airflow 1 1000 L
- Airflow 1 BULK
- See also: Airflow 2 range or Airflow 3 range

Airline/Hose

540.9mm 457mm

SACHETS:



COMPRESSOR GUIDE



Output of around 150L/min (5cfm) with receiver tank from 10L (PC Cox recommends 50L for long tool life)




Standard Nut and Tail 7A2000




European Quick Release 7A2001



American Quick Release 7A2002





PC Cox Ltd., Turnpike Road, Newbury, Berkshire, RG14 2LR T Sales +44 (0) 1635 264500 F +44 (0) 1635 264555 E sales@pccox.co.uk www.pccox.co.uk









