

Technical data sheet



Product: MAX REPAIR

Manufacturer: UHU GMBH & CO KG

Product group: KLEBSTOFF

Article group: KLEBSTOFF

Download: 30.06.2025

UHU MAX REPAIR POWER 20G

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708

UHU®

MAX REPAIR POWER

POWERFUL AND FLEXIBLE REPAIR ADHESIVE FOR LONG LASTING REPAIR RESULTS



APPLICATION

Directions for use:

Can be applied directly from the tube using the fine dispensing nozzle.

Apply the adhesive on one side. Press the parts against each other. Adjustments can be made within 5 minutes. The maximum final bonding strength is reached after approximately 24 hours.

Stains/residue: Use white spirit for removing wet adhesive residue. Dry adhesive residue can only be removed mechanically.

Advice: Loosen the stuck cap under the hot tap and remove any hardened adhesive in the tube cap with a sharp knife. After use, let some adhesive come out of the tube before you screw the cap on it.

PRODUCT DESCRIPTION

MAX REPAIR POWER is a powerful and flexible repair adhesive for long lasting results of all sorts of repairs on porous and non-porous materials. Suitable for indoor and outdoor applications.

FIELD OF APPLICATION

Suitable for repairing porous and non-porous materials such as wood, textile, leather, cork, metal, glass, plastic, rubber, ceramic tiles, stone, cement and many other materials. Suitable for indoors and outdoors.

Not suitable for Polypropylene (PP), Polyethylene (PE) and P.T.F.E.

PROPERTIES

- Extremely strong
- Extremely flexible
- Water resistant
- Gap filling
- Dishwasher-safe
- Resistant to shock and vibrations
- Temperature resistant
- UV resistant
- Acid and solvent-free
- Transparent

PREPARATION

Working Conditions: The materials to be bonded must be clean, dry, free of dust and grease.

Surface Requirements: The surface must be dry, clean and free of dust and grease.

Preliminary Surface Treatment: Surfaces must be clean, dry and free from dust and grease.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.



MAX REPAIR POWER

POWERFUL AND FLEXIBLE REPAIR ADHESIVE FOR LONG LASTING REPAIR RESULTS

TECHNICAL SPECIFICATIONS

Bonding technique:	1-Sided application
Chemical base:	SMP Polymer
Chemicals resistance:	Good
Colour:	Transparent
Cure rate:	1 mm/24h
Density approx.:	1.1 g/cm ³
Elasticity:	Limited
Filling capacity:	Very good
Final bond strength:	800 N/cm ²
Final bond strength after:	24 hours. This might vary, based on circumstances, like materials, temperature and humidity.
Hardness (Shore A):	80
Initial Bonding after:	10 minutes. This might vary, based on circumstances, like materials, temperature and humidity.
Minimum temperature resistance:	-40 °C
Maximum temperature resistance:	120 °C
Moisture resistance:	Very good
Open time approx.:	10-15 minutes
Paintability:	Good
Shear strength:	800 N/cm ²
Skinover time:	5 minutes
Solid matter approx.:	100 %
Solvent free:	Yes
UV resistance:	Good
Viscosity:	Thixotropic
Water resistance:	Very good

PACK SIZES

8 g, 20 g

STORAGE CONDITIONS

At least 24 months after date of manufacture.

Limited shelf life after opening.

Store in tightly closed packaging in a dry, cool and frost-free place.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.