

Technical data sheet



Product: 9999

Manufacturer: H.B. FULLER

Product group: KLEBSTOFF

Article group: REINIGER

Download: 16.04.2026

CYBERBOND CB 9999 CLEANER SPRAY

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708



Chemical Base:

Alcohol, Acetone, Aliphatic Hydrocarbons
Propane / Butane mixture as propellant

Description:

Cyberbond 9999 is a universal Cleaner for metals. Oil, grease and dirt quite often prevent a perfect bonding. For this reason metal parts which have to be bonded should be cleaned and degreased before. Just spray Cyberbond 9999 on the dirty parts, let the product be effective and wipe it away. Cyberbond 9999 is also suitable to remove residues of adhesives and sealants. In addition to that it also is a very good break cleaner.

Quite often plastics are dissolved by solvent based cleaners. Therefore make sure before application that Cyberbond 9999 is suitable for your cleaning process. Should not be applied on varnish or leather.

Physical properties

Density at 20°C	0,699 g/cm ³
Shelf life	1 year

The data mentioned in this TDS, particularly the recommendations and use of products are based on our recent knowledge and experience. Due to the fact of having so many different materials involved and conditions of applications which are out of our influence, we strongly recommend to do sufficient tests in order to guarantee that Cyberbond products are suitable for the intended process and applications. Except for wilful acts any liability based on such recommendations or any verbal advice is hereby expressly excluded.

For safe handling consult Material Safety Data Sheet (MSDS).

Cyberbond Europe GmbH
A H.B. Fuller Company
Werner-von-Siemens-Straße 2
31515 Wunstorf
Germany
Tel.: +49 / 50 31 / 95 66 - 0
www.cyberbond.de

