Security data sheet

Product:	9720
Manufacturer:	H.B. FULLER
Product group:	KLEBSTOFF
Article group:	SPRAY
Download:	09.05.2024

SWIFT®COL 9720

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Swift®col 9720

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	24.01.2023	100000018404	Date of first issue: 24.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Swift®col 9720

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Adhesive

Recommended restrictions on use : For industrial use only.

1.3 Details of the supplier of the safety data sheet

Company : H.B. Fuller, Isar-Rakoll, S.A.

Address : Estrada Nacional 13
PT-4486-851 Mindelo - Vila do Conde
+351 229 288 200

E-mail address of person responsible for the SDS : EU-MSDS@hbfuller.com

1.4 Emergency telephone number

Emergency telephone number : In case of poisoning:
GBK-EMTEL International
Tel.(24h): +49(0)6132/84463 (all languages)

In case of transport accidents:
Tel.(24h): (001) 352 323 3500 (Infotrac - Contract ID: 90373 / GBK)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.

Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :

Signal word : Danger

Hazard statements :

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing mist.
P280 Wear protective gloves.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Rosin
acetone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0 921-024-6 01-2119475514-35-0000	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 Skin Irrit. 2; H315 STOT SE 3; H336 (Respiratory system)	>= 10 - < 20
Rosin	8050-09-7 232-475-7 650-015-00-7 01-2119480418-32-0000	Skin Sens. 1; H317	>= 1 - < 10
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49-0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 1 - < 10
n-hexane	110-54-3 203-777-6 601-037-00-0 01-2119480412-44-0000	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 (Central nervous system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 0,25 - < 1
2,6-di-tert-butyl-p-cresol	128-37-0 204-881-4 01-2119555270-46-0000, 01-2119565113-46-	Aquatic Chronic 1; H410	>= 0,1 - < 0,25

	0000, 01-2119480433-40-0000		
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32-0000	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,1 - < 0,25
Substances with a workplace exposure limit :			
dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37-0000	Flam. Gas 1; H220 Press. Gas	>= 50 - < 70

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : If on clothes, remove clothes.
Move the victim to fresh air.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
In case of unconsciousness bring patient into stable side position for transport.

In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
If skin irritation persists, call a physician.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.

If swallowed : If accidentally swallowed obtain immediate medical attention.
Rinse mouth with water.
If conscious, drink plenty of water.
Do NOT induce vomiting.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water mist
Dry powder
Carbon dioxide (CO2)
Alcohol-resistant foam

Unsuitable extinguishing media : Water with a full water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : May release toxic, irritating and/or corrosive gases.
In case of fire, the following substance(s) may occur:
Carbon monoxide

5.3 Advice for firefighters

Special protective equipment for firefighters : No special protective measures against fire required.

Further information : In the event of fire, wear self-contained breathing apparatus.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Use breathing protection against the effects of fumes/dust/aerosol.
Evacuate personnel to safe areas.
Ensure adequate ventilation.

6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.
Prevent the material from reaching sewage system, holes and cellars.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Non-sparking tools should be used.
Ensure adequate ventilation.
Send for recovery or disposal in suitable containers.
Dispose of contaminated material as waste according to section 13.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of dust and aerosols.
Use only with adequate ventilation.
Take note of emission threshold.
Use solvent-proof equipment.
Ensure that suitable extractors are available on processing machines.
Handle with care.
Keep eye wash bottle available on working place.
Avoid release to the environment.
Keep away from children.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Do not spray on an open flame or other ignition source.
Do not spray on a naked flame or any incandescent material.
Keep away from sources of ignition - No smoking. Keep away from children.

Advice on protection against fire and explosion : Keep product and empty container away from heat and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. May form explosive mix-

tures in air. Highly volatile, flammable constituents are released during processing. In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep dark, cool and dry. Store in cool place.

Further information on storage conditions : Keep containers tightly closed in a dry, cool and well-ventilated place. Store in a cool place. Heat will increase pressure and may lead to the container exploding.

7.3 Specific end use(s)

Specific use(s) : No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethyl ether	115-10-6	TWA	400 ppm 766 mg/m3	GB EH40
		STEL	500 ppm 958 mg/m3	GB EH40
		TWA	1.000 ppm 1.920 mg/m3	2000/39/EC
	Further information: Indicative			
Rosin	8050-09-7	TWA (Fumes)	0,05 mg/m3	GB EH40
	Further information: Capable of causing occupational asthma.			
		STEL (Fumes)	0,15 mg/m3	GB EH40
	Further information: Capable of causing occupational asthma.			
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	GB EH40
		STEL	1.500 ppm 3.620 mg/m3	GB EH40
		TWA	500 ppm 1.210 mg/m3	2000/39/EC
	Further information: Indicative			
n-hexane	110-54-3	TWA	20 ppm 72 mg/m3	GB EH40
		TWA	20 ppm	2006/15/EC

			72 mg/m3	
	Further information: Indicative			
2,6-di-tert-butyl-p-cresol	128-37-0	TWA	10 mg/m3	GB EH40

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	2,035 mg/m3
acetone	Workers	Dermal	Long-term systemic effects	186 mg/kg
	Workers	Inhalation	Acute local effects	2420 mg/m3
	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
n-hexane	Workers	Dermal	Long-term systemic effects	13 mg/kg
	Workers	Inhalation	Long-term systemic effects	93 mg/m3

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
acetone	Marine water	1,06 mg/l
	Fresh water	10,6 mg/l
	Fresh water sediment	30,4 mg/l
	Marine sediment	3,04 mg/l
	Soil	0,112 mg/l
	Sewage treatment plant	29,5 mg/l

8.2 Exposure controls

Engineering measures
Please take care on national and local requirements.

Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection

Remarks : The glove material has to be impermeable and resistant to the product/the substance/the preparation.
The exact break through time can be obtained from the pro-

tective glove producer and this has to be observed.
The gloves need to be disposed after the penetration time and replaced by new ones.
Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

For the permanent contact gloves made of the following materials are suitable:
If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from Ansell or other suppliers (penetration time: 480 min).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Butyl rubber (minimum thickness: 0.7 mm; penetration time: 15 min)

As protection from splashes gloves made of the following materials are suitable:
Nitril (minimum thickness 0.12 mm), Disposable gloves with long cuffs

After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

Skin and body protection	:	Protective clothing
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In case of brief exposure or low pollution (exceeding of TLV) use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air. Ensure that suitable extractors are available on processing machines.
Protective measures	:	Keep away from food, drink and animal feedingstuffs. Instantly remove any soiled and impregnated garments. Wash hands before breaks and immediately after handling the product. Avoid contact with the eyes and skin. Store protective clothing separately.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	aerosol
Odour Threshold	:	is not determined
pH	:	is not determined
Melting point/freezing point	:	is not determined
Flash point	:	-42 °C
Evaporation rate	:	is not determined
Relative vapour density	:	is not determined
Solubility(ies)		
Water solubility	:	not miscible or difficult to mix
Partition coefficient: n-octanol/water	:	no data available
Auto-ignition temperature	:	is not determined
Decomposition temperature	:	Not applicable
Explosive properties	:	Product is not explosive. However, formation of explosive vapour/air mixtures is possible.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

No decomposition if used according to the specifications.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Develops readily flammable vapours/fumes.

10.4 Conditions to avoid

Conditions to avoid : No further relevant information available.

10.5 Incompatible materials

Materials to avoid : No further relevant information available.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

n-hexane:

Acute dermal toxicity : LD50 Dermal (Rabbit): 3.000 mg/kg

2,6-di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 Oral (Rat): 6.000 mg/kg

SECTION 12: Ecological information

12.1 Toxicity

Components:

Rosin:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3,8 - 5,4 mg/l
Exposure time: 48 h
Test Type: static test

n-hexane:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,1 - 2,98 mg/l
Exposure time: 96 h
Test Type: flow-through test

2,6-di-tert-butyl-p-cresol:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 5 mg/l
Exposure time: 48 h

Test Type: static test

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 0,42 mg/l
Exposure time: 72 h
Test Type: flow-through test

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

Product:

Mobility : Medium: Soil
Remarks: Do not allow product to reach ground water, water bodies or sewage system., Very toxic to aquatic organisms, Toxic effects on fish and plankton, Danger to drinking water if even extremely small quantities leak into soil.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Do not dispose of waste into sewer.
Hand over to disposers of hazardous waste.
The generation of waste should be avoided or minimized wherever possible.
Incinerate under controlled conditions in accordance with all local and national laws and regulations.
Disposal must be made according to official regulations.

Contaminated packaging : Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number

ADN	:	UN 1950
ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
IATA	:	UN 1950

14.2 UN proper shipping name

ADN	:	AEROSOLS
ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS
IATA	:	Aerosols, flammable

14.3 Transport hazard class(es)

ADN	:	2
ADR	:	2
RID	:	2
IMDG	:	2.1
IATA	:	2.1

14.4 Packing group

ADN

Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1

ADR

Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1
Tunnel restriction code	:	(D)

RID

Packing group	:	Not assigned by regulation
Classification Code	:	5F
Hazard Identification Number	:	23

Labels : 2.1

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)
Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA_P (Passenger)
Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN
Environmentally hazardous : no

ADR
Environmentally hazardous : no

RID
Environmentally hazardous : no

IMDG
Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-

the market and use of certain dangerous substances, mixtures and articles (Annex XVII)		lowing entries should be considered: Number on list 75Rosin acetone n-hexane
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable
RoHS: 2011/65/EU, Restriction of Hazardous Substances	:	Not applicable
Council Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors	:	Neither banned nor restricted
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	:	Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors	:	acetone
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a		FLAMMABLE AEROSOLS
Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 86,37 %, 673,7 g/l

The components of this product are reported in the following inventories:

TSCA	:	All substances listed as active on the TSCA inventory
AIIC	:	On the inventory, or in compliance with the inventory

DSL	:	All components of this product are on the Canadian DSL
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
REACH	:	On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements

H220	:	Extremely flammable gas.
H225	:	Highly flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.
H361f	:	Suspected of damaging fertility.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Flam. Liq.	:	Flammable liquids
Press. Gas	:	Gases under pressure
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure

STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2006/15/EC / TWA	:	Limit Value - eight hours
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information	:	This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Contact Point : Prepared by: Global Regulatory Department
EU-MSDS@hbfuller.com

Classification of the mixture:		**Classification procedure:**
Aerosol 1	H222, H229	Calculation method
Skin Irrit. 2	H315	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN