

# Technical data sheet



Product: 50600

Manufacturer: TESA SE

Product group: KLEBEBAND

Article group: EINSEITIG

Download: 15.01.2025

## TESA® 50600

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH  
Industriestraße 15  
D-75382 Althengstett

Telephone:  
+49(0)7051/9297-0  
Fax:  
+49(0)7051/9297-99

E-Mail:  
info@tewipack.de  
Website:  
www.tewipack.de

Managing director:  
Alexander Uhl,  
Michael Uhl  
HRB 330424  
Amtsgericht  
Stuttgart

Bank details:  
Sparkasse  
Sindelfingen  
Pforzheim  
Calw  
BLZ 666 500  
85  
Konto 17 787


Commerzbank  
Sindelfingen  
BLZ 603 400 71  
Konto 8 001 166

Vereinigte  
Volksbank AG  
Böblingen  
BLZ 603 900 00  
Konto 80 089  
003

Postbank  
Stuttgart  
BLZ 600 100  
70  
Konto 146  
294 708



# tesa<sup>®</sup> 50600 Standard



## Product Information

PET Masking Tape 220°C with Silicone Adhesive

## Product Description

tesa<sup>®</sup> 50600 is a green-translucent, high-temperature masking tape featuring a polyester backing with a silicone adhesive. tesa<sup>®</sup> 50600 is used for various applications, especially for masking during powder-coating processes, surface protection applications or bonding and splicing of non-polar materials. tesa<sup>®</sup> 50600 masking tape is also available in a version with a liner.

## Product Features

- tesa<sup>®</sup> 50600 is also available on a special 50 µm thick PET liner (50600 PV1)
- Residue-free removability for masking and surface protection applications
- The high-temperature tape features easy application and easy one-piece removal without leaving residues behind
- The tape enables sharp color edges and offers excellent paint anchorage.
- The masking tape's silicone adhesive system makes the tape extremely heat-resistant, withstanding extreme temperatures of up to 220°C for as long as 30 minutes at a time.

## Application Fields

- tesa<sup>®</sup> 50600 is ideally suited for masking off areas that are to be protected during powder-coating processes
- The high-temperature tape can withstand temperatures of up to 220°C for 30 minutes
- tesa<sup>®</sup> 50600 is used for surface protection applications or bonding and splicing of non-polar materials
- The masking tape features residue-free removal

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |          |                   |       |
|--------------------|----------|-------------------|-------|
| • Backing material | PETP     | • Total thickness | 80 µm |
| • Type of adhesive | silicone |                   |       |

## Properties/Performance Values

- |                          |        |                    |         |
|--------------------------|--------|--------------------|---------|
| • Easy to remove         | Yes    | • Tensile strength | 75 N/cm |
| • Temperature resistance | 220 °C | • Hand tearability | low     |
| • Elongation at break    | 110 %  |                    |         |

## Adhesion to Values

- |         |        |
|---------|--------|
| • Steel | 4 N/cm |
|---------|--------|

For latest information on this product please visit <http://l.tesa.com/?ip=50600>



# tesa<sup>®</sup> 50600 Standard

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=50600>