

# Technical data sheet



Product: 1601/1602/1603/1604

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: ELEKTRO

Article group: SPRAY

Download: 31.08.2025

## 3M SCOTCH INSULATING SPRAY

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH  
Industriestraße 15  
D-75382 Althengstett

Telephone:  
+49(0)7051/9297-0  
Fax:  
+49(0)7051/9297-99

E-Mail:  
info@tewipack.de  
Website:  
www.tewipack.de

Managing director:  
Alexander Uhl,  
Michael Uhl  
HRB 330424  
Amtsgericht  
Stuttgart

Bank details:  
Sparkasse  
Sindelfingen  
Pforzheim  
Calw  
BLZ 666 500  
85  
Konto 17 787

Commerzbank  
Sindelfingen  
BLZ 603 400 71  
Konto 8 001 166

Vereinigte  
Volksbank AG  
Böblingen  
BLZ 603 900 00  
Konto 80 089  
003

Postbank  
Stuttgart  
BLZ 600 100  
70  
Konto 146  
294 708

## 3M™ Insulating Spray Scotch® 1601 / 1602 / 1603 / 1604

---

### Product Description

3M™ Scotch® 1601 – 1602 – 1603 – 1604 Insulating Spray is an acrylic-based insulating varnish that forms a flexible and durable film which protects electrical connections, switches, switchgear and components and seals treated surfaces.

The insulating and coating sprays are UV, acid, oil and alkali resistant, resistant to moisture and weather and are characterized by a high dielectric strength, with excellent adhesion to all common materials such as metal, glass, plastic, wood, etc.

### Available Colours

1601 – Clear

1602 – Red

1603 – Black

1604 – Grey

### Pack Size

400ml can

### Typical Properties

- UV-resistant
- solvent resistant
- resistant to acids, bases and oils
- abrasion resistant
- Moisture and weatherproof



### Applications

3M™ Scotch® 1601 – 1602 – 1603 – 1604 Insulating Spray is used as a protective coating on electrical connections, switches, switchgear, terminal boards, electronic components, coils, and windings. It is also suitable for colour coding or for optical protection.

The substrate must be dry, free from oil and grease (\*) and free of dust, loose buildup and corrosion. Shake the can intensively for approx. 2 minutes before use, until the stirring ball is clearly audible. At room temperature (approx. +20°C) spray at a distance of 25 - 30 cm on the surface to be coated (vertical / horizontal) and allow to dry.

**Note:** \* Prior cleaning with Scotch® 1626 Cleaning and Degreasing Spray or Scotch® 1625 Special Contact Cleaning Spray is recommended

**When over-coating, a self test for compatibility is necessary**

## Technical Information

Base	modified acrylic resin
Propellant	propane/butane
Solvents	aliphatic / aromatized hydrocarbons
Color	clear / black / red / gray
Dielectric strength	34 kV/mm* acc. DIN VDE 0303
Drying time at room temperature	dust dry - after 8min dry to handle - after 20-30 min paintable - after 120 min fully dry - after 48 hrs
Temperature resistance	after 700 Std. / +120°C -> no change
Weather resistance	Salt Spray Test 5% saline solution at 35 ° C -> 168 hrs
UV-resistance	Test based on DIN ISO 4892-3 (1000 hours) -> good
Chemical resistance	Test in accordance with DIN ISO 2812-1 -> good against solvents
Surface resistance	1 x 10 <sup>12</sup> Ωcm

\* At layer thicknesses of only 25µm or 45µm (1-2x spraying), only a dielectric strength of approx. 500V may be achieved.

## Storage

3M™ Scotch® 1601 – 1602 – 1603 – 1604 Insulating Spray has a 2 year shelf life from the date of manufacture, stated on the can, when stored in humidity controlled conditions (10°C to 27°C and <75% relative humidity)

## Safety Note

Pressurised Container. Protect from sunlight and temperatures above 50°C.

3M™ Scotch® 1601 – 1602 – 1603 – 1604 Insulating Spray is highly flammable, and should not be sprayed into flames. Hold the can vertically when in use, do not incline more than 30°. This product should not be inhaled, a working environment with good ventilation must be ensured.

Protect skin and eyes, use appropriate PPE. Please refer to our SDS for further information at [https://www.3m.co.uk/3M/en\\_GB/company-uk/SDS-search/](https://www.3m.co.uk/3M/en_GB/company-uk/SDS-search/)

**Important Notice:** Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

**Warranty; Limited Remedy; Limited Liability.** This product will be free from defects in material and manufacture at the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.



### Electrical Markets Division

3M UK PLC, 3M Centre, Cain Rd,  
Bracknell RG12 8HT, United Kingdom  
0870 609 4639  
[www.3M.co.uk/electrical](http://www.3M.co.uk/electrical)

### Electrical Markets Division

3M Ireland Ltd, The Iveagh Building, The  
Park, Carrickmines, Dublin 18, Ireland  
1 800 812 732  
[www.3M.co.uk/electrical](http://www.3M.co.uk/electrical)

3M and is a trademarks of the 3M  
company.

© 3M 2019. All rights reserved.

Issue 1