

Technical data sheet



Product: CA SOLVENT 2

Manufacturer: PERMABOND ENGINEERING ADHESIVES

Product group: KLEBSTOFF

Article group: REINIGER/LÖSER

Download: 14.04.2026

PERMABOND CA SOLVENT 2

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708

Description

Permabond CA Solvent 2 is a blend of organic esters which can be used to remove cured cyanoacrylate adhesive from surfaces, clothing or to debond parts assembled with cyanoacrylate adhesives. It is non-flammable and non-hazardous.

Physical Properties

Chemical base	Organic esters
Appearance	Clear Liquid
Viscosity @20°C	<20 mPa.s
Flashpoint	> 100°C (212°F)
Specific Gravity	1.05

Storage & Handling

Storage Temperature Store in a cool place away from direct sunlight	5 to 25°C (41 to 77°F)
Shelf Life Stored in original unopened containers	12 months

Directions for Use

- Applying CA Solvent 2 remover to cured cyanoacrylate adhesive will allow its removal in several minutes to several hours, depending upon the amount of adhesive.
- Thin layers of adhesive will wipe off with the remover-soaked tissue or cloth.
- Thick beads or drops will take between 15 and 30 minutes and will require reapplication of solvent.
- Bonded parts may require several hours of soaking.
- This solvent can affect certain plastics, coatings and fabrics. It is recommended that all surfaces be tested for compatibility before use.

Additional Information

Users are reminded that all materials, whether innocuous or not, should be handled in accordance with the principles of good industrial hygiene. Full information can be obtained from the Material Safety Data Sheet.

This product is not recommended for use with strong oxidizing materials.

www.permabond.com

• UK: 0800 975 9800

• General Enquiries: +44 (0)1962 711661

• US: 732-868-1372

• Asia: + 86 21 5773 4913

info.europe@permabond.com

info.americas@permabond.com

info.asia@permabond.com

The information given and the recommendations made herein are based on our research and are believed to be accurate but no guarantee of their accuracy is made. In every case we urge and recommend that purchasers before using any product in full-scale production make their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purpose under their own operating conditions. THE PRODUCTS DISCLOSED HEREIN ARE SOLD WITHOUT ANY WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED.

No representative of ours has any authority to waive or change the foregoing provisions but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to their needs and to the circumstances prevailing in their business. Nothing contained herein shall be construed to imply the non-existence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of this patent. We also expect purchasers to use our products in accordance with the guiding principles of the Chemical Manufacturers Association's Responsible Care® program.