

Security data sheet



Product: 140

Manufacturer: H.B. FULLER

Product group: KLEBSTOFF

Article group: 1-K KLEBSTOFF

Download: 08.05.2024

KÖRAPUR® 140 GRAU

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Product name** : Körapur® 140 grau**1.2 Relevant identified uses of the substance or mixture and uses advised against**Use of the Sub-
stance/Mixture : Adhesive, SealantRecommended restrictions
on use : For industrial use only.**1.3 Details of the supplier of the safety data sheet****Company** : H.B. Fuller, Isar-Rakoll, S.A.**Address** : Estrada Nacional 13
PT-4486-851 Mindelo - Vila do Conde
+351 229 288 200**E-mail address of person
responsible for the SDS** : EU-MSDS@hbfuller.com**1.4 Emergency telephone number****Emergency telephone number** : In case of poisoning:
GBK-EMTEL International
Tel.(24h): +49(0)6132/84463 (all languages)In case of transport accidents:
Tel.(24h): (001) 352 323 3500 (Infotrac - Contract ID: 90373 /
GBK)National Poisons Information Centre (NPIC): 01 809 2566 (24
hours)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Respiratory sensitisation, Category 1

H334: May cause allergy or asthma symptoms or
breathing difficulties if inhaled.**2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)**

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

Hazard pictograms :



Signal word : Danger

Hazard statements : H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements : **Prevention:**P261 Avoid breathing dust.
P284 Wear respiratory protection.**Response:**P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:4,4'-Methylenediphenyl diisocyanate, oligomers
4,4'-methylenediphenyl diisocyanate**Additional Labelling**EUH204 Contains isocyanates. May produce an allergic reaction.
EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
---------------	-------------------	----------------	--------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

 Version
3.0

 Revision Date:
01.09.2023

 SDS Number:
100000020597

 Date of last issue: 20.06.2023
Date of first issue: 03.10.2022

	Index-No. Registration number		
Reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119488216-32-0000	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Acute Tox. 4; H312 Acute toxicity estimate Acute inhalation toxicity (vapour): 11 mg/l	$\geq 1 - < 10$
di-"isononyl" phthalate (Unbranched)	28553-12-0 249-079-5 01-2119430798-28-0000	Aquatic Chronic 4; H413	$\geq 2,5 - < 10$
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17-0000	Carc. 2; H351	$\geq 1 - < 10$
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35-0000	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 Asp. Tox. 1; H304 Acute toxicity estimate Acute inhalation toxicity (vapour): 17,2 mg/l	$\geq 1 - < 10$
xylenes	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32-0000, 01-2119486136-34-0000	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	$\geq 1 - < 10$
4,4'-Methylenediphenyl diisocyanate, oligomers	25686-28-6 500-040-3 01-2119457013-49-0000	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	$\geq 0,1 - < 1$

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version
3.0

Revision Date:
01.09.2023

SDS Number:
100000020597

Date of last issue: 20.06.2023
Date of first issue: 03.10.2022

		STOT RE 2; H373 (Respiratory system) Carc. 2; H351 Acute toxicity estimate Acute inhalation toxicity (dust/mist): 1,5 mg/l	
4,4'-methylenediphenyl diisocyanate	101-68-8 202-966-0 615-005-00-9 01-2119457014-47-0000	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 ≥ 5 % STOT SE 3; H335 ≥ 5 % Skin Irrit. 2; H315 ≥ 5 % Resp. Sens. 1; H334 ≥ 0,1 % Acute toxicity estimate Acute inhalation toxicity (dust/mist): 1,5 mg/l	≥ 0,1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures
4.1 Description of first aid measures

General advice : Even minimal concentrations of isocyanate can lead to a reaction in sensitised people.
Symptoms that may occur include the following:
irritation of the eyes, nose, throat and lungs, possibly together

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version 3.0	Revision Date: 01.09.2023	SDS Number: 100000020597	Date of last issue: 20.06.2023 Date of first issue: 03.10.2022
----------------	------------------------------	-----------------------------	---

with a dry throat, a feeling of chest tightness and breathing difficulties.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Show this safety data sheet to the doctor in attendance.

- | | |
|-------------------------|---|
| If inhaled | : Remove person to fresh air. If signs/symptoms continue, get medical attention.
In case of unconsciousness bring patient into stable side position for transport. |
| In case of skin contact | : Treat affected skin with cotton wool or cellulose.
Wash off with plenty of water.
Use a mild soap if available.
If skin irritation persists, call a physician. |
| In case of eye contact | : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists. |
| If swallowed | : If accidentally swallowed obtain immediate medical attention.
Do NOT induce vomiting. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|-------|--|
| Risks | : May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
|-------|--|

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|---|
| Treatment | : In instances of existing sensitisation towards isocyanates, a doctor should be consulted with regards to work-related contact with other sensitising substances, or substances which irritate the airway. |
|-----------|---|

Treatment for exposure should be geared towards monitoring symptoms and the patient's clinical condition.
It must be ensured that the patient has sufficient ventilation and oxygen supply.

Isocyanates can cause sensitisation of the airways, or asthma-like symptoms (bronchospasms). Delayed breathing symptoms, including lung oedema, may occur.

People who have shown signs of breathlessness after considerable exposure should remain under observation for 24-48 hours.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Alcohol-resistant foam
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : Water with a full water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : May release toxic, irritating and/or corrosive gases.
In case of fire, the following substance(s) may occur:
Hydrogen chloride (HCl)
Nitrogen oxides
Sulphur oxides (SO_x)
Carbon monoxide

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

Further information : In the event of fire, wear self-contained breathing apparatus.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.

6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.
Send for recovery or disposal in suitable containers.
Soak up with inert absorbent material (e.g. sand, silica gel,

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

acid binder, universal binder, sawdust).
Dispose of contaminated material as waste according to section 13.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Advice on safe handling : Avoid formation of dust and aerosols.
Use only with adequate ventilation.
Handle with care.
Keep eye wash bottle available on working place.
Avoid release to the environment.
Keep away from children.
- Advice on protection against fire and explosion : In the event of fire and/or explosion do not breathe fumes.
Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire. The product contains small quantities of organic solvents. The possibility of an ignitable vapour / air mixture forming is very slight but, under certain local conditions, this should not be overlooked. Keep away from sources of ignition - No smoking.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep dark, cool and dry. Do not freeze.
- Further information on storage conditions : Keep containers tightly closed in a dry, cool and well-ventilated place. Store in a cool place. Heat will increase pressure and may lead to the container exploding.
- Storage class (TRGS 510) : 13, Non Combustible Solids

7.3 Specific end use(s)

- Specific use(s) : No further relevant information available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
polyvinyl chloride	9002-86-2	OELV - 8 hrs	1 mg/m ³	IE OEL

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

 Version
3.0

 Revision Date:
01.09.2023

 SDS Number:
100000020597

 Date of last issue: 20.06.2023
Date of first issue: 03.10.2022

(Suspension)		(TWA) (Respirable dust)		
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m ³	IE OEL
di-"isononyl" phthalate (Un-branched)	28553-12-0	OELV - 8 hrs (TWA)	5 mg/m ³	IE OEL
titanium dioxide	13463-67-7	OELV - 8 hrs (TWA) (Respirable dust)	4 mg/m ³	IE OEL
		OELV - 8 hrs (TWA) (inhalable dust)	10 mg/m ³	IE OEL
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		OELV - 15 min (STEL)	200 ppm 884 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 8 hrs (TWA)	100 ppm 442 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
xylenes	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		OELV - 8 hrs (TWA)	50 ppm 221 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 15 min (STEL)	100 ppm 442 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
4,4'-methylenediphenyl diisocyanate	101-68-8	OELV - 8 hrs (TWA)	0,005 ppm (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

	sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			
		OELV - 15 min (STEL)	0,07 mg/m ³ (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			
		OELV - 8 hrs (TWA)	0,02 mg/m ³ (NCO)	IE OEL
	Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction mass of ethylbenzene and xylene	Workers	Inhalation	Acute systemic effects	289 mg/m ³
	Workers	Inhalation	Acute local effects	289 mg/m ³
	Workers	Dermal	Long-term systemic effects	180 mg/kg
	Workers	Inhalation	Long-term systemic effects	77 mg/m ³
4,4'-methylenediphenyl diisocyanate	General population	Eye contact	Local effects	
	Workers	Eye contact	Local effects	
	Workers	Inhalation	Local, long-term	0,05 mg/m ³
	Workers	Inhalation	Local, short-term	0,1 mg/m ³
	General population	Inhalation	Local, short-term	0,05 mg/m ³
	General population	Inhalation	Local, long-term	0,025 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction mass of ethylbenzene and xylene	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Soil	2,31 mg/kg
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg
	Marine sediment	12,46 mg/kg
4,4'-methylenediphenyl diisocyanate	Soil	1 mg/kg
	Sewage treatment plant	1 mg/l
	Fresh water	1 mg/l
	Marine water	0,1 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

8.2 Exposure controls**Engineering measures**

Please take care on national and local requirements.

Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection
Material : Nitrile rubberRemarks : Direct contact with the isocyanate-based product must be avoided by organizational measures.
The glove material has to be impermeable and resistant to the product/the substance/the preparation. The exact break through time can be obtained from the protective glove producer and this has to be observed.Skin and body protection : Protective clothing
When carrying out activities where unintentional skin contact with the isocyanate-based product may occur (e.g. during maintenance work, or when opening a barrel), wear long-sleeved protective clothing and gloves.

Respiratory protection : Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Protective measures : Keep away from food, drink and animal feedingstuffs.
Instantly remove any soiled and impregnated garments.
Wash hands before breaks and immediately after handling the product.
Avoid contact with the eyes and skin.
Store protective clothing separately.**Environmental exposure controls**

Air : Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Physical state	: solid
Colour	: grey
Odour	: solvent-like
Odour Threshold	: is not determined

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

Melting point/freezing point	:	is not determined
Boiling point/boiling range	:	is not determined
Flammability	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	Upper flammability limit is not determined
Lower explosion limit / Lower flammability limit	:	Lower flammability limit is not determined
Flash point	:	Not applicable
Auto-ignition temperature	:	not self-igniting
Decomposition temperature	:	Not applicable
pH	:	is not determined
Solubility(ies) Water solubility	:	not miscible or difficult to mix, reacts with water
Partition coefficient: n-octanol/water	:	no data available
Vapour pressure	:	is not determined
Density	:	1,17 g/cm ³ (20 °C)
Relative vapour density	:	is not determined

9.2 Other information

Explosives	:	Not explosive
Evaporation rate	:	is not determined

SECTION 10: Stability and reactivity**10.1 Reactivity**

No further relevant information available.

10.2 Chemical stability

No decomposition if used according to the specifications.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Reacts with alcohols, amines, aqueous acids and alkalis.
---------------------	---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version 3.0	Revision Date: 01.09.2023	SDS Number: 100000020597	Date of last issue: 20.06.2023 Date of first issue: 03.10.2022
----------------	------------------------------	-----------------------------	---

Mixture reacts slowly with water resulting in evolution of CO₂.
Evolution of CO₂ in closed containers causes overpressure
and produces a risk of bursting.

10.4 Conditions to avoid

Conditions to avoid : No further relevant information available.

10.5 Incompatible materials

Materials to avoid : No further relevant information available.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 Hours
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:**Reaction mass of ethylbenzene and xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Test atmosphere: vapour
Method: Acute toxicity estimate

Acute dermal toxicity : LD50 (Rat): 1.468 mg/kg

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3.500 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 17,2 mg/l
Test atmosphere: vapour
Method: Calculation method

xylenes:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

Acute oral toxicity : LD50 Oral (Rat): 4.300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 47.635 mg/l
Exposure time: 4 Hours
Test atmosphere: vapour

4,4'-Methylenediphenyl diisocyanate, oligomers:

Acute inhalation toxicity : LC50: 1,5 mg/l
Exposure time: 4 Hours
Test atmosphere: dust/mist

Acute toxicity estimate: 1,5 mg/l
Test atmosphere: dust/mist
Method: Calculation method

4,4'-methylenediphenyl diisocyanate:

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l
Test atmosphere: dust/mist
Method: Calculation method

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation**Skin sensitisation**

Based on available data, the classification criteria are not met.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Components:**titanium dioxide:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen

Reproductive toxicity

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

11.2 Information on other hazards**Endocrine disrupting properties****Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential**Components:****di-"isononyl" phthalate (Unbranched):**

Partition coefficient: n-octanol/water : log Pow: 8,8 - 9,7 (25 °C)
pH: 4,6
GLP: no

ethylbenzene:

Partition coefficient: n-octanol/water : log Pow: 3,13 - 3,14
GLP: no

xylenes:

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15
GLP: no

4,4'-methylenediphenyl diisocyanate:

Partition coefficient: n-octanol/water : log Pow: 5,22

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

12.4 Mobility in soil**Product:**

Mobility : Medium: Soil
Remarks: Do not allow product to reach ground water, water bodies or sewage system.

12.5 Results of PBT and vPvB assessment**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : Do not dispose of with domestic refuse.
Do not dispose of waste into sewer.
Hand over to disposers of hazardous waste.
Can be deposited with household garbage after solidification following consultation with the operator of the waste disposal facility and the pertinent authorities and under adherence to the necessary technical regulations.
The generation of waste should be avoided or minimized wherever possible.
Incinerate under controlled conditions in accordance with all local and national laws and regulations.
Disposal must be made according to official regulations.

These EU waste code numbers are recommendations for waste accruing through the use of adhesives and sealants. Any waste produced from organic solvents or other dangerous substances (according GHS) listed under section 3 of this safety datasheet is itself classified as dangerous (*).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

Waste accruing during application:

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Waste accruing during cleaning:

08 04 11* adhesive and sealant sludges containing organic solvents or other dangerous substances
08 04 12 adhesive and sealant sludges other than those mentioned in 08 04 11

Waste packaging:

15 01 01 paper and cardboard packaging
15 01 02 plastic packaging
15 01 04 metallic packaging
15 01 10* packaging containing residues of or contaminated by dangerous substances.

Contaminated packaging : Disposal must be made according to official regulations.

SECTION 14: Transport information**14.1 UN number or ID number**

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, : Conditions of restriction for the following entries should be considered:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

mixtures and articles (Annex XVII)

Number on list 754,4'-methylenediphenyl diisocyanate (Number on list 74)
phenol
p-toluenesulphonyl isocyanate
dibutyltin dilaurate
octamethylcyclotetrasiloxane
xylenes4,4'-methylenediphenyl diisocyanate (Number on list 74)
4,4'-Methylenediphenyl diisocyanate, oligomers
o-(p-isocyanatobenzyl)phenyl isocyanate (Number on list 74)
xylenes

REACH - Candidate List of Substances of Very High Concern for Authorisation (SVHC, Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

RoHS: 2011/65/EU, Restriction of Hazardous Substances : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 7,51 %, 87,9 g/l**Other regulations:**

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: On the inventory, or in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
REACH	: On the inventory, or in compliance with the inventory
KKDIK	: On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information**Full text of H-Statements**

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficul-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

ties if inhaled.

H335 : May cause respiratory irritation.

H351 : Suspected of causing cancer.

H373 : May cause damage to organs through prolonged or repeated exposure.

H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard

Carc. : Carcinogenicity

Eye Irrit. : Eye irritation

Flam. Liq. : Flammable liquids

Resp. Sens. : Respiratory sensitisation

Skin Irrit. : Skin irritation

Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

IE OEL : List of Chemical Agents and Carcinogens with Occupational Exposure Limit Values - Code of Practice, Schedule 1 and 2

2000/39/EC / TWA : Limit Value - eight hours

2000/39/EC / STEL : Short term exposure limit

IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)

IE OEL / OELV - 15 min (STEL) : Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Körapur® 140 grau

Version	Revision Date:	SDS Number:	Date of last issue: 20.06.2023
3.0	01.09.2023	100000020597	Date of first issue: 03.10.2022

of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : This safety datasheet only contains information relating to safety and does not replace any product information or product specification.
Penetrometer test according to ADR 2.3.4.3
Test result: solid (penetration after 5 s < 15 mm)
Burning test according to 33.2.4 "Manual of Tests and Criteria" (Recommendations on the TRANSPORT OF DANGEROUS GOODS [United Nations]):
Burning rate: ≤ 2.2 mm/s (Not a dangerous good according to ADR class 4.1)

Modified data compared to the previous version

The following sections have been updated:

- Section 3
- Section 8
- Section 11
- Section 12
- Section 15

Contact Point : Prepared by: Global Regulatory Department
EU-MSDS@hbfuller.com

Classification of the mixture:

Resp. Sens. 1 H334

Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IE / EN