

# Technical data sheet



Product: 764

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: KLEBEBAND

Article group: EINSEITIG

Download: 07.12.2025

## GENERAL PURPOSE VINYL TAPE 764

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH  
Industriestraße 15  
D-75382 Althengstett

Telephone:  
+49(0)7051/9297-0  
Fax:  
+49(0)7051/9297-99

E-Mail:  
info@tewipack.de  
Website:  
www.tewipack.de

Managing director:  
Alexander Uhl,  
Michael Uhl  
HRB 330424  
Amtsgericht  
Stuttgart

Bank details:  
Sparkasse  
Sindelfingen  
Pforzheim  
Calw  
BLZ 666 500  
85  
Konto 17 787

Commerzbank  
Sindelfingen  
BLZ 603 400 71  
Konto 8 001 166

Vereinigte  
Volksbank AG  
Böblingen  
BLZ 603 900 00  
Konto 80 089  
003

Postbank  
Stuttgart  
BLZ 600 100  
70  
Konto 146  
294 708

# Technical Data

## General Purpose Vinyl Tape 764

<b>Product Description</b>	3M™ General Purpose Vinyl Tape 764 can be used in non-critical applications such as colour coding, bundling and safety marking, etc.			
<b>Product Construction</b>	<b>Backing</b>	<b>Adhesive</b>	<b>Colour</b>	<b>Standard Roll Length</b>
	Polyvinyl chloride	Rubber	Yellow, white, red, black, blue, transparent, green, orange, purple, grey, brown	Yellow, red and white: 25 mm, 50 mm, 75 mm, 1250 mm* x 33 m (1", 2", 3", 50" x 36 yds.) All other colours: 25 mm, 50 mm, 75 mm, 1250 mm* x 33 m (1", 2", 50" x 36 yds.)
*Log rolls are untrimmed, approximately 116.8 cm (49") usable material.				
<b>Typical Physical Properties</b>	<b>Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.</b>			
				<b>ASTM Test Method</b>
	Adhesion to Steel:	21 N/100 mm (18 oz./in. width)		D-3330
	Tensile Strength:	228 N/100 mm (13 lbs./in. width)		D-3759
	Elongation at Break:	180%		D-3759
	Total Thickness:	0.125 mm (5.0 mils) nominal		D-3652
	Temperature Use Range:	60°F to 85°F (16°C to 29°C)		
<b>Features</b>	<ul style="list-style-type: none"> <li>While vinyl tapes resist most common solvents, care should be taken to avoid ketones, chlorinated hydrocarbons and esters found in lacquers, thinners, degreasers, paint strippers, etc., which may cause the backing to swell or curl</li> <li>Pigmented vinyl backing to conform to many irregular surfaces</li> <li>Rubber adhesive for good instant adhesion</li> </ul>			
<b>Application Techniques</b>	Best results are attained when applied to a clean, dry surface at temperatures between 16°C to 27°C (60°F to 80°F).			
<b>Application Ideas</b>	<ul style="list-style-type: none"> <li>General-purpose holding and colour coding</li> <li>Temporary marking of parts or machines</li> <li>Protect parts, equipment or products from abrasion</li> </ul>			
<b>Storage</b>	Store under normal conditions of 16°C to 27°C (60° to 80°F) and 40 to 60% R.H. in the original carton.			
<b>Shelf Life</b>	To obtain best performance, use this product within 18 months from date of manufacture.			

# General Purpose Vinyl Tape 764

<b>Technical Information</b>	The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.
<b>Product Use</b>	Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.
<b>Warranty, Limited Remedy, and Disclaimer</b>	<p>Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.</p> <p>If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.</p>
<b>Limitation of Liability</b>	Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



**3M Industrial Adhesives and Tapes Division**

**3M Canada**

P.O. Box 5757

London, ON N6A 4T1

Phone 1-800-364-3577

Web [3M.ca/AssemblySolutions](http://3M.ca/AssemblySolutions)

3M and 3M Science. Applied to Life. are trademarks of 3M. Used under license in Canada.  
© 2017, 3M. All rights reserved. 170709398 E BA-17-24361