# Technical data sheet



**Product:** 8959

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: **KLEBEBAND** 

Article group: **EINSEITIG** 

Download: 31.08.2025

SCOTCH FILAMENT TAPE 8959

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Calw

Konto 17 787



# **Product Data Sheet**

October 2009

Supersedes: December 2003

Product Description	8959 is a general purpose tape reinforced with two directional (cross weave) glass filaments.
Key Features	The ScotchPro™ polypropylene backing provides excellent abrasion, moisture and scuff resistance.
	The adhesive is specially formulated to provide good adhesion to fiberboard surfaces.

## Construction

Adhesive Type	Synthetic Rubber Resin
	(Hot Melt)
Backing	
_	BOPP
Reinforcement	Glass Yarns
Total Thickness	
AFERA 5006	130 µm
	·
Core size (ID)	76 mm (3")
Colour	Transparent
Coloui	·

# **Performance Characteristics**

Adhesion to Stainless Steel AFERA 5001	9,0 N/cm
Tensile Strength AFERA 5004	280 N/cm
Elongation at Break AFERA 5004	6 %
Static Shear AFERA 5012	2000+ minutes

Storage	Store in clean dry place. Temperature of 21 °C and 50 % relative humidity are recommended.
Shelf Life	Scotch 8959 has a shelf life of 12 months from date of dispatch by 3M.
Precautionary Information	Refer to product label and Material Safety Data Sheet for health and safety information before using the product. For information please contact your local 3M Office.  www.3M.com
For Additional Information	To request additional product information see address below
Important Notice	All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications.

This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark of the 3M Company.

## 3M United Kingdom PLC

2M Centre, Cain Road, Bracknell RG12 8HT United Kingdom

## 3M Ireland Ltd

The Iveagh Building, 3rd Floor The Park, Carrickmines 18 Ireland

# 3M Belgium bvba/sprl

Hermeslaan 7 1831 Diegem Belgium

# **3M Nederland B.V.** Molengraaffsingel 29

2629 JD Delft The Netherlands

#### 3M Svenska AB

Herrjärva torg 4 170 67 Solna Sweden

#### 3M a/s

Hannemanns Allé 53 DK-2300 Copenhagen S. Denmark

# 3M Norge AS

Tærudgata 16 2004 Lillestrøm Norway

# Suomen 3M Oy

Keilaranta 6 02150 Espoo Finland

#### 3M Eesti OÜ

Pärnu mnt. 158 11317 Tallinn Estonia

#### 3M Latvia SIA

K.Ulmaņa gatve 5 Rīga, LV-1004 Latvia

# 3M Lietuva UAB

A.Goštauto g. 40 Vilnius LT- 03163 Lithuania