

# Technical data sheet



Product: GPH

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: KLEBEBAND

Article group: DOPPELSEITIG

Download: 24.06.2026

3M™ VHB™ GPH-060GF/110GF/160GF

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH  
Industriestraße 15  
D-75382 Althengstett

Telephone:  
+49(0)7051/9297-0  
Fax:  
+49(0)7051/9297-99

E-Mail:  
info@tewipack.de  
Website:  
www.tewipack.de

Managing director:  
Alexander Uhl,  
Michael Uhl  
HRB 330424  
Amtsgericht  
Stuttgart

Bank details:  
Sparkasse  
Sindelfingen  
Pforzheim  
Calw  
BLZ 666 500  
85  
Konto 17 787

Commerzbank  
Sindelfingen  
BLZ 603 400 71  
Konto 8 001 166

Vereinigte  
Volksbank AG  
Böblingen  
BLZ 603 900 00  
Konto 80 089  
003

Postbank  
Stuttgart  
BLZ 600 100  
70  
Konto 146  
294 708

# 3M<sup>™</sup> VHB<sup>™</sup> GPH Series

## Product Data Sheet

September 2022  
Supersedes: September 2017

**Product Description** 3M<sup>™</sup> VHB<sup>™</sup> GPH Series, a general purpose, high temperature, grey conformable double coated acrylic foam tape with a high initial tack and a soft foam. Available in three different thicknesses with a 3M branded red siliconised polyethylene film liner.

- Key Features**
- Double coated acrylic foam tape
  - 100 % closed cell acrylic foam
  - High temperature performance (short term 230 °C)
  - Good balance of high temperature and peel & shear performance
  - High initial tack
  - Soft foam enables stress relaxation & an easy application
  - Good sealing properties
  - For indoor and outdoor applications

- Applications & Benefits**
- Its temperature performance enables bonding of materials in applications with high operating temperatures such as prior to processing in a powder coating line
  - Capability to bond to a variety of substrates makes it a good fit for multi material bonding - those substrates have a high or medium surface energy including many metals (e.g. stainless steel) and plastics (e.g. Polyamide, PMMA, ABS)
  - For applications in metal working, signage, appliances and specialty vehicle

**Physical Properties**

	GPH-060GF	GPH-110GF	GPH-160GF
<b>Adhesive Type</b>	Acrylic foam adhesive		
<b>Thickness</b> acc. to ASTM D-3652	0.60 mm	1.10 mm	1.60 mm
<b>Foam Density</b>	710 kg/m <sup>3</sup>		
<b>Release Liner</b>	3M branded red siliconised polyethylene film		
<b>Tape Colour</b>	Grey		

**Performance Characteristics**

Type	GPH-060GF	GPH-110GF	GPH-160GF
<b>90 ° Peel adhesion to Stainless Steel</b> acc. to ASTM D3330, 90° peel angle @ RT, after 72h @ RT dwell	25 N/cm	37 N/cm	34 N/cm
<b>90 ° Peel adhesion to PA6</b> acc. to ASTM D3330, 90° peel angle @ RT, after 72h @ RT dwell	33 N/cm	48 N/cm	55 N/cm
<b>90 ° Peel adhesion to ABS</b> acc. to ASTM D3330, 90° peel angle @ RT, after 72h @ RT dwell	21 N/cm	33 N/cm	32 N/cm
<b>90 ° Peel adhesion to PMMA</b> acc. to ASTM D3330, 90° peel angle @ RT, after 72h @ RT dwell	21 N/cm	34 N/cm	37 N/cm
<b>Dynamic Shear</b> acc. to ASTM D1002 on stainless steel, after 72h @ RT dwell	547 N/6.54 cm <sup>2</sup>	476 N/6.54 cm <sup>2</sup>	375 N/6.54 cm <sup>2</sup>
<b>Static Shear Strength</b> acc. to ASTM D3654, after 72h @ RT dwell (Weight held for 10.000 minutes to stainless steel, 3.32cm <sup>2</sup> (0.5in <sup>2</sup> ))	23 °C - 1000 g 150 °C - 500 g		
<b>Normal Tensile (T-Block)</b> acc. to ASTM D897 to Aluminium @ RT, after 72h @ RT dwell, 6.45 cm <sup>2</sup> , test speed 50 mm/min	410 N/6.54 cm <sup>2</sup>	439 N/6.54 cm <sup>2</sup>	470 N/6.54 cm <sup>2</sup>
<b>Temperature Performance</b>	Short term (minutes, hours): 230 °C Long term (days, weeks): 150 °C		

**Application Temperature**

Ideal application temperature range is 21 °C to 38 °C. Pressure sensitive adhesives use viscous flow to achieve substrate contact area.

**Low Temperature Application:**

3M™ VHB™ GPH Tape be applied at 10 °C and down to 5 °C when using 3M Adhesion Promoter AP111 or Primer 94

To obtain good performance with all 3M™ VHB™ Tapes, it is important to ensure that the surfaces are clean, dry and free of condensed moisture.

**Shelf Life**

24 months from date of production when stored at 16 °C – 25 °C and 40-65 % relative humidity.

Performance of tapes is not projected to change even after shelf life expires; however, 3M does suggest that 3M™ VHB™ Tapes are used prior to the shelf life date whenever possible.

---

**Automotive  
Disclaimer**

Automotive Applications: This product is an industrial product and has not been designed or tested for use in certain automotive applications, including, but not limited to, automotive electric powertrain battery or high voltage applications. This product does not fully adhere to typical automotive design or quality system requirements, such as IATF 16949 or VDA 6.3. This product may not be manufactured in an IATF certified facility and may not meet a Ppk of 1.33 for all properties. The product may not undergo an automotive production part approval process (PPAP). Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's automotive application and for conducting incoming inspections before use of the product. Failure to do so may result in injury, death, and/or harm to property. No written or verbal statement, report, data or recommendation by 3M related to automotive use of the product shall have any force or effect unless in an agreement signed by the Technical Director of 3M's Automotive Division. Customer assumes all responsibility and risk if customer chooses to use this product in an automotive electric powertrain battery or high voltage application, and 3M will not be liable for any loss or damage arising from or related to the 3M product or customer's use of the product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity or recall costs), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability. In no event shall 3M be liable for any damages in excess of the purchase price paid for the product.

NOTWITHSTANDING ANY OTHER STATEMENT TO THE CONTRARY, 3M MAKES NO REPRESENTATIONS, WARRANTIES OR CONDITIONS WHATSOEVER, EXPRESS OR IMPLIED, REGARDING THE PRODUCT IF USED IN AN AUTOMOTIVE ELECTRIC POWERTRAIN BATTERY OR HIGH VOLTAGE APPLICATION, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY ON PERFORMANCE, LONGEVITY, SUITABILITY, COMPATIBILITY, OR INTEROPERABILITY, OR ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE.

---

---

**Important Notice**

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law.

---

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

---

3M and VHB are trademarks of the 3M Company

**3M United Kingdom PLC**  
2M Centre, Cain Road, Bracknell  
RG12 8HT  
United Kingdom

**3M Svenska AB**  
Herrjärva torg 4  
170 67 Solna  
Sweden

**3M Eesti OÜ**  
Pärnu mnt. 158  
11317 Tallinn  
Estonia

**3M Ireland Ltd**  
The Iveagh Building, 3rd Floor  
The Park, Carrickmines 18  
Ireland

**3M a/s**  
Hannemanns Allé 53  
DK-2300 Copenhagen S.  
Denmark

**3M Latvia SIA**  
K.Ulmaņa gatve 5  
Rīga, LV-1004  
Latvia

**3M Belgium bvba/sprl**  
Hermeslaan 7  
1831 Diegem  
Belgium

**3M Norge AS**  
Tærudgata 16  
2004 Lillestrøm  
Norway

**3M Lietuva UAB**  
A.Goštauto g. 40  
Vilnius LT- 03163  
Lithuania

**3M Nederland B.V.**  
Molengraaffsingel 29  
2629 JD Delft  
The Netherlands

**Suomen 3M Oy**  
Keilaranta 6  
02150 Espoo  
Finland