

# Technical data sheet



Product: 9460, 9469, 9473

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: KLEBEBAND

Article group: DOPPELSEITIG

Download: 01.05.2026

**3M VHB (F)9460PC,(F)9469PC/FL,(F)9473PC**

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH  
Industriestraße 15  
D-75382 Althengstett

Telephone:  
+49(0)7051/9297-0  
Fax:  
+49(0)7051/9297-99

E-Mail:  
info@tewipack.de  
Website:  
www.tewipack.de

Managing director:  
Alexander Uhl,  
Michael Uhl  
HRB 330424  
Amtsgericht  
Stuttgart

Bank details:  
Sparkasse  
Sindelfingen  
Pforzheim  
Calw  
BLZ 666 500  
85  
Konto 17 787

Commerzbank  
Sindelfingen  
BLZ 603 400 71  
Konto 8 001 166

Vereinigte  
Volksbank AG  
Böblingen  
BLZ 603 900 00  
Konto 80 089  
003

Postbank  
Stuttgart  
BLZ 600 100  
70  
Konto 146  
294 708



# VHB™ Adhesive Transfer Tapes with High Performance Acrylic Adhesive 100MP

**F9460PC • F9469PC • F9473PC • 9460PC • 9469PC • 9473PC • 9469FL**

## Product Data Sheet

Date: September 2022  
Supersedes: July 2018

### Product Description

3M™ VHB™ Adhesive Transfer Tapes F9460PC, 9460PC, F9469PC, 9469PC, 9469FL, F9473PC and 9473PC utilize the 3M™ High Performance Acrylic Adhesive 100MP, which has good long term holding power.

### Key Features

- For interior and exterior industrial applications to replace rivets, spot welds and other permanent fasteners.
- 3M™ VHB™ Adhesive Transfer Tapes are transparent

### Physical Properties

| Products            | F9460PC<br>9460PC   | F9469PC<br>9469PC | F9473PC<br>9473PC |
|---------------------|---|-------------------|-------------------|
| Adhesive thickness* | 0,050 mm  | 0,125 mm          | 0,250 mm          |
| Liner thickness *   | 0,100 mm  |                   |                   |
| Liner weight        | 100 g/sqm   |                   |                   |
| Liner material      | Polycoated paper, brown   |                   |                   |
| Liner printing      | Versions with "F" prefix have liner printing<br>Versions without "F" have no printing |                   |                   |
| Adhesive colour     | transparent   |                   |                   |

\*AFERA 5006

| Products            | 9469FL                   |
|---------------------|--------------------------|
| Adhesive thickness* | 0,125 mm                 |
| Liner thickness *   | 0,100 mm                 |
| Liner weight        | 100 g/sqm                |
| Liner material      | Polypropylene, unprinted |
| Adhesive colour     | transparent              |

## Performance Characteristics

| Products  | F9460PC<br>9460PC | F9469PC<br>9469PC<br>9469FL | F9473PC<br>9473PC |
|---|-------------------|-----------------------------|-------------------|
| <b>Adhesion to Stainless Steel</b><br>(FTM2 - after 72 h RT using 50 µm aluminium foil) | 12,0 N/cm         | 19,5 N/cm                   | 19,5 N/cm         |
| <b>Adhesion to PET</b><br>(FTM2 - after 72 h RT using 50 µm aluminium foil)             | 8,7 N/cm          | 11,1 N/cm                   | 12,4 N/cm         |
| <b>Static Shear</b><br>(FTM8 - 1000 g/25 mm* 12,5 mm on stainless steel, 150 °C)        | > 10,000 Minutes  |                             |                   |

|  |  |
|--|--|
| <b>Immersion 7 days in Engine oil at 50 °C</b>                             | No changes in appearance                                       |
| <b>Immersion 7 days in 5 % salt water</b>                                  | No changes in appearance                                       |
| <b>7 days high humidity chamber 38 °C, 100 RH</b>                          | No changes in appearance                                       |
| <b>7 days automotive cycle 4 h -40 °C, 4 h 90 °C, 16 h 38 °C, 100 % RH</b> | No changes in appearance                                       |
| <b>Storage 4 h at 260 °C</b>   | No changes in appearance                                       |
| <b>Immersion 1 h in Gasoline</b>   | No changes in appearance                                       |
| <b>Immersion 1 h 5 % H2SO4</b>   | No changes in appearance<br>Slight adhesión loss 1 mm at edges |
| <b>Immersion 1 h 5 % NaOH</b>  | No changes in appearance<br>Slight adhesión loss 1 mm at edges |

These 3M™ VHB™ Adhesive Transfer Tapes are made from the same adhesive system and are thermoplastic in nature, becoming softer as temperature increases and firmer as temperature decreases. As the adhesive becomes firmer, the adhesion performance generally increases. At low temperatures (lower than -40 °C, the 3M™ VHB™ Adhesive Transfer Tapes become very firm and glassy; the ability to absorb impact energy is reduced.

## Application Techniques

Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure helps develop better adhesive contact and improve bond strength. To obtain optimum adhesion, the bonding surfaces must be clean, dry, and well unified. Some typical surface cleaning solvents are isopropyl alcohol/water mixture or heptane. \*

Ideal tape application temperature range is 21 °C to 38 °C. Initial tape application to surfaces at temperatures below 10 °C is not recommended because the adhesive becomes too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.

**\*Note:** Be sure to follow the manufacturer's precautions and directions for use when using solvents.

---

|                                 |   |
|---------------------------------|---|
| <b>Storage &amp; Shelf Life</b> | Store at 16 °C – 25 °C and 40-65 % relative humidity in its original box. The product can be stored up to 18 months after production. |
|---------------------------------|---|

---

|                                    |                               |
|------------------------------------|-------------------------------|
| <b>Recognition / Certification</b> | UL-Recognised in File MH17478 |
|------------------------------------|-------------------------------|

---

|                                  |  |
|----------------------------------|--|
| <b>Precautionary Information</b> | <p>TSCA: These products are defined as articles under the Toxic Substances Certification Control Act and therefore, are exempt from inventory listing requirements.</p> <p>MSDS: These products are not subject to the MSDS requirements of the Occupational Safety and Health Administration's Hazard Communication Standard, 29 C.F.R. 1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the 3M directions for use, the products should not present a health and safety hazard. However, use or processing of the products in a manner not in accordance with the directions for use may affect their performance and present potential health and safety hazards.</p> |
|----------------------------------|--|

---

|                                   |  |
|-----------------------------------|--|
| <b>For Additional Information</b> | <p>To request additional product information or to arrange for sales assistance, call.....<br/>Address correspondence to: 3M</p> |
|-----------------------------------|--|

---

|                              |  |
|------------------------------|--|
| <b>Automotive Disclaimer</b> | <p>Automotive Applications: This product is an industrial product and has not been designed or tested for use in certain automotive applications, including, but not limited to, automotive electric powertrain battery or high voltage applications. This product does not fully adhere to typical automotive design or quality system requirements, such as IATF 16949 or VDA 6.3. This product may not be manufactured in an IATF certified facility and may not meet a Ppk of 1.33 for all properties. The product may not undergo an automotive production part approval process (PPAP). Customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's automotive application and for conducting incoming inspections before use of the product. Failure to do so may result in injury, death, and/or harm to property. No written or verbal statement, report, data or recommendation by 3M related to automotive use of the product shall have any force or effect unless in an agreement signed by the Technical Director of 3M's Automotive Division. Customer assumes all responsibility and risk if customer chooses to use this product in an automotive electric powertrain battery or high voltage application, and 3M will not be liable for any loss or damage arising from or related to the 3M product or customer's use of the product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity or recall costs), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability. In no event shall 3M be liable for any damages in excess of the purchase price paid for the product.</p> <p>NOTWITHSTANDING ANY OTHER STATEMENT TO THE CONTRARY, 3M MAKES NO REPRESENTATIONS, WARRANTIES OR CONDITIONS WHATSOEVER, EXPRESS OR IMPLIED, REGARDING THE PRODUCT IF USED IN AN</p> |
|------------------------------|--|

---

AUTOMOTIVE ELECTRIC POWERTRAIN BATTERY OR HIGH VOLTAGE APPLICATION, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTY ON PERFORMANCE, LONGEVITY, SUITABILITY, COMPATIBILITY, OR INTEROPERABILITY, OR ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE.

---

### Important Notice

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

---

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

---

3M is a trademark the 3M Company.

**3M United Kingdom PLC**  
2M Centre, Cain Road, Bracknell  
RG12 8HT  
United Kingdom

**3M Svenska AB**  
Herrjärva torg 4  
170 67 Solna  
Sweden

**3M Eesti OÜ**  
Pärnu mnt. 158  
11317 Tallinn  
Estonia

**3M Ireland Ltd**  
The Iveagh Building, 3rd Floor  
The Park, Carrickmines 18  
Ireland

**3M a/s**  
Hannemanns Allé 53  
DK-2300 Copenhagen S.  
Denmark

**3M Latvia SIA**  
K.Ulmaņa gatve 5  
Rīga, LV-1004  
Latvia

**3M Belgium bvba/sprl**  
Hermeslaan 7  
1831 Diegem  
Belgium

**3M Norge AS**  
Tærudgata 16  
2004 Lillestrøm  
Norway

**3M Lietuva UAB**  
A.Goštauto g. 40  
Vilnius LT- 03163  
Lithuania

**3M Nederland B.V.**  
Molengraaffsingel 29  
2629 JD Delft  
The Netherlands

**Suomen 3M Oy**  
Keilaranta 6  
02150 Espoo  
Finland