

Technical data sheet



Product: 2903

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: KLEBEBAND

Article group: EINSEITIG

Download: 09.05.2025

3M™ SCOTCH® DUCT CLOTH TAPE 2903

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708

3M[®] Scotch[®] Duct Cloth Tape 2903

Product Data Sheet

June 2016
Supersedes: New

Product Description

3M™ Scotch® Duct Cloth Tape 2903 is a general purpose conformable cloth duct tape made with polyethylene film over cloth scrim and a synthetic rubber adhesive. A good choice for general maintenance, bundling, wrapping, attaching, sealing, protecting, and colour coding.

Key Features

- Aggressive synthetic rubber adhesive provides instant adhesion to a wide variety of surfaces
- Cloth scrim tears straight in both directions.
- Cloth scrim has high tensile strength, ideal for bundling materials
- Conformable and can be applied to irregular surfaces

Physical Properties

Thickness AFERA 5006) Tape Liner	0,15 mm None
Adhesive Type	Synthetic rubber and resin
Tape Colour	Black, White and Silver

Performance Characteristics

Adhesion to Stainless Steel (AFERA 5001 TM A)	8 N / cm
Tensile Strength (AFERA 5004 MD)	100 N / 25cm
Elongation at Break (AFERA 5004 MD)	30%

Storage & Shelf Life

Store at 16 °C – 25 °C and 40-65 % relative humidity in its original box. The product can be stored up to 12 months after production.

For Additional Information

To request additional product information or to arrange for sales assistance, please see below for contact details.

Important Notice

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

3M is a trademark the 3M Company.

**3M Svenska AB
Industri**

Bollstanäsvägen 3
191 89 Sollentuna

Tel: 08-92 21 00

Fax: 08-92 22 88

E-post:

kundservice@mmm.co

[m](http://www.3M.se/tejp)

www.3M.se/tejp

**3M a/s
Industri**

Hannemanns Allé 53
2300 København S

Tlf.: 43 48 01 00

Fax.: 43 20 15 65

E-mail:

dkindustri@mmm.co

[m](http://www.3Mindustri.dk)

www.3Mindustri.dk

**3M Norge AS
Avd. Industri**

Hvamveien 6

2013 Skjetten

Tel: 0 63 84

Fax: 63 84 17 88

E-post:

Kundeservice@mmm.co

[m](http://www.3M.no/tape)

www.3M.no/tape

**Suomen 3M Oy
Teollisuustuotteet**

PL 600

Keilaranta 6

02151 Espoo

Puh: 09-525 21

Fax: 09-525 2279

www.3M.fi/teollisuus