

Technical data sheet



Product: 389

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: KLEBEBAND

Article group: EINSEITIG

Download: 31.08.2025

SCOTCH® TAPE 389 CLOTH TAPE

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708



Scotch®

Tape 389 Cloth Tape

Product Information

06/04

Product Description / Markets

Scotch® Tape 389 is a polyethylene treated closely woven cloth tape that has excellent holding power and conformability, and it is hand tearable. It is available in 9 different colours and it is used in a variety of industrial applications.

Features	Advantages	Benefits
* Polyethylene coated cloth backing	* Conformability	* Can cover irregular shaped surfaces
	* Easy tear by hand	* No need for special dispensers
	* Resists moisture	* Can be used in some aqueous environments
	* Good tensile strength	* Toughness
	* Available in many colours	* Good contrast to different surfaces
* Crosslinked rubber resin adhesive	* High instant adhesion	* Sticks easily
	* Good holding power	* Resists lifting
	* Adheres aggressively to a wide variety of surfaces	* Useful for many general purposes

Applications / Performance

Scotch® Tape 389 can be used for colour coding, pipe wrapping, container sealing, repairing, temporary holding of floor carpets, reinforcing, decorating, splicing and a variety of industrial applications. The temperature resistance of this tape is up to 70 °C for one hour.

Scotch® Tape 389

Product Characteristics

Thickness	:	0.26 mm	AFERA 4006
Adhesion to steel	:	22.5 N/25 mm	AFERA 4001
Tensile strength	:	200 N/25 mm	AFERA 4004
Elongation	:	6 %	AFERA 4005
Temperature performance	:	70 °C/ 1 hour	

Satisfactory performance of Scotch® Tape 389 will be achieved at varying temperatures/time exposure on many substrates. If Scotch® Tape 389 needs to be removed from a surface, tests should be conducted to establish Scotch® Tape 389 performance parameters in your process conditions.

Available Sizes/Coloures

Width (mm)	:	19, 25, 38, 50, 75 and 100
Length (m)	:	50
Colours	:	Black, brown, red, white, silver, olive, yellow, dark and light blue*

*Note: not all colours are available in all sizes, check with 3M Sales Representative for further information.

Storage Conditions

Store in clean dry place. Temperature of 21 °C and 50 percent relative humidity are recommended.

Disclaimer

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



Industrial Adhesives & Tapes Division
3M Belgium
Hermeslaan 7
1831 Diegem
Belgium

Industrial Adhesives & Tapes Division
3M Nederland
Molengraafsingel 29
2629 JD Delft
Nederland