

Technical data sheet



Product: 9050

Manufacturer: H.B. FULLER

Product group: KLEBSTOFF

Article group: PRIMER

Download: 17.05.2024

CYBERBOND CB 9050

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708



CB 9050

Technical Datasheet

The Primer Cyberbond 9050 enables you to bond unpolare materials such as e. g. Polyethylene (PE), Polypropylene (PP), Polyoxymethylene (POM), Silicone as well as modern Thermoplastic Elastomere (TPE) by means of Cyberbond Cyanoacrylate Adhesive. Cyberbond 9056 changes the surface tension. The advantages are:

- high strength bonding of materials which could not be bonded before
- a fast and easy to use method to support bonding,
- a higher flexibility of choosing materials.

Cyberbond 9050 will be brushed on the mating parts. After evaporation application of Cyberbond Cyanoacrylate Adhesive immediately can start. The parts also can be temporarily stored for 24 h.

Shelf life: 1 year after delivery

LINOP Equipment

Cyberbond offers by means of the LINOP Equipment range suitable dosing and LED based curing devices. We also refer to suitable dosing tips which help an economical use of the adhesives (also if used manually).

Storage

Store products in a cold and dark place. Before use allow to reach ambient temperature.

For safe handling consult Material Saftey Data Sheet (MSDS).

Cyberbond Europe GmbH
A H.B. Fuller Company
Werner-von-Siemens-Straße 2
31515 Wunstorf
Germany
Tel.: +49 / 50 31 / 95 66 - 0
www.cyberbond.de

