# Security data sheet



**Product:** F201HV

Manufacturer: PERMABOND ENGINEERING ADHESIVES

Product group: **KLEBSTOFF** 

Article group: ANAEROB

Download: 07.05.2024

### PERMABOND F201HV

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Konto 17 787



## **Permabond F201HV**

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 1 / 15

## **Safety Data Sheet**

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name Permabond F201HV

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Adhesive

Identified Uses Industrial Professional Consumer
Use -

### 1.3. Details of the supplier of the safety data sheet

Name Permabond Engineering Adhesives
Full address Niederkasseler Lohweg 18
District and Country 40547 Düsseldorf
Germany

Tel. +44 (0)1962 711 661

e-mail address of the competent person

responsible for the Safety Data Sheet

info.europe@permabond.com

Supplier: Permabond Engineering Adhesives Ltd

Wessex Way, Colden Common,

Winchester, Hampshire SO21 1WP, UK

tel: +44 (0)1962 711 661

mail: info.europe@permabond.com

### 1.4. Emergency telephone number

For urgent inquiries refer to +44 (0)1962 711 661 ( 8.00 am-5.00 pm Mon-Fri)

CHEMTREC UK: +(44)-870-8200418
CHEMTREC Ireland: +(353)-19014670
CHEMTREC Australia: +(61)-290372994
CHEMTREC New Zealand: +(64)-98010034

### **SECTION 2. Hazards identification**

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

toxicity, category 3

| Reproductive toxicity, category 1B                | H360D | May damage the unborn child.                       |
|---|-------|--|
| Serious eye damage, category 1                    | H318  | Causes serious eye damage.                         |
| Skin irritation, category 2                       | H315  | Causes skin irritation.                            |
| Specific target organ toxicity - single exposure, | H335  | May cause respiratory irritation.                  |
| category 3  |       |  |
| Skin sensitization, category 1                    | H317  | May cause an allergic skin reaction.               |
| Hazardous to the aquatic environment, chronic     | H412  | Harmful to aquatic life with long lasting effects. |
|   |       |  |

#### E١



### **Permabond Engineering Adhesives**

### Permabond F201HV

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 2 / 15

### SECTION 2. Hazards identification .../>>

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H360DMay damage the unborn child.H318Causes serious eye damage.H315Causes skin irritation.

H335 May cause respiratory irritation.H317 May cause an allergic skin reaction.

**H412** Harmful to aquatic life with long lasting effects.

Restricted to professional users.

Precautionary statements:

P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P302+P352 In case of contact with the skin: wash abundantly with soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice / attention.

Contains: TETRAHYDROFURFURYL METHACRYLATE

CUMYL HYDROPEROXIDE METHACRYLIC ACID

HYDROXYPROPYL METHACRYLATE

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

### SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

TETRAHYDROFURFURYL METHACRYLATE

INDEX  $30 \le x < 60$  Repr. 1B H360D, Skin Sens. 1 H317, Aquatic Chronic 3 H412

EC 219-529-5 CAS 2455-24-5

REACH Reg. 1-2120748481-53-XXXX HYDROXYPROPYL METHACRYLATE

INDEX 10 ≤ x < 30 Eye Irrit. 2 H319, Skin Sens. 1 H317

EC 248-666-3 CAS 27813-02-1

REACH Reg. 01-2119490226-37-XXXX

2-PROPENOIC ACID, 2-METHYL-, 2-HYDROXY-3-[(1-OXO-2-PROPENYL)OXY]PROPYL ESTER, POLYMER WITH 1,3-BUTADIENE AND 2-PROPENENITRILE, 1-CYANO-4-[2-HYDROXY-3-[(2-METHYL-1-OXO-2-PROPENYL)OXY]PROPOXY]-1-METHYL-4-OXOBUTYL TERMINATED

TERMINATED

INDEX  $25 \le x < 30$  Aquatic Chronic 3 H412

EC

CAS 118578-03-3

©EPY 11.5.1 - SDS 1004.14



## **Permabond F201HV**

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 3 / 15

### SECTION 3. Composition/information on ingredients

**METHACRYLIC ACID** 

INDEX 607-088-00-5  $1 \le x < 3$  Acute Tox. 3 H311, Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1A

H314, Eye Dam. 1 H318, STOT SE 3 H335, Classification note according to

Annex VI to the CLP Regulation: D

EC 201-204-4 STOT SE 3 H335: ≥ 1% CAS 79-41-4 LD50 Oral: 1320 mg/kg

LD50 Oral: 1320 mg/kg, LD50 Dermal: 750 mg/kg, STA Inhalation vapours:

11 mg/l

REACH Reg. 01-2120741502-64-XXXX

**CUMYL HYDROPEROXIDE** 

*IDEX* 1 ≤ x < 2,5 **Org. Perox E H242, Acute Tox. 3 H331, Acute Tox. 4 H302, Acute Tox. 4** 

H312, STOT RE 2 H373, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3  $\,$ 

H335, Aquatic Chronic 2 H411

Skin Corr. 1B H314: ≥ 10%, Skin Irrit. 2 H315: ≥ 3%, STOT SE 3 H335: ≥ 1%

LD50 Oral: 382 mg/kg, LD50 Dermal: 1400 mg/kg, STA Inhalation

mists/powders: 0,501 mg/l

REACH Reg. 01-2119475796-19-XXXX

201-254-7

80-15-9

CUMENE

EC

CAS

INDEX 601-024-00-X  $0 \le x < 0,1$  **F** 

Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, Aquatic Chronic 2

H411

EC 202-704-5 CAS 98-82-8

REACH Reg. 01-2119473983-24-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

Skin: Wash the skin thoroughly with soap and water. If symptoms arise, request medical assistance

Eyes: Make sure you have removed any contact lenses before rinsing your eyes. Wash

Readyly and abundantly the eyes with water keeping the eyelids open.

Continue to rinse for at least 15 minutes. Consult a doctor if the discomfort continues. Ingestion: rinse the mouth with water thoroughly. Make a abundant quantity of water drink.

Do not cause vomiting. Consult a doctor.

Inhalation: move the subject exposed in the open air. Consult a doctor in case of serious symptoms or

persistent.

### 4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash. Contact with eyes: irritating and can cause redness and pain.

### 4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor no specific recommendation. Symptomatic treatment.

### **SECTION 5. Firefighting measures**

### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO2), and nitric oxides (NOx).

### 5.3. Advice for firefighters

### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.



## **Permabond F201HV**

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 4 / 15

### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### **SECTION 6. Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### **SECTION 7. Handling and storage**

### 7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 6.1C

### 7.3. Specific end use(s)

Adhesive

### **SECTION 8. Exposure controls/personal protection**

### 8.1. Control parameters

Regulatory References:

| BGR | България        | НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ,<br>СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17<br>Януари 2020г.)  |
|-----|-----------------|---|
| CZE | Česká Republika | Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb.,<br>kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů   |
| DEU | Deutschland     | Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56 |
| DNK | Danmark         | Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019   |
| ESP | España          | Límites de exposición profesional para agentes químicos en España 2021  |
| EST | Eesti           | Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse<br>nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 17.10.2019, 1 - jõust.<br>17.01.2020]                         |
| FRA | France          | Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS  |



# **Permabond F201HV**

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 5 / 15

### SECTION 8. Exposure controls/personal protection ..../>>

| FIN | Suomi          | HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25  |
|-----|----------------|---|
| GRC | Ελλάδα         | Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"» |
| HUN | Magyarország   | Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről   |
| HRV | Hrvatska       | Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama<br>na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)  |
| ITA | Italia         | Decreto Legislativo 9 Aprile 2008, n.81   |
| LTU | Lietuva        | Jsakymas dėl lietuvos higienos normos hn 23:2011 "cheminių medžiagų profesinio poveikio<br>ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai" patvirtinimo  |
| LVA | Latvija        | Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības<br>prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)  |
| NOR | Norge          | Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255   |
| NLD | Nederland      | Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit   |
| PRT | Portugal       | Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos   |
| POL | Polska         | Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy   |
| ROU | România        | Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006   |
| SWE | Sverige        | Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska<br>gränsvärden (AFS 2018:1)  |
| SVK | Slovensko      | NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov  |
| SVN | Slovenija      | Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)   |
| TUR | Türkiye        | Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik<br>12.08.2013 / 28733   |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits (Fourth Edition 2020)   |
| EU  | OEL EU         | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.  |
|     | TLV-ACGIH      | ACGIH 2022  |

|                         |                | Н           | YDROXYPROF | YL METHACE | RYLATE       |          |         |          |
|-------------------------|----------------|-------------|------------|------------|--------------|----------|---------|----------|
| Predicted no-effect cor | ncentration    | - PNEC      |            |            |              |          |         |          |
| Normal value in fresh   | water          |             |            |            |              | 0,904    | mg/l    |          |
| Normal value in marii   | ne water       |             |            |            |              | 0,09     | mg/l    |          |
| Normal value for fres   | h water sedi   | ment        |            |            |              | 6,28     | mg/kg/d |          |
| Normal value for mar    | ine water se   | diment      |            |            |              | 6,28     | mg/kg/d |          |
| Normal value of STP     |                |             | 10         | mg/l       |              |          |         |          |
| Normal value for the    | terrestrial co | mpartment   |            |            |              | 0,727    | mg/kg/d |          |
| lealth - Derived no-eff | ect level - D  | NEL / DMEL  |            |            |              |          |         |          |
|                         | Effects or     | n consumers |            |            | Effects on v | vorkers  |         |          |
| Route of exposure       | Acute          | Acute       | Chronic    | Chronic    | Acute        | Acute    | Chronic | Chronic  |
|                         | local          | systemic    | local      | systemic   | local        | systemic | local   | systemic |
| Oral                    |                |             |            |            |              |          |         | 14.7     |
|                         |                |             |            |            |              |          |         | mg/kg/d  |
| Skin                    |                |             |            |            |              |          |         | 4.2      |
|                         |                |             |            |            |              |          |         | mg/kg    |
|                         |                |             |            |            |              |          |         | bw/d     |



# **Permabond F201HV**

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 6 / 15

### SECTION 8. Exposure controls/personal protection ....

|                  |                 |               |       | METHA   | CRYLIC ACID |              |                |         |          |
|------------------|-----------------|---------------|-------|---------|-------------|--------------|----------------|---------|----------|
| hreshold Limit   | Value           |               |       |         |             |              |                |         |          |
| Type             | Country         | TWA/8h        |       | STEL/15 | imin        | Remarks      | / Observations |         |          |
| •                |                 | mg/m3         | ppm   | mg/m3   | ppm         |              |                |         |          |
| AGW              | DEU             | 180           | 50    | 360     | 100         |              |                |         |          |
| TLV              | DNK             | 70            | 20    |         |             |              |                |         |          |
| VLA              | ESP             | 72            | 20    |         |             |              |                |         |          |
| VLEP             | FRA             | 70            | 20    |         |             |              |                |         |          |
| HTP              | FIN             | 71            | 20    |         |             |              |                |         |          |
| RV               | LVA             | 10            |       |         |             |              |                |         |          |
| TLV              | NOR             | 70            | 20    |         |             |              |                |         |          |
| TLV              | ROU             | 30            | 8,5   |         |             |              |                |         |          |
| NGV/KGV          | SWE             | 70            | 20    | 100     | 30          |              |                |         |          |
| WEL              | GBR             | 72            | 20    | 143     | 40          |              |                |         |          |
| redicted no-eff  | fect concentr   | ation - PNE   | C     |         |             |              |                |         |          |
| Normal value     | in fresh water  | •             |       |         |             |              | 0,82           | mg/l    |          |
| Normal value     | in marine wat   | er            |       |         |             |              | 0,82           | mg/l    |          |
| lealth - Derived | I no-effect lev | el - DNEL /   | DMEL  |         |             |              |                | _       |          |
|                  | Effe            | ects on consu | ımers |         |             | Effects on v | vorkers        |         |          |
| Route of expo    | sure Acu        | ıte Acı       | ute   | Chronic | Chronic     | Acute        | Acute          | Chronic | Chronic  |
|                  | loca            | al sys        | temic | local   | systemic    | local        | systemic       | local   | systemic |
| Inhalation       |                 | -             |       | 6.55    | 6.3         |              |                | 88      | 29.6     |
|                  |                 |               |       | mg/m3   | mg/m3       |              |                | mg/m3   | mg/m3    |
| Skin             |                 |               |       | -       | 2.55        |              |                | -       | 4.25     |
|                  |                 |               |       |         | mg/kg bw/d  |              |                |         | mg/kg    |
|                  |                 |               |       |         |             |              |                |         | bw/d     |

|                        |                | TETF        | RAHYDROFUR | FURYL METHA | ACRYLATE           |          |         |          |
|------------------------|----------------|-------------|------------|-------------|--------------------|----------|---------|----------|
| redicted no-effect co  | ncentration    | - PNEC      |            |             |                    |          |         |          |
| Normal value in fresh  | n water        |             |            |             |                    | 0,347    | mg/l    |          |
| Normal value in mari   | ne water       |             |            |             |                    | 0,035    | mg/l    |          |
| Normal value for fres  | h water sed    | iment       |            |             |                    | 2,12     | mg/kg/d |          |
| Normal value for mar   | ine water se   | ediment     |            |             |                    | 0,212    | mg/kg/d |          |
| Normal value of STP    | microorgan     | isms        |            |             |                    | 15,8     | mg/l    |          |
| Normal value for the   | terrestrial co | ompartment  |            |             |                    | 0,221    | mg/kg/d |          |
| ealth - Derived no-eff | ect level - D  | NEL / DMEL  |            |             |                    |          |         |          |
|                        | Effects o      | n consumers |            |             | Effects on workers |          |         |          |
| Route of exposure      | Acute          | Acute       | Chronic    | Chronic     | Acute              | Acute    | Chronic | Chronic  |
|                        | local          | systemic    | local      | systemic    | local              | systemic | local   | systemic |
| Oral                   |                |             |            | 0.5         |                    |          |         |          |
|                        |                |             |            | mg/kg/d     |                    |          |         |          |
| Inhalation             |                |             |            | 0.87        |                    |          |         | 3.53     |
|                        |                |             |            | mg/m3       |                    |          |         | mg/m3    |
| Skin                   |                |             |            | 0.5         |                    |          |         | 1        |
|                        |                |             |            | ma/ka/d     |                    |          |         | ma/ka/d  |

### 2-PROPENOIC ACID, 2-METHYL-, 2-HYDROXY-3-[(1-OXO-2-PROPENYL)OXY]PROPYL ESTER, POLYMER WITH

1,3-BUTADIENE AND 2-PROPENENITRILE,

1-CYANO-4-[2-HYDROXY-3-[(2-METHYL-1-OXO-2-PROPENYL)OXY]PROPOXY]-1-METHYL-4-OXOBUTYL TERMINATED

| TERMINATED                             |  |                   |         |            |              |          |         |          |  |  |
|--|--|-------------------|---------|------------|--------------|----------|---------|----------|--|--|
| Predicted no-effect co                 | ncentration                                | - PNEC            |         |            |              |          |         |          |  |  |
| Normal value in fresh water 0,002 mg/l |  |                   |         |            |              |          |         |          |  |  |
| Normal value in mari                   | Normal value in marine water 0,0002 mg/l   |                   |         |            |              |          |         |          |  |  |
| Normal value for mar                   | rine water, ir                             | termittent releas | е       |            |              | 0,707    | mg/l    |          |  |  |
| Normal value of STP                    | Normal value of STP microorganisms 42 mg/l |                   |         |            |              |          |         |          |  |  |
| Normal value for the                   | terrestrial co                             | mpartment         |         |            |              | 1        | mg/kg   |          |  |  |
| Health - Derived no-eff                | ect level - D                              | NEL / DMEL        |         |            |              |          |         |          |  |  |
|  | Effects o                                  | n consumers       |         |            | Effects on v | vorkers  | kers    |          |  |  |
| Route of exposure                      | Acute                                      | Acute             | Chronic | Chronic    | Acute        | Acute    | Chronic | Chronic  |  |  |
|  | local                                      | systemic          | local   | systemic   | local        | systemic | local   | systemic |  |  |
| Oral                                   |  |                   |         | 0.39       |              |          |         |          |  |  |
|  |  |                   |         | mg/kg bw/d |              |          |         |          |  |  |
| Inhalation                             |  |                   |         | 0.68       |              |          |         | 2.75     |  |  |
|  |  |                   |         | mg/m3      |              |          |         | mg/m3    |  |  |
| Skin                                   |  |                   |         | 0.39       |              |          |         | 0.78     |  |  |
|  |  |                   |         | ma/ka bw/d |              |          |         | ma/ka/d  |  |  |



## **Permabond F201HV**

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 7 / 15

SECTION 8. Exposure controls/personal protection ..../>

|                         |                |             | CUMYL HY | /DROPEROXII | DE         |          |         |            |
|-------------------------|----------------|-------------|----------|-------------|------------|----------|---------|------------|
| Predicted no-effect co  | ncentration    | - PNEC      |          |             |            |          |         |            |
| Normal value in fresh   | n water        |             |          |             |            | 0,0031   | mg/l    |            |
| Normal value in mari    | ne water       |             |          |             |            | 0,00031  | mg/l    |            |
| Normal value for fres   | h water sed    | ment        |          |             |            | 0,023    | mg/kg   |            |
| Normal value for mar    | ine water se   | diment      |          |             |            | 0,0023   | mg/kg   |            |
| Normal value for wat    | er, intermitte | nt release  |          |             |            | 0,031    | mg/l    |            |
| Normal value of STP     | microorgan     | isms        |          |             |            | 0,35     | mg/l    |            |
| Normal value for the    | terrestrial co | mpartment   |          |             |            | 0,0029   | mg/kg   |            |
| Health - Derived no-eff | ect level - D  | NEL / DMEL  |          |             |            |          |         |            |
|                         | Effects o      | n consumers |          |             | Effects on | workers  |         |            |
| Route of exposure       | Acute          | Acute       | Chronic  | Chronic     | Acute      | Acute    | Chronic | Chronic    |
|                         | local          | systemic    | local    | systemic    | local      | systemic | local   | systemic   |
| Inhalation              |                |             |          |             |            |          |         | 6<br>mg/m3 |

| Threshold Limit \ | /alue   |        |     |         |     |                        |                        |  |
|-------------------|---------|--------|-----|---------|-----|------------------------|------------------------|--|
| Type              | Country | TWA/8h |     | STEL/15 | min | Remarks / Observations | Remarks / Observations |  |
|                   |         | mg/m3  | ppm | mg/m3   | ppm |                        |                        |  |
| TLV               | BGR     | 100    | 20  | 250     | 50  | SKIN                   | SKIN                   |  |
| TLV               | CZE     | 100    | 20  | 250     | 50  | SKIN                   | SKIN                   |  |
| AGW               | DEU     | 50     | 10  | 200     | 40  | SKIN                   |                        |  |
| TLV               | DNK     | 100    | 20  |         |     | SKIN E                 | KIN E                  |  |
| VLA               | ESP     | 50     | 10  | 250     | 50  | SKIN                   | SKIN                   |  |
| TLV               | EST     | 100    | 20  | 250     | 50  | SKIN                   | SKIN                   |  |
| VLEP              | FRA     | 100    | 20  | 250     | 50  | SKIN                   | SKIN                   |  |
| HTP               | FIN     | 50     | 10  | 250     | 50  | SKIN                   | SKIN                   |  |
| TLV               | GRC     | 245    | 50  | 370     | 75  |                        |                        |  |
| AK                | HUN     | 50     |     | 250     |     | SKIN                   | SKIN                   |  |
| GVI/KGVI          | HRV     | 50     | 10  | 250     | 50  | SKIN                   |                        |  |
| VLEP              | ITA     | 50     | 10  | 250     | 50  | SKIN                   |                        |  |
| RD                | LTU     | 50     | 10  | 170     | 35  | SKIN                   | SKIN                   |  |
| RV                | LVA     | 100    | 20  | 250     | 50  | SKIN                   | SKIN                   |  |
| TLV               | NOR     | 100    | 20  | 250     | 50  | SKIN                   |                        |  |
| TGG               | NLD     | 100    |     | 250     |     | SKIN                   |                        |  |
| VLE               | PRT     | 50     | 10  | 250     | 50  | INHAL                  | NHAL                   |  |
| VLE               | PRT     | 50     | 10  | 250     | 50  | SKIN                   |                        |  |
| NDS/NDSCh         | POL     | 50     |     | 250     |     | SKIN                   | SKIN                   |  |
| TLV               | ROU     | 50     | 10  | 250     | 50  | SKIN                   | SKIN                   |  |
| NGV/KGV           | SWE     | 50     | 10  | 250     | 50  | SKIN                   | SKIN                   |  |
| NPEL              | SVK     | 50     | 10  | 250     | 50  | SKIN                   | SKIN                   |  |
| MV                | SVN     | 100    | 20  | 250     | 50  | SKIN                   |                        |  |
| ESD               | TUR     | 100    | 20  | 250     | 50  | SKIN                   |                        |  |
| WEL               | GBR     | 125    | 25  | 250     | 50  | SKIN                   | SKIN                   |  |
| OEL               | EU      | 50     | 10  | 250     | 50  | SKIN                   | SKIN                   |  |
| TLV-ACGIH         |         |        | 5   |         |     |                        |                        |  |

### Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash



## **Permabond F201HV**

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 8 / 15

### SECTION 8. Exposure controls/personal protection .../

body with soap and water after removing protective clothing.

**EYE PROTECTION** 

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

### **SECTION 9. Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

| Properties                             | Value  |                | Information       |             |                   |
|--|--------|----------------|-------------------|-------------|-------------------|
| Appearance                             | liquid |                |                   |             |                   |
| Colour                                 | brown  | l .            |                   |             |                   |
| Odour                                  | chara  | cteristic      |                   |             |                   |
| Melting point / freezing point         | not av | ailable        |                   |             |                   |
| Initial boiling point                  | not av | ailable        |                   |             |                   |
| Flammability                           | not av | ailable        |                   |             |                   |
| Lower explosive limit                  | not av | ailable        |                   |             |                   |
| Upper explosive limit                  | not av | ailable        |                   |             |                   |
| Flash point                            | > 100  | °C             |                   |             |                   |
| Auto-ignition temperature              | not av | ailable        |                   |             |                   |
| Decomposition temperature              | not av | ailable        |                   |             |                   |
| рН                                     | not av | ailable        | Reason for missir | ng data:sub | stance/mixture is |
|  |        |                | non-soluble       | (in         | water)            |
| Kinematic viscosity                    | not av | ailable        |                   |             |                   |
| Dynamic viscosity                      | ~3250  | 00 mPa.s Thixo | Temperature: 23   | °C          |                   |
| Solubility                             | not av | ailable        |                   |             |                   |
| Partition coefficient: n-octanol/water | not av | ailable        |                   |             |                   |
| Vapour pressure                        | not av | ailable        |                   |             |                   |
| Density and/or relative density        | 1      |                |                   |             |                   |
| Relative vapour density                | not av | ailable        |                   |             |                   |
| Particle characteristics               | not ap | plicable       |                   |             |                   |
|  |        |                |                   |             |                   |

### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

### **SECTION 10. Stability and reactivity**

### 10.1. Reactivity

Information not available

### 10.2. Chemical stability

The product is stable if stored in original containers at temperatures lower than the self accelerated decomposition temperature (SADT).

#### E١



### **Permabond Engineering Adhesives**

### Permabond F201HV

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 9 / 15

### SECTION 10. Stability and reactivity .../>

### 10.3. Possibility of hazardous reactions

Information not available

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition. Avoid transferring into containers that may have been contaminated with other substances. Avoid storing close to inflammable or combustible products.

### 10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

#### 10.6. Hazardous decomposition products

Thermal decomposition can lead to the formation of explosive peroxides or other potentially hazardous substances.

### **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

### ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture: > 5 mg/l
ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: >2000 mg/kg
ATE (Dermal) of the mixture: >2000 mg/kg

METHACRYLIC ACID

 LD50 (Dermal):
 750 mg/kg

 LD50 (Oral):
 1320 mg/kg

 LC50 (Inhalation vapours):
 7,1 mg/l/4h

STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

TETRAHYDROFURFURYL METHACRYLATE

LD50 (Oral): 3945 mg/kg

2-PROPENOIC ACID, 2-METHYL-, 2-HYDROXY-3-[(1-OXO-2-PROPENYL)OXY]PROPYL ESTER, POLYMER WITH 1,3-BUTADIENE AND 2-PROPENENITRILE.

1-CYANO-4-[2-HYDROXY-3-[(2-METHYL-1-OXO-2-PROPENYL)OXY]PROPOXY]-1-METHYL-4-OXOBUTYL TERMINATED

 LD50 (Dermal):
 > 2000 mg/kg

 LD50 (Oral):
 > 5000 mg/kg

 LC50 (Inhalation mists/powders):
 > 2 mg/l/1h

#### Ε



### **Permabond Engineering Adhesives**

## **Permabond F201HV**

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 10 / 15

### SECTION 11. Toxicological information .../>>

**CUMYL HYDROPEROXIDE** 

 LD50 (Dermal):
 1400 mg/kg

 LD50 (Oral):
 382 mg/kg

 LC50 (Inhalation mists/powders):
 1,37 mg/l/4h

STA (Inhalation mists/powders): 0,501 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

 CUMENE
 > 3160 mg/kg Rabbit

 LD50 (Dermal):
 > 3160 mg/kg Rabbit

 LD50 (Oral):
 1400 mg/kg Rat

 LC50 (Inhalation vapours):
 > 17,6 mg/l/6h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

May damage the unborn child

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

### **SECTION 12. Ecological information**

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

### 12.1. Toxicity

METHACRYLIC ACID

 LC50 - for Fish
 85 mg/l/96h

 EC50 - for Crustacea
 > 130 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 45 mg/l/72h

TETRAHYDROFURFURYL METHACRYLATE

 LC50 - for Fish
 34,7 mg/l/96h

 EC50 - for Crustacea
 69 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 > 100 mg/l/72h

 Chronic NOEC for Fish
 9,4 mg/l



## **Permabond F201HV**

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 11 / 15

### SECTION 12. Ecological information .../>>

Chronic NOEC for Crustacea

37,2 mg/l

2-PROPENOIC ACID, 2-METHYL-, 2-HYDROXY-3-[(1-OXO-2-PROPENYL)OXY]PROPYL ESTER, POLYMER WITH 1,3-BUTADIENE AND 2-PROPENENITRILE, 1-CYANO-4-[2-HYDROXY-3-[(2-METHYL-1-OXO-2-PROPENYL)OXY]PROPOXY]-1-METHYL-4-OXOBUTYL TERMINATED

LC50 - for Fish 70,7 mg/l/96h
EC50 - for Algae / Aquatic Plants 97 mg/l/72h
Chronic NOEC for Fish 50 mg/l
Chronic NOEC for Crustacea 0,1 mg/l

**CUMYL HYDROPEROXIDE** 

LC50 - for Fish

EC50 - for Crustacea

EC50 - for Algae / Aquatic Plants

Chronic NOEC for Crustacea

Chronic NOEC for Algae / Aquatic Plants

Chronic NOEC for Algae / Aquatic Plants

1 mg/l

### 12.2. Persistence and degradability

METHACRYLIC ACID Rapidly degradable

TETRAHYDROFURFURYL METHACRYLATE

NOT rapidly degradable

2-PROPENOIC ACID, 2-METHYL-, 2-HYDROXY-3-[(1-OXO-2-PROPENYL)OXY]PROPYL ESTER, POLYMER WITH 1,3-BUTADIENE AND 2-PROPENENITRILE, 1-CYANO-4-[2-HYDROXY-3-[(2-METHYL-1-OXO-2-PROPENYL)OXY]PROPOXY]-1-METHYL-4-OXOBUTYL TERMINATED

NOT rapidly degradable

CUMYL HYDROPEROXIDE NOT rapidly degradable

**CUMENE** 

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

### 12.3. Bioaccumulative potential

TETRAHYDROFURFURYL METHACRYLATE

Partition coefficient: n-octanol/water 1,38 Log Kow

 $2-PROPENOIC\ ACID,\ 2-METHYL-,\ 2-HYDROXY-3-[(1-OXO-2-PROPENYL)OXY]PROPYL\ ESTER,\ POLYMER\ WITH\ 1,3-BUTADIENE\ AND\ 2-PROPENENITRILE,\ 1-CYANO-4-[2-HYDROXY-3-[(2-METHYL-1-OXO-2-PROPENYL)OXY]PROPOXY]-1-METHYL-4-OXOBUTYL$ 

TERMINATED

BCF 164

**CUMENE** 

Partition coefficient: n-octanol/water 3,55 BCF 94,69

12.4. Mobility in soil

**CUMENE** 

Partition coefficient: soil/water 2,946

### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.



## **Permabond F201HV**

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 12 / 15

### SECTION 12. Ecological information .../>>

### 12.7. Other adverse effects

Information not available

### **SECTION 13. Disposal considerations**

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

08 04 09\* stickers and sealed sealing, containing organic solvents or other dangerous substances

### **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

### 14.1. UN number or ID number

not applicable

### 14.2. UN proper shipping name

not applicable

### 14.3. Transport hazard class(es)

not applicable

### 14.4. Packing group

not applicable

### 14.5. Environmental hazards

not applicable

### 14.6. Special precautions for user

not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

### **SECTION 15. Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75



### Permabond F201HV

Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 13 / 15

### **SECTION 15. Regulatory information**

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

Healthcare controls

H226

H312

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3 Org. Perox E Organic peroxide, type E

Repr. 1B Reproductive toxicity, category 1B Acute Tox. 3 Acute toxicity, category 3 Acute Tox. 4 Acute toxicity, category 4 Aspiration hazard, category 1 Asp. Tox. 1

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Skin Corr. 1A Skin corrosion, category 1A Skin Corr. 1B Skin corrosion, category 1B Eve Dam. 1 Serious eye damage, category 1 Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Flammable liquid and vapour.

Skin sensitization, category 1 Skin Sens. 1

**Aquatic Chronic 2** Hazardous to the aquatic environment, chronic toxicity, category 2 Hazardous to the aquatic environment, chronic toxicity, category 3 **Aquatic Chronic 3** 

H242 Heating may cause a fire. H360D May damage the unborn child. H311 Toxic in contact with skin. Toxic if inhaled. H331 Harmful if swallowed. H302 Harmful in contact with skin.

H332 Harmful if inhaled.

H304 May be fatal if swallowed and enters airways.

May cause damage to organs through prolonged or repeated exposure. H373

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. H319 Causes serious eye irritation. H315 Causes skin irritation.

H335 May cause respiratory irritation. H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

#### E١



### **Permabond Engineering Adhesives**

### Permabond F201HV

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 14 / 15

### SECTION 16. Other information .../>>

### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

### **GENERAL BIBLIOGRAPHY**

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

### Note for users

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the





## **Permabond F201HV**

Revision nr.1 Dated 27/04/2023 First compilation Printed on 27/04/2023 Page n. 15 / 15

suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.