

Technical data sheet



Product: 1200 OS

Manufacturer: DOWSIL

Product group: KLEBSTOFF

Article group: PRIMER

Download: 17.07.2025

DOWSIL™ 1200 OS PRIMER, UV TRACEABLE

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708



Technical Data Sheet

DOWSIL™ 1200 OS Primer, UV Traceable

Features & Benefits

- Improves adhesion of silicone sealants to many substrates
- Provides more uniform and stronger bonds
- Primer is suitable for Weathersealing and Structural Glazing applications
- Optimizes adhesion of sealant to surface
- More rapid development of adhesion to surface
- Traceability through UV lamp

Applications

- Primer for silicone adhesives and sealants

Typical Properties

Specification Writers: These values are not intended for use in preparing specifications.

Property	Unit	Result
Color		Colorless
Viscosity at 23°C	mPa.s	1
Flash point – closed cup	°C	27
Specific gravity at 23°C		0.82

Description

In some instances, a specific cleaner or primer will be required for the silicone sealant to achieve optimal adhesion to a specific substrate. DOWSIL™ 1200 OS Primer, UV Traceable is used to get adhesion of silicone sealants to various substrates. This moisture curing primer is supplied as a dilute solution of reactive materials in low viscosity siloxane.

DOWSIL™ 1200 OS Primer, UV Traceable contains a small amount of UV tracer. This allows tracing correct primer application by using a UV lamp. Please contact your representative to learn more about appropriate UV lamp features.

How to Use

For obtaining best results, the following steps should be followed on all surfaces except silicone rubber.

1. Thoroughly clean and degrease the surface using the 2-cloth cleaning method and appropriate solvent (such as DOWSIL™ R-40 Universal Cleaner), when needed. Cleaning procedures are defined in the technical manual. Allow the surface to dry.
2. Apply a thin coat of DOWSIL™ 1200 OS Primer, UV Traceable by applying with a clean cloth. In most cases, a thin primer film will give best adhesion.
3. At standard temperatures and humidity conditions (23°C, 50% R.H.), the primer should be allowed to air dry from 15 to 30 minutes. Because the primer hydrolyses in contact to air moisture, low humidity will necessitate longer drying time. The optimal drying time for a specific area should be determined prior to use. Primer which is allowed to dry extensively will not promote adhesion anymore. As a general rule, drying times of more than 4 hours at standard temperatures and humidity should be avoided.
4. If needed, for quality assurance it is possible to use a UV lamp to trace the correct application of the primer. The UV-tracer will be visible for some days and automatically disappears with time.
5. Apply silicone sealant from Dow.

Always use buffer container to avoid contamination and product deactivation, do not mix used materials into fresh or unused primer can.

Handling Precautions

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.

Usable Life and Storage

When stored at or below 25°C in the original unopened containers, this product has a usable life of 18 months from the date of production.

This material must be stored in a warehouse suitable for flammable materials.

Containers should be kept tightly sealed when not in use. The primer hydrolyses upon contact with air moisture, and prolonged exposure will reduce or destroy its effectiveness.

Once hydrolysed, indicated by a milky appearance, the material cannot be reclaimed, and will contaminate any unreacted primer.

Packaging Information

DOWSIL™ 1200 OS Primer, UV Traceable is available in standard industrial container sizes.

Limitations

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

Health and Environmental Information

To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.

For further information, please see our website, dow.com or consult your local Dow representative.

Disposal Considerations

Dispose in accordance with all local, state (provincial) and federal regulations. Empty containers may contain hazardous residues. This material and its container must be disposed in a safe and legal manner.

It is the user's responsibility to verify that treatment and disposal procedures comply with local, state (provincial) and federal regulations. Contact your Dow Technical Representative for more information.

Product Stewardship

Dow has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products - from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

dow.com

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



©™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
DOWSIL™ 1200 OS Primer, UV Traceable
© 2019–2023 The Dow Chemical Company. All rights reserved.