

# Security data sheet



Product: PLUS ENDFEST 300

Manufacturer: UHU GMBH & CO KG

Product group: KLEBSTOFF

Article group: 2-K KLEBSTOFF

Download: 22.12.2024

## UHU PLUS ENDFEST 300 50ML 45735

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH  
Industriestraße 15  
D-75382 Althengstett

Telephone:  
+49(0)7051/9297-0  
Fax:  
+49(0)7051/9297-99

E-Mail:  
info@tewipack.de  
Website:  
www.tewipack.de

Managing director:  
Alexander Uhl,  
Michael Uhl  
HRB 330424  
Amtsgericht  
Stuttgart

Bank details:  
Sparkasse  
Sindelfingen  
Pforzheim  
Calw  
BLZ 666 500  
85  
Konto 17 787

Commerzbank  
Sindelfingen  
BLZ 603 400 71  
Konto 8 001 166

Vereinigte  
Volksbank AG  
Böblingen  
BLZ 603 900 00  
Konto 80 089  
003

Postbank  
Stuttgart  
BLZ 600 100  
70  
Konto 146  
294 708

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 42 (replaces version 41)

Revision: 26.01.2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**Application of the substance / the mixture** Adhesive**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

UHU GmbH &amp; Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.: 0049-(0)7223-284-0

E-mail: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

**Further information obtainable from:** PSRA**1.4 Emergency telephone number:**

Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111

Schottland (NHS 24) 111

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

**Hazard pictograms**

GHS07



GHS09

**Signal word** Warning

(Contd. on page 2)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 42 (replaces version 41)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 1)

· **Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)

reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)

· **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing vapours.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

· **Additional information:**

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Adhesive

· **Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Eye Irrit. 2; H319: C $\geq$ 5% Skin Irrit. 2; H315: C $\geq$ 5 %	50-100%
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40-xxxx	reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	$\geq$ 2.5-<10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:** No special measures required.

(Contd. on page 3)

GB

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 42 (replaces version 41)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 2)

- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**  
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Send for recovery or disposal in suitable receptacles.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 10

(Contd. on page 4)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 42 (replaces version 41)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 3)

- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **DNELs**

**25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)**

Oral	Consumer, oral, longterm exposition	0.5 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	0.75 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	0.0893 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	4.93 mg/m <sup>3</sup> (rat)
	Consumer, inhalative, longterm exposition	0.87 mg/m <sup>3</sup> (rat)

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Appropriate engineering controls** No further data; see section 7.

- **Individual protection measures, such as personal protective equipment**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Respiratory protection:** Not required.

- **Recommended filter device for short term use:** Combination filter A-P1

- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Recommended thickness of the material: > 0,12 mm

Hand protection Material : butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm)

Break through time : > 8 h

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber

(Contd. on page 5)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 42 (replaces version 41)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 4)

Nitrile rubber, NBR

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· **Eye/face protection**



Tightly sealed goggles

Goggles recommended during refilling

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

Colourless

· **Odour:**

Weak, characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

Undetermined.

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

Not determined.

· **Upper:**

Not determined.

· **Flash point:**

>150 °C

· **Decomposition temperature:**

Not determined.

· **pH at 20 °C**

6

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Dynamic at 20 °C:**

40000 mPas

· **Solubility**

· **water:**

Not miscible or difficult to mix.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure:**

Not determined.

· **Density and/or relative density**

· **Density at 20 °C:**

1.15 g/cm<sup>3</sup>

· **Relative density**

Not determined.

(Contd. on page 6)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 42 (replaces version 41)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 5)

· <b>Vapour density</b>	Not determined.
· <b>9.2 Other information</b>	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
· <b>Appearance:</b>	
· <b>Form:</b>	Fluid
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product does not present an explosion hazard.
· <b>Solvent content:</b>	
· <b>Solids content:</b>	91.0 %
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not determined.
· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Void
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 7)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 42 (replaces version 41)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 6)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity**  
Not applicable.  
Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Sensitisation** Not applicable.
- **Repeated dose toxicity** Not applicable.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.

(Contd. on page 8)

GB



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 42 (replaces version 41)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

Toxic for aquatic organisms

(Contd. of page 7)

### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR/ADN, IMDG, IATA**

UN3082

-

· **14.2 UN proper shipping name**

· **ADR/ADN**

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))

· **IMDG**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT

· **IATA**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))

· **14.3 Transport hazard class(es)**

· **ADR/ADN**



· **Class**

9 (M6) Miscellaneous dangerous substances and articles.

(Contd. on page 9)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 29.01.2024

Version number 42 (replaces version 41)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 8)

· Label	9
· IMDG, IATA	
	
· Class	9 Miscellaneous dangerous substances and articles.
· Label	9
· 14.4 Packing group	
· ADR/ADN, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	Symbol (fish and tree)
· Special marking (ADR/ADN):	Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· 14.6 Special precautions for user	
Warning: Miscellaneous dangerous substances and articles.	
· Hazard identification number (Kemler code):	90
· EMS Number:	F-A,S-F
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	
Not applicable.	
· Transport/Additional information:	
· ADR/ADN	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	(-)
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 42 (replaces version 41)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 9)

- **UN "Model Regulation":** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL - A - (EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700), REACTION PRODUCT: BISPHENOL-F-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category E2** Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 11)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 42 (replaces version 41)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 10)

EUH205 Contains epoxy constituents. May produce an allergic reaction.

**Classification according to Regulation (EC) No 1272/2008**

Skin corrosion/irritation  
Serious eye damage/irritation  
Skin sensitisation  
Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- **Department issuing SDS:** UHU QESH
- **Contact:** UHU QESH
- **Date of previous version:** 31.03.2023
- **Version number of previous version:** 41
- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

- **\* Data compared to the previous version altered.**

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 24 (replaces version 23)

Revision: 26.01.2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**Application of the substance / the mixture** Adhesive**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

UHU GmbH &amp; Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.: 0049-(0)7223-284-0

E-mail: sds@boltonadhesives.com

Fax: 0049-(0)7223-284-245

**Further information obtainable from:** PSRA**1.4 Emergency telephone number:**

Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

England and Wales (NHS Direct) 111

Schottland (NHS 24) 111

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

**Hazard pictograms**

GHS05 GHS07

**Signal word** Danger**Hazard-determining components of labelling:**

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

(Contd. on page 2)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 24 (replaces version 23)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 1)

amine, polyethylenepoly-,triethylenetetramine fraction

· **Hazard statements**

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P260 Do not breathe vapours.

P280 Wear protective gloves / eye protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Adhesive

· **Dangerous components:**

CAS: 10563-29-8 EINECS: 234-148-4	N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Skin Sens. 1B, H317	≥5-≤10%
CAS: 90640-67-8 EINECS: 292-588-2 Reg.nr.: 01-2119487919-13	amine, polyethylenepoly-,triethylenetetramine fraction ⚠ Skin Corr. 1B, H314; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥3-<5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 3)

GB

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 24 (replaces version 23)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Send for recovery or disposal in suitable receptacles.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 8 A
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 24 (replaces version 23)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 3)

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

##### · **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **Additional information:** The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

##### · **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Recommended filter device for short term use:** Combination filter A-P1

##### · **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

##### · **Material of gloves**

Recommended thickness of the material: > 0,12 mm

Hand protection Material : butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm)

Break through time : > 8 h

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber  
Nitrile rubber, NBR

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

##### · **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

(Contd. on page 5)

GB



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 24 (replaces version 23)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 4)

· **Eye/face protection**



Tightly sealed goggles

Goggles recommended during refilling

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· <b>Physical state</b>	Fluid
· <b>Colour:</b>	Yellow
· <b>Odour:</b>	Amine-like
· <b>Odour threshold:</b>	Not determined.
· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Boiling point or initial boiling point and boiling range</b>	~278 °C
· <b>Flammability</b>	Not applicable.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	Not determined.
· <b>Upper:</b>	Not determined.
· <b>Flash point:</b>	>100 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Not determined.
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.
· <b>Dynamic at 20 °C:</b>	32500 mPas
· <b>Solubility</b>	
· <b>water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure:</b>	Not determined.
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C:</b>	0.95 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.

· **9.2 Other information**

All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

· **Appearance:**

· **Form:** Fluid

· **Important information on protection of health and environment, and on safety.**

· **Ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product does not present an explosion hazard.

(Contd. on page 6)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 24 (replaces version 23)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 5)

- **Solvent content:**
- **Solids content:** 84.2 %
- **Change in condition**
- **Evaporation rate** Not determined.

· **Information with regard to physical hazard classes**

- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Skin corrosion/irritation**  
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**  
Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity**  
Not applicable.

(Contd. on page 7)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 24 (replaces version 23)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 6)

- Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Sensitisation** Not applicable.
- **Repeated dose toxicity** Not applicable.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Must not reach sewage water or drainage ditch undiluted or unneutralised.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Disposal must be made according to official regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024



Version number 24 (replaces version 23)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 7)

### SECTION 14: Transport information

<ul style="list-style-type: none"> <li>· 14.1 UN number or ID number</li> <li>· ADR/ADN, IMDG, IATA</li> </ul>	UN2735	
<ul style="list-style-type: none"> <li>· 14.2 UN proper shipping name</li> <li>· ADR/ADN</li> <li>· IMDG, IATA</li> </ul>	<p>2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine)</p> <p>POLYAMINES, LIQUID, CORROSIVE, N.O.S. (N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine)</p>	
<ul style="list-style-type: none"> <li>· 14.3 Transport hazard class(es)</li> <li>· ADR/ADN</li> </ul>	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	<p>8 (C7) Corrosive substances.</p> <p>8</p>
<ul style="list-style-type: none"> <li>· IMDG, IATA</li> </ul>	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	<p>8 Corrosive substances.</p> <p>8</p>
<ul style="list-style-type: none"> <li>· 14.4 Packing group</li> <li>· ADR/ADN, IMDG, IATA</li> </ul>	III	
<ul style="list-style-type: none"> <li>· 14.5 Environmental hazards:</li> </ul>	Not applicable.	
<ul style="list-style-type: none"> <li>· 14.6 Special precautions for user</li> <li>· Hazard identification number (Kemler code):</li> <li>· EMS Number:</li> <li>· Segregation groups</li> <li>· Stowage Category</li> <li>· Stowage Code</li> </ul>	<p>Warning: Corrosive substances.</p> <p>80</p> <p>F-A,S-B</p> <p>(SGG18) Alkalis</p> <p>B</p> <p>SW2 Clear of living quarters.</p>	
<ul style="list-style-type: none"> <li>· 14.7 Maritime transport in bulk according to IMO instruments</li> </ul>	Not applicable.	
<ul style="list-style-type: none"> <li>· Transport/Additional information:</li> <li>· Quantity limitations</li> </ul>	<p>On passenger aircraft/rail: 5 L</p> <p>On cargo aircraft only: 60 L</p>	
<ul style="list-style-type: none"> <li>· ADR/ADN</li> <li>· Limited quantities (LQ)</li> </ul>	5L	

(Contd. on page 9)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 24 (replaces version 23)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 8)

· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	E
<hr/>	
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (N'-(3-AMINOPROPYL)-N,N-DIMETHYLPROPANE-1,3-DIAMINE), 8, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

GB

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2024

Version number 24 (replaces version 23)

Revision: 26.01.2024

**Trade name:** UHU PLUS ENDFEST 300 YE SY 50ML\*6 DE

(Contd. of page 9)

· **Relevant phrases**

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H412 Harmful to aquatic life with long lasting effects.

· **Classification according to Regulation (EC) No 1272/2008**

Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

· **Department issuing SDS:** UHU QESH

· **Contact:** UHU QESH

· **Date of previous version:** 25.10.2022

· **Version number of previous version:** 23

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1B: Skin sensitisation – Category 1B
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* **Data compared to the previous version altered.**

GB