# Technical data sheet

| | |
|---|---|
| Product: | 2090 |
| Manufacturer: | 3M DEUTSCHLAND GMBH |
| Product group: | KLEBEBAND |
| Article group: | EINSEITIG |
| Download: | 04.09.2026 |

## SCOTCH-BLUE™ #2090

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708

**3M Construction & Home Improvement Markets**

Product Information Sheet

January 2010

# Scotch-Blue™ Painter's Tape for Multi-Surfaces #2090

Scotch-Blue™ Painter's Tape for Multi-Surfaces #2090 is a medium adhesion tape ideal for paint masking on multiple surfaces, including painted walls and trim, woodwork, glass and metal. It can be removed cleanly from the surface for up to 14 days even in direct sunlight.

| Product Characteristic | Value |
|---|---|
| Backing | Crepe Paper |
| Adhesive | Acrylic |
| Standard Roll Length | 60 yards (54.8 m) |
| Color | Blue |

| Typical Physical Properties | Value | **Note:** The following technical information and data should be considered representative or typical only and should not be used for specification purposes. |
|---|---|---|
| **Adhesion to Steel** | **23 oz./in.** | **ASTM D-3330** |
| **Tensile Strength** | **27 lbs./in.** | **ASTM D-3759** |
| **Elongation at Break** | **7 %** | **ASTM D-3759** |
| **Total Thickness** | **5.4 mils** | **ASTM D-3652** |

**Features/Advantages Benefits:**

| Feature (HAS) | Advantage (WHICH MEANS) | Benefit (SO THAT) |
|---|---|---|
| Acrylic Adhesive | Adhesive Transfer Resistance | Sticks easily to the surface and stays intact upon removal /reduces labor and rework |
| | Increased Light and UV Stability | Clean removal / reduces labor |
| | Medium adhesion | Easy to use/reduces labor |
| | Controlled tack | Minimal adhesion build over time with clean and safe removal / reduces rework and labor, and helps to produce high-quality results |
| Crepe Paper Backing | Smoothness | Consistent surface contact and secure holding power |
| | Conformability | Easy handling/helps reduce overall project time |

| | | |
|---|---|---|
| | Strong | Removes from surface without tearing |
| Backing Saturant | Easy Tear | Good handling/helps reduce waste |
| | Solvent and Moisture Resistance | Resists paint bleed-through and adhesive doesn't soften or transfer when tape is wet |
| Backsize Treatment | Controlled Unwind | Easy to use/smooth unwind |

**Warnings:**

- Do not use with or on nitrocellulose lacquer coatings
- Do not use on wallpapers, unpainted wallboard, wood floors or poorly bonded finishes.

---

**3M Construction and Home Improvement Markets Division**
3M Center, Building 251-1C-09
St. Paul, MN 55144-1000

**IMPORTANT NOTICE:** All statements, technical information and recommendations herein are based on tests 3M believes to be reliable. 3M does not warrant or guarantee the accuracy or completeness of this information. THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE: 3M's only obligation shall be to replace such quantity of this 3M product proved to be defective. User is responsible for determining whether this 3M product is fit for a particular purpose and suitable for user's method of application. Because there are many factors that can affect the use and performance of this product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate this product to determine whether it is fit for a particular purpose, is suitable for the user's method of application, and meets the user's performance specifications and expectations.

**Limitation of Liability:** 3M SHALL NOT BE LIABLE FOR ANY LOSS OR DAMAGES, WHETHER DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL (INCLUDING BUT NOT LIMITED TO LOST PROFITS, BUSINESS, OR REVENUES) ARISING OUT OF THE USE OF OR INABILITY TO USE THIS 3M PRODUCT, WARRANTY, OR STRICT LIABILITY. No statement or recommendation not contained herein shall have any force or effect unless contained in an agreement signed by a 3M officer..

3M, Scotch, and the Plaid Design are trademarks of 3M Company.
© 3M 2010