

# Security data sheet



Product: PRE-BONDING CLEANER

Manufacturer: BOSTIK SA

Product group: KLEBSTOFF

Article group: REINIGER

Download: 24.05.2026

## BOSTIK BORN2BOND PREBONDING CLEANER

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH  
Industriestraße 15  
D-75382 Althengstett

Telephone:  
+49(0)7051/9297-0  
Fax:  
+49(0)7051/9297-99

E-Mail:  
info@tewipack.de  
Website:  
www.tewipack.de

Managing director:  
Alexander Uhl,  
Michael Uhl  
HRB 330424  
Amtsgericht  
Stuttgart

Bank details:  
Sparkasse  
Sindelfingen  
Pforzheim  
Calw  
BLZ 666 500  
85  
Konto 17 787

Commerzbank  
Sindelfingen  
BLZ 603 400 71  
Konto 8 001 166

Vereinigte  
Volksbank AG  
Böblingen  
BLZ 603 900 00  
Konto 80 089  
003

Postbank  
Stuttgart  
BLZ 600 100  
70  
Konto 146  
294 708



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**BOSTIK BORN2BOND PREBONDING CLEANER**  
Supersedes Date: 01-Jul-2021

Revision date 13-Dec-2022  
Revision Number 1.02

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name BOSTIK BORN2BOND PREBONDING CLEANER

Pure substance/mixture Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Cleaning agent

Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Category 3 Narcotic effects	
Chronic aquatic toxicity	Category 2 - (H411)
Aerosols	Category 1 - (H222, H229)

### 2.2. Label elements

Contains Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane, Isopropyl alcohol

# SAFETY DATA SHEET

BOSTIK BORN2BOND PREBONDING CLEANER  
Supersedes Date: 01-Jul-2021

Revision date 13-Dec-2022  
Revision Number 1.02



**Signal word**  
Danger

## Hazard statements

H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H411 - Toxic to aquatic life with long lasting effects.  
H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.

## Precautionary Statements - EU (§28, 1272/2008)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P211 - Do not spray on an open flame or other ignition source  
P251 - Do not pierce or burn, even after use  
P261 - Avoid breathing vapours/spray  
P280 - Wear protective gloves and eye/face protection  
P312 - Call a POISON CENTER or doctor/physician if you feel unwell  
P391 - Collect spillage  
P273 - Avoid release to the environment  
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

## 2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture. Toxic to aquatic life. In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	RR-100219-3	>25 - <40	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411)	-	01-2119475515-33-xxxx

# SAFETY DATA SHEET

**BOSTIK BORN2BOND PREBONDING CLEANER**  
Supersedes Date: 01-Jul-2021

Revision date 13-Dec-2022  
Revision Number 1.02

				Flam. Liq. 2 (H225)		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane	921-024-6	RR-100221-7	>25 - <40	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225)	-	01-2119475514-35-XXXX
Isopropyl alcohol	(603-117-00-0) 200-661-7	67-63-0	20 - 25	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	01-2119457558-25-XXXX
Carbon dioxide	204-696-9	124-38-9	1 - <5	Press. Gas (H280)	-	[4]

NOTE [4] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex IV of REACH

## Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and
-----------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------

# SAFETY DATA SHEET

BOSTIK BORN2BOND PREBONDING CLEANER  
Supersedes Date: 01-Jul-2021

Revision date 13-Dec-2022  
Revision Number 1.02

vomiting.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

**Note to doctors** No information available.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

**Suitable Extinguishing Media** Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray.

**Unsuitable extinguishing media** Full water jet. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

#### **5.2. Special hazards arising from the substance or mixture**

**Specific hazards arising from the chemical** Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

**Hazardous combustion products** Carbon oxides. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

#### **5.3. Advice for firefighters**

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

#### **6.2. Environmental precautions**

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

#### **6.3. Methods and material for containment and cleaning up**

**Methods for containment** Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

**Prevention of secondary hazards** Eliminate all ignition sources if safe to do so.

# SAFETY DATA SHEET

BOSTIK BORN2BOND PREBONDING CLEANER  
Supersedes Date: 01-Jul-2021

Revision date 13-Dec-2022  
Revision Number 1.02

## 6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Keep/store only in original container. Store in a dry place. Store in a closed container.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Cleaning agent.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	United Kingdom
Isopropyl alcohol 67-63-0	-	TWA: 400 ppm TWA: 999 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1250 mg/m <sup>3</sup>
Carbon dioxide 124-38-9	TWA: 5000 ppm TWA: 9000 mg/m <sup>3</sup>	TWA: 5000 ppm TWA: 9150 mg/m <sup>3</sup> STEL: 15000 ppm

# SAFETY DATA SHEET

**BOSTIK BORN2BOND PREBONDING CLEANER**  
**Supersedes Date:** 01-Jul-2021

**Revision date** 13-Dec-2022  
**Revision Number** 1.02

	STEL: 27400 mg/m <sup>3</sup>
--	-------------------------------

Chemical name	European Union	Ireland	United Kingdom
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane RR-100221-7	DNEL (Ind/Prof) 773 mg/Kg bw/day (dermal) 2035 mg/m <sup>3</sup> /8h (inhalation)	-	-
Isopropyl alcohol 67-63-0	-	40 mg/L (urine - Acetone end of shift at end of workweek)	-

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	2085 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	300 mg/kg bw/d	

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane (RR-100221-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker DNEL	Inhalation	2035 mg/m <sup>3</sup>	
Long term Systemic health effects worker DNEL	Dermal	773 mg/kg bw/d	

Isopropyl alcohol (67-63-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	500 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	888 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	447 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	149 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	149 mg/kg bw/d	

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane (RR-100221-7)			
Type	Exposure route	Derived No Effect Level	Safety factor

# SAFETY DATA SHEET

**BOSTIK BORN2BOND PREBONDING CLEANER**  
**Supersedes Date:** 01-Jul-2021

**Revision date** 13-Dec-2022  
**Revision Number** 1.02

		(DNEL)	
Consumer Long term Systemic health effects	Dermal	699 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	608 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Oral	699 mg/kg bw/d	

<b>Isopropyl alcohol (67-63-0)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	89 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	319 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d	

## Predicted No Effect Concentration (PNEC)

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>Isopropyl alcohol (67-63-0)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	140.9 mg/l
Marine water	140.9 mg/l
Sewage treatment plant	2251 mg/l
Freshwater sediment	552 mg/kg dry weight
Marine sediment	552 mg/kg dry weight
Soil	28 mg/kg dry weight

## 8.2. Exposure controls

### Engineering controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

### Personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

#### Hand protection

Wear suitable gloves. Glove thickness > 0.7mm. Butyl rubber. Nitrile rubber. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374

#### Skin and body protection

Wear appropriate personal protective clothing to prevent skin contact.

#### Respiratory protection

Ensure adequate respiratory protection during spray applications. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Recommended filter type:

Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming to EN 140 with Type A filter or better.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

# SAFETY DATA SHEET

BOSTIK BORN2BOND PREBONDING CLEANER  
Supersedes Date: 01-Jul-2021

Revision date 13-Dec-2022  
Revision Number 1.02

## 9.1. Information on basic physical and chemical properties

Physical state	Aerosol
Appearance	Aerosol
Colour	Colourless
Odour	Solvent.
Odour threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	Not applicable . °C	None known
Initial boiling point and boiling range	Not applicable, Aerosol .	Not applicable, Aerosol
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	Not applicable, Aerosol .	Not applicable, Aerosol
Autoignition temperature	425 °C	None known
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Water solubility	Miscible in water.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	0.728	None known
Bulk Density	No data available	
Liquid Density	0.72 - 0.73 g/cm <sup>3</sup>	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

## 9.2. Other information

Solid content (%)	No information available
VOC content	approx 694.5 g/L

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity No information available.

### 10.2. Chemical stability

Stability Stable under normal conditions.

### Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

# SAFETY DATA SHEET

BOSTIK BORN2BOND PREBONDING CLEANER  
Supersedes Date: 01-Jul-2021

Revision date 13-Dec-2022  
Revision Number 1.02

## 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Heating causes rise in pressure with risk of bursting.

## 10.4. Conditions to avoid

**Conditions to avoid** Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight.

## 10.5. Incompatible materials

**Incompatible materials** Strong acids. Strong bases. Strong oxidising agents. Incompatible with oxidising agents.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

<b>Inhalation</b>	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

#### Acute toxicity

#### Numerical measures of toxicity

##### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane	LD50 >5840 mg/kg (Rattus)	LD50 >2800-3100 mg/kg (Rattus)	LD50 (4h) >25200 mg/m <sup>3</sup> LD50 (4h) >20 mg/l (rattus) v

# SAFETY DATA SHEET

**BOSTIK BORN2BOND PREBONDING CLEANER**  
Supersedes Date: 01-Jul-2021

Revision date 13-Dec-2022  
Revision Number 1.02

Isopropyl alcohol	>5000 mg/Kg	= 4059 mg/kg (Oryctolagus cuniculus)	=72600 mg/m <sup>3</sup> (Rattus) 4 h
-------------------	-------------	--------------------------------------	---------------------------------------

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Irritating to skin.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes serious eye irritation.

Isopropyl alcohol (67-63-0)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			Irritant

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

Isopropyl alcohol (67-63-0)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig		No sensitisation responses were observed

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Component Information  
Isopropyl alcohol (67-63-0)

Method	Species	Results
OECD Test No. 476: In vitro Mammalian Cell Gene Mutation Test	Hamster, in vitro	Not mutagenic

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** May cause drowsiness or dizziness.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

# SAFETY DATA SHEET

**BOSTIK BORN2BOND PREBONDING CLEANER**  
**Supersedes Date:** 01-Jul-2021

**Revision date** 13-Dec-2022  
**Revision Number** 1.02

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics RR-100219-3	ErL50 (72h) = 10-30 mg/L (Pseudokirchneriella subcapitata)	LL50 (96h) >13.4 mg/L (Oncorhynchus mykiss) OECD 203	-	EL50 (48h) = 3.0 mg/L (Daphnia magna)		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane RR-100221-7	EL50 (72h)= 26 mg/L (Pseudokirchneriella subcapitata) OECD 201	LL50 (96h) =12 mg/L (Oncorhynchus mykiss) OECD 203	-	EL50 (48h) =3mg/L (Daphnia magna) OECD 202		
Isopropyl alcohol 67-63-0	EC50 72 h > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h > 1400000 ?g/L (Lepomis macrochirus )	-	EC50: =13299mg/L (48h, Daphnia magna)		

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	98%	Readily biodegradable

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane (RR-100221-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	98%	Readily biodegradable

### 12.3. Bioaccumulative potential

**Bioaccumulation**

#### Component Information

Chemical name	Partition coefficient
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane	4
Isopropyl alcohol	0.05

### 12.4. Mobility in soil

**Mobility in soil** No information available.

### 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** No information available.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The substance is not PBT / vPvB
Isopropyl alcohol	The substance is not PBT / vPvB PBT assessment does not apply

# SAFETY DATA SHEET

BOSTIK BORN2BOND PREBONDING CLEANER  
Supersedes Date: 01-Jul-2021

Revision date 13-Dec-2022  
Revision Number 1.02

## 12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

## 12.7. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable. Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
<b>Contaminated packaging</b>	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
<b>European Waste Catalogue</b>	16 05 04* gases in pressure containers (including halons) containing dangerous substances 15 01 04 metallic packaging
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

<b>14.1 UN number or ID number</b>	UN1950
<b>14.2 Proper Shipping Name</b>	Aerosols
<b>14.3 Transport hazard class(es)</b>	2
<b>Labels</b>	2.2
<b>14.4 Packing group</b>	Not regulated
<b>Description</b>	UN1950, Aerosols, 2, (E), Environmentally Hazardous
<b>14.5 Environmental hazards</b>	Yes
<b>14.6 Special Provisions</b>	327, 625, 344, 190
<b>Classification code</b>	5A
<b>Tunnel restriction code</b>	(E)
<b>Limited quantity (LQ)</b>	1 L

### IMDG

<b>14.1 UN number or ID number</b>	UN1950
<b>14.2 Proper Shipping Name</b>	Aerosols
<b>14.3 Transport hazard class(es)</b>	2.2
<b>14.4 Packing group</b>	Not regulated
<b>Description</b>	UN1950, Aerosols (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane), 2.2, Marine Pollutant
<b>14.5 Marine pollutant</b>	P
<b>14.6 Special Provisions</b>	63,190, 277, 327, 344, 381, 959
<b>Limited Quantity (LQ)</b>	See SP277
<b>EmS-No</b>	F-D, S-U
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

# SAFETY DATA SHEET

**BOSTIK BORN2BOND PREBONDING CLEANER**  
Supersedes Date: 01-Jul-2021

Revision date 13-Dec-2022  
Revision Number 1.02

<b>14.1 UN number or ID number</b>	UN1950
<b>14.2 Proper Shipping Name</b>	Aerosols, non-flammable
<b>14.3 Transport hazard class(es)</b>	2.2
<b>14.4 Packing group</b>	Not regulated
<b>Description</b>	UN1950, Aerosols, non-flammable, 2.2
<b>14.5 Environmental hazards</b>	Yes
<b>14.6 Special Provisions</b>	A145, A167, A98, A802
<b>Limited quantity (LQ)</b>	30 kg G
<b>ERG Code</b>	2L

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

##### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### **Dangerous substance category per Seveso Directive (2012/18/EU)**

P3a - FLAMMABLE AEROSOLS

P3b - FLAMMABLE AEROSOLS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

##### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

##### **Persistent Organic Pollutants**

Not applicable

##### **Regulation (EC) No. 648/2004 (Detergents regulation)**

Labelling for contents according to regulation (EC) No. 648/2004

aliphatic hydrocarbons	>30%
------------------------	------

#### National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No  
Chemical Safety Assessment has been carried out for this mixture

# SAFETY DATA SHEET

BOSTIK BORN2BOND PREBONDING CLEANER  
Supersedes Date: 01-Jul-2021

Revision date 13-Dec-2022  
Revision Number 1.02

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour  
H280 - Contains gas under pressure; may explode if heated  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

#### Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

#### Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 13-Dec-2022

#### Indication of changes

**Revision note** SDS sections updated: 2, 3, 9, 11, 15, 16.

**Training Advice** When working with hazardous materials, regular training of operators is required by law

**Further information** No information available

#### Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**