

Technical data sheet



Product: 5136

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: KLEBSTOFF

Article group: PRIMER

Download: 17.07.2025

3M™ SCOTCHCAST™ RESIN PRIMER 5136N

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708

3M™ Scotchcast™ Resin Primer 5136N One-Part, Solvent-Based Primer

Data Sheet

May 2012

Description 3M™ Scotchcast™ Resin Primer 5136N is a one-part, solvent-based primer designed to help improve the adhesion of Scotchcast epoxy and polyurethane resins to substrates such as neoprene, rubber, semi-flexible epoxies and polyurethanes.

Handling Properties

Handling Properties	
Density	0.98 kg/l (8.18 lbs/gal)
Flash Point	1°F (-17°C)
Drying Time	2 - 4 min. @ 73.4°F (23°C)

Usage Information Apply the primer to a clean surface by spraying, dipping or brushing. Allow 2-4 minutes for drying of the primer.

Handling & Safety Precautions Read all Health Hazard, Precautionary and First Aid statements found in the Material Safety Data Sheet (MSDS) and/or product label of chemicals prior to handling or use.

Shelf Life & Storage 3M™ Scotchcast™ Resin Primer 5136N has a 2-year shelf life from date of manufacture when stored in a humidity controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity). When not in use, containers should be kept tightly closed. Storage at conditions outside those suggested may compromise the performance of the resin primer.

Availability 3M™ Scotchcast™ Resin Primer 5136N is a one-part, solvent-based primer

Please contact your local distributor; available from 3M.com/electrical [Where to Buy] or call 1-800-676-8381

3M™ Scotchcast™ Resin Primer 5136N

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product, which are not contained in 3M's current publications, or any contrary statements contained on your purchase order, shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

**Warranty; Limited
Remedy; Limited
Liability**

This product will be free from defects in material and manufacture at the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

3M and Scotchcast are trademarks of 3M Company.

**Electrical Markets Division**

6801 River Place Blvd.
Austin, TX 78726-9000
800-676-8381
FAX: 800-828-9329
www.3M.com/oem

Please recycle
© 3M 2012 All rights reserved
78-8141-5231-6 Rev A