

# Technical data sheet



Product: 2000

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: KLEBEBAND

Article group: EINSEITIG

Download: 09.05.2025

## SCOTCH® 2000™ ELECTRICIAN'S DUCT TAPE

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH  
Industriestraße 15  
D-75382 Althengstett

Telephone:  
+49(0)7051/9297-0  
Fax:  
+49(0)7051/9297-99

E-Mail:  
info@tewipack.de  
Website:  
www.tewipack.de

Managing director:  
Alexander Uhl,  
Michael Uhl  
HRB 330424  
Amtsgericht  
Stuttgart

Bank details:  
Sparkasse  
Sindelfingen  
Pforzheim  
Calw  
BLZ 666 500  
85  
Konto 17 787

Commerzbank  
Sindelfingen  
BLZ 603 400 71  
Konto 8 001 166

Vereinigte  
Volksbank AG  
Böblingen  
BLZ 603 900 00  
Konto 80 089  
003

Postbank  
Stuttgart  
BLZ 600 100  
70  
Konto 146  
294 708



# Scotch® 2000™

## Electrician's Duct Tape

### 1. Product Description

Scotch® 2000 Electrician's Duct Tape is a water resistant duct tape with a polyvinyl chloride (PVC) backing and a rubber adhesive. Scotch® 2000 is designed to be an electrician's utility tape for holding and bundling applications.

- Easy tear
- No cloth—does not absorb water.
- Clean removal (minimal residue)
- Not recommended for sealing air ducts.

### 2. Typical Properties

Properties measured at room temperature 23°C unless otherwise stated.

Physical Properties	Typical Value
Color	Grey
Thickness ASTM D1000	0,15 mm
Adhesion to Steel ASTM D1000	2,19 N/10 mm.
Tensile Strength ASTM D1000	21,02 N/10 mm
Elongation at Break ASTM D1000	100%

**Note:** These are typical properties and should not be used for specification purposes.

Insert Company  
address  
before issue

Reference: AABBC28219\_02  
© 3M 2014 All Rights Reserved.

Issue date 02.11.2016

### 3. User Information

#### 3.1 Agency Approvals & Self Certifications

- For RoHS information, please visit [www.3M.com/RoHS](http://www.3M.com/RoHS)

#### 3.2 Shelf Life & Storage

Scotch® 2000 has a three year shelf life (from date of manufacture) when stored under the following recommended storage conditions. Store behind present stock in a clean, dry place at a temperature of 21°C and 40-50% relative humidity. Good stock rotation is recommended.

#### 3.3 Availability

Please contact your local distributor.

### 4. Additional Information

To request additional product information see address below.

#### ***Important Notice***

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application.

Values presented have been determined by standard test methods and are average values not meant to be used for specification purposes.

All questions of warranty and liability relating to 3M products are governed by the terms of the respective sale subject, where applicable, to the prevailing law.

3M is a trademark of the 3M Company.

Insert Company  
address  
before issue

Reference: AABBC28219\_02

Issue date 02.11.2016

© 3M 2014 All Rights Reserved.