

Technical data sheet



Product: 1609

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: ELEKTRO

Article group: AEROSOL

Download: 01.06.2025

SCOTCH® 1609 SILICONE SPRAY

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708

3M™ Silicone Spray Scotch® 1609

Product Description

Scotch 1609 Silicone Spray is an oil and grease-free protective, lubricating, separating, and care-agent for plastics, wood, rubber and metals and provides long-lasting protection against moisture and corrosion.

The silicone spray can be used wherever oil and grease protection is needed. It lubricates moving parts without hardening and can be used within a wide temperature range (-32°C up to 177°C). Scotch 1609 Silicone Spray is neutral to paints, plastics, rubber, foam, wood and fabric.

Pack Size

400ml can

Typical Properties

- Clear, stain-free lubricant
- Clean, non-resinous lubricating film
- Good temperature resistance
- Protects against oxidation and corrosion
- Good adhesion
- Water repellent and antistatic



Applications

The Silicone Spray Scotch 1609 is used as a lubricant for electrical appliances, locks, hinges, sunroofs, seat rails, safety belt winder, etc. It is suitable as a release agent in molding processes and can be used as an assembly aid when pulling cables. It also finds use in presses and guides for wood and paper processing as well as the treatment of cutting edges and tools. It can help to prevent buildups in conveyor belt applications.

Scotch 1609 protects, insulates and cares for plastic, rubber and metal parts and enables good sliding action. Rubber seals are maintained and do not freeze or stick.

The substrate should be dry, free of oil and grease (*) and free of dust. Shake the can vigorously for about 30 seconds, apply the silicone spray from a distance of 20 - 30 cm and spread with a soft, lint-free cloth.

Note: * Prior cleaning with Scotch® 1626 Cleaning and Degreasing Spray or Scotch® 1625 Special Contact Cleaning Spray is recommended

Technical Information

Base	Silicone
Propellant	propane/butane
Solvent	aliphatic petroleum distillates
Colour	clear
Density at 20 °C	0.61 g/cm ³
Dielectric strength at 25 °C	appr. 16kV / mm
Dielectric constant at 25 °C and between 0.5 and 100 kHz	appr. 2.70
Specific resistance	10 ¹⁴ Ωcm
Application temperature	16°C up to 25°C
Temperature resistance	-32°C up to +177°C

Storage

3M™ Scotch® 1609 Silicone Spray has a 2 year shelf life from the date of manufacture, stated on the can, when stored in humidity controlled conditions (10°C to 27°C and <75% relative humidity)

Safety Note

Pressurised Container. Protect from sunlight and temperatures above 50°C.

3M™ Scotch® 1609 Silicone Spray is highly flammable, and should not be sprayed into flames. Hold the can vertically when in use, do not incline more than 30°. This product should not be inhaled, a working environment with good ventilation must be ensured.

Protect skin and eyes, use appropriate PPE. Please refer to our SDS for further information at https://www.3m.co.uk/3M/en_GB/company-uk/SDS-search/

Important Notice: Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture at the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.



Electrical Markets Division

3M UK PLC, 3M Centre, Cain Rd,
Bracknell RG12 8HT, United Kingdom
0870 609 4639
www.3M.co.uk/electrical

Electrical Markets Division

3M Ireland Ltd, The Iveagh Building, The
Park, Carrickmines, Dublin 18, Ireland
1 800 812 732
www.3M.co.uk/electrical

3M and is a trademarks of the 3M
company.

© 3M 2020. All rights reserved.

Issue 1