

# Technical data sheet



Product: 3430

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: KLEBEBAND

Article group: EINSEITIG

Download: 02.05.2026

## SCOTCH™ TAPE 3430

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH  
Industriestraße 15  
D-75382 Althengstett

Telephone:  
+49(0)7051/9297-0  
Fax:  
+49(0)7051/9297-99

E-Mail:  
info@tewipack.de  
Website:  
www.tewipack.de

Managing director:  
Alexander Uhl,  
Michael Uhl  
HRB 330424  
Amtsgericht  
Stuttgart

Bank details:  
Sparkasse  
Sindelfingen  
Pforzheim  
Calw  
BLZ 666 500  
85  
Konto 17 787

Commerzbank  
Sindelfingen  
BLZ 603 400 71  
Konto 8 001 166

Vereinigte  
Volksbank AG  
Böblingen  
BLZ 603 900 00  
Konto 80 089  
003

Postbank  
Stuttgart  
BLZ 600 100  
70  
Konto 146  
294 708



# Scotch™ Tape 3430

## High Performance Auto Refinish Tape

### Product Information

12/95

### Product Description / Markets

Scotch™ Tape 3430 is a brown colored creped paper masking tape for high quality performance auto refinishing masking.

Features	Advantages	Benefits
* Latex saturated heavy weight creped paper backing	* Excellent solvent resistance * Good water resistance	* Prevents paint bleed through * No need to re-mask after wet sanding
* Controlled crosslinked rubber resin adhesive	* Good conformability * Excellent edge tear resistance * Excellent sliver resistance * Easy hand tear * Excellent instant adhesion * Excellent holding power * Good adhesive transfer resistance * Controlled unwind	* Performs well with water based paint systems * Better curve masking * Prevents tearing in curves or on difficult surfaces * Easy removal * Better handling * Sticks easily * Resists lifting even in repeat bake cycles * Clean removal * Easy handling

### Applications / Performance

The excellent temperature performance of 110 °C for one hour of the Scotch™ Tape 3430 allows higher curing temperatures with infrared or heat lamps and for longer and repeat bake cycles.

# Scotch™ Tape 3430

## Product Characteristics

Thickness	:	0.175 mm	AFERA 4006
Adhesion to steel	:	10 N/25 mm	AFERA 4001
Tensile strength	:	110 N/25 mm	AFERA 4004
Elongation	:	10.5 %	AFERA 4005
Temperature performance	:	110 °C	

Satisfactory performance and clean removal of Scotch™ Tape 3430 will be achieved at varying temperatures/time exposure on many substrates. Tests should be conducted to establish Scotch™ Tape 3430 performance parameters in your process conditions. The optimum level for product performance and easy removal is at 110 °C for 60 min.

## Available Sizes

Width (mm)	:	9, 12, 15, 19, 25, 30, 38, 50, 75 and 100
Length (m)	:	50

## Storage Conditions

Store in clean dry place. Temperature of 21 °C and 50 percent relative humidity are recommended.

## Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. Please ensure before using our products that it is suitable for your intended use. All questions of liability relating to this products are governed by the Terms of Sale subject, where applicable, to the prevailing law.

## Masking and Packaging Systems Division

3M Europe  
Masking & Packaging Systems Division  
Hermeslaan 7  
B - 1831 Diegem  
Tel: ++32-2-722.45.50  
Fax: ++32-2-722.45.18

