

Security data sheet



Product: PLUS ENDFEST 300

Manufacturer: UHU GMBH & CO KG

Product group: KLEBSTOFF

Article group: 2-K KLEBSTOFF

Download: 31.07.2025

UHU PLUS ENDFEST 300 163G 45630

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH
Industriestraße 15
D-75382 Althengstett

Telephone:
+49(0)7051/9297-0
Fax:
+49(0)7051/9297-99

E-Mail:
info@tewipack.de
Website:
www.tewipack.de

Managing director:
Alexander Uhl,
Michael Uhl
HRB 330424
Amtsgericht
Stuttgart

Bank details:
Sparkasse
Sindelfingen
Pforzheim
Calw
BLZ 666 500
85
Konto 17 787

Commerzbank
Sindelfingen
BLZ 603 400 71
Konto 8 001 166

Vereinigte
Volksbank AG
Böblingen
BLZ 603 900 00
Konto 80 089
003

Postbank
Stuttgart
BLZ 600 100
70
Konto 146
294 708

**Safety data sheet
according to UK REACH**

Printing date 22.03.2025

Version number 48 (replaces version 47)

Revision: 22.03.2025

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- **1.1 Product identifier**
 - **Trade name:** UHU PLUS ENDFEST 300 YE FB 163G*20 L011
 - **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
 - **Application of the substance / the mixture** Adhesive
 - **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
UHU GmbH & Co.KG
Herrmannstraße 7
D-77815 Bühl (Baden)
Tel.: 0049-(0)7223-284-0
E-mail: sds@boltonadhesives.com
Fax: 0049-(0)7223-284-245
 - **Further information obtainable from:** PSRA
 - **1.4 Emergency telephone number:**
Tel.: + 49 (0) 30/19240 (Notruf)
Tel.: + 49 (0) 72 23/28 40
- England and Wales (NHS Direct) 111
Schottland (NHS 24) 111

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS07



GHS09

- **Signal word** Warning

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 48 (replaces version 47)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 1)

· Hazard statements

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P261 Avoid breathing vapours.
- P280 Wear protective gloves.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P501 Dispose of contents/container in accordance with national regulations.

· Additional information:

- EUH205 Contains epoxy constituents. May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

Description: Adhesive

· Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26-XXXX	bis-[4-(2,3-epoxipropoxy)phenyl]propane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	50-100%
EC number: 701-263-0 Reg.nr.: 01-2119454392-40-xxxx	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<10%
CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - <1100) ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	≥2.5-<10%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information: No special measures required.

(Contd. on page 3)

GB

**Safety data sheet
according to UK REACH**

Printing date 22.03.2025

Version number 48 (replaces version 47)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 2)

- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 10

(Contd. on page 4)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 48 (replaces version 47)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 3)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

1675-54-3 bis-[4-(2,3-epoxipropoxy)phenyl]propane

Oral	Consumer, oral, longterm exposition	0.5 mg/kg bw/day (rat)
Dermal	Worker, dermal, shortterm exposition	8.3 mg/kg bw/day
	Worker, dermal, longterm exposition	0.75 mg/kg bw/day (rat)
Inhalative	Consumer, dermal, longterm exposition	0.0893 mg/kg bw/day (rat)
	Worker, inhalative, shortterm exposition	12.3 mg/m ³
	Worker, inhalative, longterm exposition	4.93 mg/m ³ (rat)
	Consumer, inhalative, longterm exposition	0.87 mg/m ³ (rat)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Oral	Consumer, oral, longterm exposition	6.25 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	104.15 mg/kg bw/day
	Consumer, dermal, longterm exposition	62.5 mg/kg bw/day
Inhalative	Worker, inhalative, longterm exposition	29.39 mg/m ³
	Consumer, inhalative, longterm exposition	8.7 mg/m ³

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight >700 - <1100)

Oral	Consumer, oral, longterm exposition	0.5 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	0.75 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	0.0893 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	4.93 mg/m ³ (rat)
	Consumer, inhalative, longterm exposition	0.87 mg/m ³ (rat)

· **PNECs**

1675-54-3 bis-[4-(2,3-epoxipropoxy)phenyl]propane

Oral	Secondary Poisoning	11 mg/kg (rat)
	Fresh water	0.006 mg/l (rat)
	Fresh water sediment	0.341 mg/kg dry weight (rat)
	Marine water	0.001 mg/l (rat)
	Marine sediment	0.034 mg/kg dry weight (rat)
	Soil	0.065 mg/kg (rat)
	Sewage treatment plant	10 mg/l (rat)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

	Fresh water	0.003 mg/l
	Fresh water sediment	0.294 mg/kg dry weight

(Contd. on page 5)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 48 (replaces version 47)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 4)

Marine water	0 mg/l
Marine sediment	0.0294 mg/kg dry weight
Soil	0.237 mg/kg

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Recommended thickness of the material: > 0,12 mm

glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber

Nitrile rubber, NBR

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

· **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· **Eye/face protection**



Tightly sealed goggles

Goggles recommended during refilling

GB

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 48 (replaces version 47)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state	Fluid
· Colour:	Colourless
· Odour:	Weak, characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	>150 °C
· Decomposition temperature:	Not determined.
· pH at 20 °C	6
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	40000 mPas
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.15 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Solvent content:	
· Solids content:	91.0 %
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void

(Contd. on page 7)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 48 (replaces version 47)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 6)

· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

1675-54-3 bis-[4-(2,3-epoxipropoxy)phenyl]propane

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity**
Not applicable.

(Contd. on page 8)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 48 (replaces version 47)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 7)

- Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Sensitisation** Not applicable.
- **Repeated dose toxicity** Not applicable.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
- The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- Also poisonous for fish and plankton in water bodies.
- Toxic for aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Disposal must be made according to official regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 48 (replaces version 47)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 8)

SECTION 14: Transport information

- 14.1 UN number or ID number
- ADR/ADN, IMDG, IATA

UN3082

-

- 14.2 UN proper shipping name
- ADR/ADN

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))

- IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT

- IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))

- 14.3 Transport hazard class(es)

- ADR/ADN



- Class

9 (M6) Miscellaneous dangerous substances and articles.

- Label

9

- IMDG, IATA



- Class

9 Miscellaneous dangerous substances and articles.

- Label

9

- 14.4 Packing group

- ADR/ADN, IMDG, IATA

III

- 14.5 Environmental hazards:

- Marine pollutant:

Symbol (fish and tree)

- Special marking (ADR/ADN):

Symbol (fish and tree)

(Contd. on page 10)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 48 (replaces version 47)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 9)

· Special marking (IATA):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
· Hazard identification number (Kemler code):	90
· EMS Number:	F-A,S-F
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR/ADN	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	(-)
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700), REACTION PRODUCT: BISPHENOL-F-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

(Contd. on page 11)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 48 (replaces version 47)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 10)

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** E2 Hazardous to the Aquatic Environment

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation

Serious eye damage/irritation

Skin sensitisation

Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Department issuing SDS:** PSRA

· **Contact:** PSRA

· **Date of previous version:** 03.02.2025

· **Version number of previous version:** 47

(Contd. on page 12)

GB

**Safety data sheet
according to UK REACH**

Printing date 22.03.2025

Version number 48 (replaces version 47)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 11)

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 28 (replaces version 27)

Revision: 22.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Trade name:** UHU PLUS ENDFEST 300 YE FB 163G*20 L011
 - **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
 - **Application of the substance / the mixture** Adhesive
 - **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
UHU GmbH & Co.KG
Herrmannstraße 7
D-77815 Bühl (Baden)
Tel.: 0049-(0)7223-284-0
E-mail: sds@boltonadhesives.com
Fax: 0049-(0)7223-284-245
 - **Further information obtainable from:** PSRA
 - **1.4 Emergency telephone number:**
Tel.: + 49 (0) 30/19240 (Notruf)
Tel.: + 49 (0) 72 23/28 40
- England and Wales (NHS Direct) 111
Schottland (NHS 24) 111

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS05 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 28 (replaces version 27)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 1)

Amines, polyethylenepoly-, triethylenetetramine fraction

· Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P260 Do not breathe vapours.

P280 Wear protective gloves / eye protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with national regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Adhesive

· Dangerous components:

CAS: 10563-29-8 EINECS: 234-148-4 Reg.nr.: 01-2119970376-29-XXXX	N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Sens. 1B, H317	≥5-≤10%
CAS: 90640-67-8 EINECS: 292-588-2 Reg.nr.: 01-2119487919-13-XXXX	Amines, polyethylenepoly-, triethylenetetramine fraction ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥3-<5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:** Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

GB

**Safety data sheet
according to UK REACH**

Printing date 22.03.2025

Version number 28 (replaces version 27)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
· **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
· **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 8 A
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 28 (replaces version 27)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

10563-29-8 N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

Oral	Consumer, oral, longterm exposition	0.2 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	0.67 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, shortterm exposition	7.5 mg/m ³ (rat)
	Worker, inhalative, longterm exposition	3.7 mg/m ³ (rat)
	Consumer, inhalative, longterm exposition	0.65 mg/m ³ (rat)

90640-67-8 Amines, polyethylenepoly-, triethylenetetramine fraction

Oral	Consumer, oral, longterm exposition	14 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	0.54 mg/m ³ (rat)
	Consumer, inhalative, longterm exposition	0.096 mg/m ³ (rat)

PNECs

10563-29-8 N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

Fresh water	0.092 mg/l (rat)
Fresh water sediment	0.0336 mg/kg dry weight (rat)
Marine water	0.00092 mg/l (rat)
Marine sediment	0.0034 mg/kg dry weight (rat)
Soil	0.0013 mg/kg (rat)
Sewage treatment plant	18.1 mg/l (rat)

90640-67-8 Amines, polyethylenepoly-, triethylenetetramine fraction

Fresh water	0.027 mg/l (rat)
Fresh water sediment	8.572 mg/kg dry weight (rat)
Marine water	0.003 mg/l (rat)
Marine sediment	0.857 mg/kg dry weight (rat)
Soil	1.25 mg/kg (rat)
Sewage treatment plant	0.13 mg/l (rat)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 28 (replaces version 27)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 4)

- **Respiratory protection:** Not required.
- **Recommended filter device for short term use:** Combination filter A-P1
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Recommended thickness of the material: > 0,12 mm

Hand protection Material : butyl-rubber (e.g. Butoject 898: material thickness 0,7 mm)

Break through time : > 8 h

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

glove material for short-term use / splash: (10 min <BTT <480 min): nitrile rubber, neoprene rubber
Nitrile rubber, NBR

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

- **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

- **Eye/face protection**



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Fluid

- **Colour:**

Yellow

- **Odour:**

Amine-like

- **Odour threshold:**

Not determined.

- **Melting point/freezing point:**

Undetermined.

- **Boiling point or initial boiling point and boiling range**

~278 °C

- **Flammability**

Not applicable.

(Contd. on page 6)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 28 (replaces version 27)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 5)

<ul style="list-style-type: none"> · Lower and upper explosion limit · Lower: · Upper: · Flash point: · Decomposition temperature: · pH · Viscosity: · Kinematic viscosity · Dynamic at 20 °C: · Solubility · water: · Partition coefficient n-octanol/water (log value) · Vapour pressure: · Density and/or relative density · Density at 20 °C: · Relative density · Vapour density 	<ul style="list-style-type: none"> Not determined. Not determined. >100 °C Not determined. Not determined. Not determined. Not determined. 32500 mPas Not miscible or difficult to mix. Not determined. Not determined. 0.95 g/cm³ Not determined. Not determined.
<ul style="list-style-type: none"> · 9.2 Other information · Appearance: · Form: · Important information on protection of health and environment, and on safety. · Ignition temperature: · Explosive properties: · Solvent content: · Solids content: · Change in condition · Evaporation rate 	<ul style="list-style-type: none"> All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture. Fluid Product is not selfigniting. Product does not present an explosion hazard. 84.2 % Not determined.
<ul style="list-style-type: none"> · Information with regard to physical hazard classes · Explosives · Flammable gases · Aerosols · Oxidising gases · Gases under pressure · Flammable liquids · Flammable solids · Self-reactive substances and mixtures · Pyrophoric liquids · Pyrophoric solids · Self-heating substances and mixtures · Substances and mixtures, which emit flammable gases in contact with water · Oxidising liquids · Oxidising solids 	<ul style="list-style-type: none"> Void Void Void Void Void Void Void Void Void Void Void Void Void Void Void

(Contd. on page 7)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 28 (replaces version 27)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 6)

- | | |
|----------------------------------|------|
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

10563-29-8 N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

Oral	LD50	1669 mg/kg (rat)
------	------	------------------

90640-67-8 Amines, polyethylenepoly-, triethylenetetramine fraction

Oral	LD50	1716.2 mg/kg (rat)
------	------	--------------------

Dermal	LD50	1465.4 mg/kg (rabbit)
--------	------	-----------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity**
Not applicable.
Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Sensitisation** Not applicable.
- **Repeated dose toxicity** Not applicable.

(Contd. on page 8)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 28 (replaces version 27)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 7)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· **Aquatic toxicity:** No further relevant information available.

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· Uncleaned packaging:

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR/ADN, IMDG, IATA

UN2735

· 14.2 UN proper shipping name

· ADR/ADN

2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine)

· IMDG, IATA

POLYAMINES, LIQUID, CORROSIVE, N.O.S. (N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine)

(Contd. on page 9)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 28 (replaces version 27)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR/ADN



· **Class** 8 (C7) Corrosive substances.
· **Label** 8

· IMDG, IATA



· **Class** 8 Corrosive substances.
· **Label** 8

· 14.4 Packing group

· **ADR/ADN, IMDG, IATA** III

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user** Warning: Corrosive substances.

· **Hazard identification number (Kemler code):** 80

· **EMS Number:** F-A,S-B

· **Segregation groups** (SGG18) Alkalis

· **Stowage Category** B

· **Stowage Code** SW2 Clear of living quarters.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· Transport/Additional information:

· **Quantity limitations** On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

· ADR/ADN

· **Limited quantities (LQ)** 5L

· **Excepted quantities (EQ)** Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Transport category** 3

· **Tunnel restriction code** E

· IMDG

· **Limited quantities (LQ)** 5L

(Contd. on page 10)

GB

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 28 (replaces version 27)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 9)

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (N'-(3-AMINOPROPYL)-N,N-DIMETHYLPROPANE-1,3-DIAMINE), 8, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 11)

Safety data sheet according to UK REACH

Printing date 22.03.2025

Version number 28 (replaces version 27)

Revision: 22.03.2025

Trade name: UHU PLUS ENDFEST 300 YE FB 163G*20 L011

(Contd. of page 10)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
Serious eye damage/irritation	
Skin sensitisation	

· Department issuing SDS: PSRA

· Contact: PSRA

· Date of previous version: 04.02.2025

· Version number of previous version: 27

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB