

# Technical data sheet



Product: SAFETY-WALK

Manufacturer: 3M DEUTSCHLAND GMBH

Product group: ARBEITSSCHUTZ

Article group: SAFETY-WALK

Download: 11.03.2026

## 3M™ SAFETY-WALK™ EDGING COMPOUND - EU

This data sheet was provided to you by Tewipack Uhl GmbH. The company tewipack Uhl GmbH assumes no responsibility for the topicality and the Accuracy of the information contained. The properties of the products can vary due to various influences such as composition and condition of the Substrate, impurities in or on the substrate, temperature and humidity at the Change storage and environmental conditions during use. Using this product in combination with other material, the customer is responsible for to check through our own tests whether the product is suitable for the planned combination and whether this combination delivers the expected results

Tewipack Uhl GmbH  
Industriestraße 15  
D-75382 Althengstett

Telephone:  
+49(0)7051/9297-0  
Fax:  
+49(0)7051/9297-99

E-Mail:  
info@tewipack.de  
Website:  
www.tewipack.de

Managing director:  
Alexander Uhl,  
Michael Uhl  
HRB 330424  
Amtsgericht  
Stuttgart

Bank details:  
Sparkasse  
Sindelfingen  
Pforzheim  
Calw  
BLZ 666 500  
85  
Konto 17 787

Commerzbank  
Sindelfingen  
BLZ 603 400 71  
Konto 8 001 166

Vereinigte  
Volksbank AG  
Böblingen  
BLZ 603 900 00  
Konto 80 089  
003

Postbank  
Stuttgart  
BLZ 600 100  
70  
Konto 146  
294 708

## Product Description

3M™ Safety-Walk™ Edging Compound is a liquid, solvent-based compound in a convenient tube applicator. The product fills in the exposed edges of Safety-Walk slip-resistant materials, providing extra protection at the edges from excessive moisture or liquids.

## Product Line

3M™ Safety-Walk™ Edging Compound

Size: tube (147 ml)

One tube (147 ml) seals approximately 23 m – 30 m

## Characteristics

These are typical values for unprocessed product.

Characteristics	Value
Base	Synthetic resin
Colour	Clear
Net weight	7.0 - 7.4 lbs./gallon 0.83 kg/l - 0.88 kg/l
Solids content	43% – 47%
Consistency	Thin syrup
Flash point	+4°C
Viscosity	3200 cps - 5200 cps
Brookfield Viscometer	RVF #4 sp. @ 10 rpm
Tack free time	10 – 15 minutes
Dry time	1 -2 days

## Flammability

Flammability standards are different from country to country. Ask your local 3M contact for details, please.

## Directions for Use

### Surface Preparation

Make sure surface is clean, dry, smooth when applying 3M™ Safety-Walk™ Edging Compound. Repair or replace any broken or damaged surface.

### Application

Apply 3M™ Safety-Walk™ Edging Compound by evenly squeezing the tube and running the nozzle along the edges between the Safety-Walk™ tapes/treads and the substrate. The edge protection must cover both the 3M™ Safety-Walk™ Edging Compound and the substrate. A hand applicator or brush may also be used.

## Limited Remedy

### Unsuitable End Uses

This bulletin provides technical information only.

3M recommended product end uses are listed in each 3M product bulletin. End uses not listed in the applicable 3M Product Bulletins are typically not eligible for 3M Warranties. For non-recommended and/or non-warranted end uses or applications, users must test and approve the end uses or applications, assume any associated risks, and acknowledge that 3M has no liability for such end uses or applications. Please contact your 3M representative with any questions about applications, end uses, and warranties.

### Limitations of liability

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.

## Shelf Life and Storage

The shelf life as defined below remains an indicative and maximum data, subject to many external and non-controllable factors. It may never be interpreted as warranty.

The shelf life is never more than 5 years from the date of shipping from manufacturer.

Storage conditions: +16°C to +27°C, out of sunlight, original container in clean and dry area.

## Health and Safety

When handling any chemical products, read the manufacturer's container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information.

Follow the link to obtain SDS sheets for 3M products on [3M.com/SDS](https://www.3m.com/SDS).

IMPORTANT! When using any equipment, always follow the manufacturer's instructions for safe operation.

3M and Safety-Walk are trademarks of 3M. All other trademarks are the property of their respective owners.

#### 3M United Kingdom PLC

Commercial Solutions Division

Cain Road

Bracknell, RG12 8HT

UK

[www.3m.co.uk/graphics-and-signage-uk/](https://www.3m.co.uk/graphics-and-signage-uk/)

#### 3M Ireland (Dublin)

The Iveagh Building

The Park, Carrickmines

Dublin 18

Ireland

[www.3m.couk/graphics-and-signage-uk/](https://www.3m.couk/graphics-and-signage-uk/)

© 3M 2021. All rights reserved.